Appendix F

Noise Calculations

Noise Calculations for Airport Perimeter Dike FEMA and Seismic Improvement Project

Mechanical-Construction Airport Site		
Construction Equipment 1 (Drill Rig)	95	dBA at 50 feet
Construction Equipment 2 (Excavator/Dozer/Paver/Roller)	85	dBA at 50 feet
Combined Daytime Noise at 50 feet (Ltotal at 50 feet)	95.4	dBA
Ltotal=10 log(10^L1/10+10^L2/10)		

Noise Threshold Limits and Distances from Project Sites to those Limits for Construction Equipment by Technique

		Distance to Leq Threshold from Middle of Project Site (feet)
Noise Threshold	- Leq (dBA)	Mechanical
Sensitive Receptors	100	29.5
	75	524.4
Source: FTA 2018		

Noise Level at Nearest Sensitive Receptor	Distance (ft)	Noise Level
Commercial Property Along Harbor Bay Parkway	400	77.4

Vibration Source Levels for Construction Equipment (FTA 2018)

Equipment	PPV at 25 feet	VBA
Large Bulldozer	0.089	87

Vibration Calculations with Equations for Vibration-Causing Equipment for Project Site

	Distance to	
	Threshold from	
	Middle of	
	Project Site	
Threshold	(feet)	Notes
		Building damage threshold (sensitive
PPV=PPVref * (25/d)^1.5	20.5	buildings)

Noise Calculations for Airport Perimeter Dike FEMA and Seismic Improvement Project

Mechanical-Construction NPORDS Site		
Construction Equipment 2 (Excavator/Dozer/Paver/Roller)	85	dBA at 50 feet
Construction Equipment 2 (Excavator/Dozer/Paver/Roller)	85	dBA at 50 feet
Combined Daytime Noise at 50 feet (Ltotal at 50 feet)	88.0	dBA
Ltotal=10 log(10^L1/10+10^L2/10)		

Noise Threshold Limits and Distances from Project Sites to those Limits for Construction Equipment by Technique

Noise Threshold Elinics and Distances from Troject Sites to those Elinics for Community Teaming		
		Distance to Leq Threshold from Middle of Project Site (feet)
Noise Threshold	Threshold Level - Leq (dBA)	Mechanical
Sensitive Receptors	100	12.6
	75	223.6
Source: FTA 2018	·	·

Noise Level at Nearest Sensitive Receptor	Distance (ft)	Noise Level
Spunkmeyer Field	200	76.0
Corica Park golf Course	500	68.0