



City of Victorville

Department of Development

Planning ♦ Building ♦ Code Enforcement

14343 Civic Drive
PO Box 5001
Victorville, CA 92393-5001
(760) 955-5135
Fax (760) 269-0070
planning@victorvilleca.gov

Greenhouse as Emissions Screening Table Review

Note: This form is to be used only for projects which are subject to CEQA and not exempt from CEQA (i.e. Negative Declaration, Mitigated Negative Declaration or Environmental Impact Report).

GENERAL INFORMATION

Applicant: Tanner Family Trust Contact Name: Frank Tanner, Trustee

Address: 2501 Markwood Street, Duarte, CA. 91010

Telephone No.: _____ Email Address: _____

TYPE OF PROJECT

Residential (Single-Family or Multi-Family) Commercial or Industrial

PROJECT LOCATION

General Location/Address of Project: Eucalyptus Street and Topaz Road

Name of Business (if applicable): _____

Assessor's Parcel No(s): 0405-322-08 & 0405-322-09

Existing Zoning: R-1T

PROJECT DESCRIPTION:

Vesting Tentative Map – Tract No. 20386 65 Lots Single Family Residential - each parcel approx. 7,200 sf.

Instructions

1. Fill out the appropriate section below for either Residential or Commercial/Industrial.
2. Choose items which the proposed project will incorporate into the development to reach a minimum of 45 points.
3. Do not chose items which are independently required by other laws, codes or the VVMC, such as the California Building Green Code, the Civic Center Sustainability Plan or required infrastructure improvements.
4. For those items listed with a TBD point value, please provide specific information and background studies (i.e. traffic study) for Staff to determine an assigned point value.
5. Submit the Screening Table along with the Planning Commission Review Application.

Residential Section

Feature	Description	Assigned Point Values	Project Points
Reduction Measure PS E1: Residential Energy Efficiency			
Building Envelope			
Insulation	2008 Baseline (walls R-13.; roof/attic: R-30)	0 points	12
	Modestly Enhanced Insulation (walls R-13.; roof/attic: R-38)	12 points	
	Enhanced Insulation (rigid wall insulation R-13, roof/attic: R-38)	15 points	
	Greatly Enhanced Insulation (spray foam wall insulated walls R-15 or higher, roof/attic R-38 or higher)	18 points	
Windows	2008 Baseline Windows (0.57 U-factor, 0.4 solar heat gain coefficient (SHGC))	0 points	6
	Modestly Enhanced Window Insulation (0.4 U-Factor, 0.32 SHGC)	6 points	
	Enhanced Window Insulation (0.32 U-Factor, 0.25 SHGC)	7 points	
	Greatly Enhanced Window Insulation (0.28 or less U-Factor, 0.22 or less SHGC)	9 points	
Cool Roof	Modest Cool Roof (CRRC Rated 0.15 aged solar reflectance, 0.75 thermal emittance)	10 points	10
	Enhanced Cool Roof(CRRC Rated 0.2 aged solar reflectance, 0.75 thermal emittance)	12 points	
	Greatly Enhanced Cool Roof (CRRC Rated 0.35 aged solar reflectance, 0.75 thermal emittance)	14 points	
Air Infiltration	Minimizing leaks in the building envelope is as important as the insulation properties of the building. Insulation does not work effectively if there is excess air leakage.		
	Air barrier applied to exterior walls, caulking, and visual inspection such as the HERS Verified Quality Insulation Installation (QII or equivalent)	10 points	
	Blower Door HERS Verified Envelope Leakage or equivalent	8 points	
Thermal Storage of Building	Thermal storage is a design characteristic that helps keep a constant temperature in the building. Common thermal storage devices include strategically placed water filled columns, water storage tanks, and thick masonry walls.		
	Modest Thermal Mass (10% of floor or 10% of walls: 12" or more thick exposed concrete or masonry. No permanently installed floor covering such as carpet, linoleum, wood or other insulating materials)	2 points	
	Enhanced Thermal Mass (20% of floor or 20% of walls: 12" or more thick exposed concrete or masonry. No permanently installed floor covering such as carpet, linoleum, wood or other insulating materials)	4 points	

Feature	Description	Assigned Point Values	Project Points
Indoor Space Efficiencies			
Heating/ Cooling Distribution System	Minimum Duct Insulation (R-4.2 required)	0 points	
	Modest Duct insulation (R-6)	7 points	
	Enhanced Duct Insulation (R-8)	8 points	
	Distribution loss reduction with inspection (HERS Verified Duct Leakage or equivalent)	12 points	
Space Heating/ Cooling Equipment	2008 Minimum HVAC Efficiency (SEER 13/75% AFUE or 7.7 HSPF)	0 points	4
	Improved Efficiency HVAC (SEER 14/78% AFUE or 8 HSPF)	4 points	
	High Efficiency HVAC (SEER 15/80% AFUE or 8.5 HSPF)	7 points	
	Very High Efficiency HVAC (SEER 16/82% AFUE or 9 HSPF)	9 points	
Water Heaters	2008 Minimum Efficiency (0.57 Energy Factor)	0 points	12
	Improved Efficiency Water Heater (0.675 Energy Factor)	12 points	
	High Efficiency Water Heater (0.72 Energy Factor)	15 points	
	Very High Efficiency Water Heater (0.92 Energy Factor)	18 points	
	Solar Pre-heat System (0.2 Net Solar Fraction)	4 points	
	Enhanced Solar Pre-heat System (0.35 Net Solar Fraction)	8 points	
Daylighting	Daylighting is the ability of each room within the building to provide outside light during the day reducing the need for artificial lighting during daylight hours.		
	All peripheral rooms within the living space have at least one window (required)	0 points	
	All rooms within the living space have daylight (through use of windows, solar tubes, skylights, etc.)	1 points	
	All rooms daylighted	2 points	
Artificial Lighting	2008 Minimum (required)	0 points	8
	Efficient Lights (25% of in-unit fixtures considered high efficacy. High efficacy is defined as 40 lumens/watt for 15 watt or less fixtures; 50 lumens/watt for 15-40 watt fixtures, 60 lumens/watt for fixtures >40watt)	8 points	
	High Efficiency Lights (50% of in-unit fixtures are high efficacy)	10 points	
	Very High Efficiency Lights (100% of in-unit fixtures are high efficacy)	12 points	
Appliances	Energy Star Refrigerator (new)	1 points	2
	Energy Star Dish Washer (new)	1 points	

Feature	Description	Assigned Point Values	Project Points
	Energy Star Washing Machine (new)	1 points	
Miscellaneous Residential Building Efficiencies			
Building Placement	North/South alignment of building or other building placement such that the orientation of the buildings optimizes natural heating, cooling, and lighting.	5 point	5
Shading	At least 90% of south-facing glazing will be shaded by vegetation or overhangs at noon on Jun 21 st .	4 Points	
Energy Star Homes	EPA Energy Star for Homes (version 3 or above)	25 points	
Independent Energy Efficiency Calculations	Provide point values based upon energy efficiency modeling of the Project. Note that engineering data will be required documenting the energy efficiency and point values based upon the proven efficiency beyond Title 24 Energy Efficiency Standards.	TBD	
Other	This allows innovation by the applicant to provide design features that increases the energy efficiency of the project not provided in the table. Note that engineering data will be required documenting the energy efficiency of innovative designs and point values given based upon the proven efficiency beyond Title 24 Energy Efficiency Standards.	TBD	
Existing Residential Retrofits	<p>The applicant may wish to provide energy efficiency retrofit projects to existing residential dwelling units to further the point value of their project. Retrofitting existing residential dwelling units within the City is a key reduction measure that is needed to reach the reduction goal. The potential for an applicant to take advantage of this program will be decided on a case by case basis and must have the approval of the City Planning Department. The decision to allow applicants to ability to participate in this program will be evaluated based upon, but not limited to the following;</p> <p>Will the energy efficiency retrofit project benefit low income or disadvantaged residents?</p> <p>Does the energy efficiency retrofit project fit within the overall assumptions in reduction measures associated with existing residential retrofits?</p> <p>Does the energy efficiency retrofit project provide co-benefits important to the City?</p> <p>Point value will be determined based upon engineering and design criteria of the energy efficiency retrofit project.</p>	TBD	
Reduction Measure PS E2: Residential Renewable Energy Generation			
Photovoltaic	<p>Solar Photovoltaic panels installed on individual homes or in collective neighborhood arrangements such that the total power provided augments:</p> <p>Solar Ready Homes (sturdy roof and solar ready service panel)</p> <p>10 percent of the power needs of the project</p> <p>20 percent of the power needs of the project</p> <p>30 percent of the power needs of the project</p> <p>40 percent of the power needs of the project</p>	<p>2 points</p> <p>10 points</p> <p>15 points</p> <p>20 points</p> <p>28 points</p>	2

Feature	Description	Assigned Point Values	Project Points
	50 percent of the power needs of the project 60 percent of the power needs of the project 70 percent of the power needs of the project 80 percent of the power needs of the project 90 percent of the power needs of the project 100 percent of the power needs of the project	35 points 38 points 42 points 46 points 52 points 58 points	
Wind turbines	<p>Some areas of the City lend themselves to wind turbine applications. Analysis of the area’s capability to support wind turbines should be evaluated prior to choosing this feature.</p> <p>Individual wind turbines at homes or collective neighborhood arrangements of wind turbines such that the total power provided augments:</p> 10 percent of the power needs of the project 20 percent of the power needs of the project 30 percent of the power needs of the project 40 percent of the power needs of the project 50 percent of the power needs of the project 60 percent of the power needs of the project 70 percent of the power needs of the project 80 percent of the power needs of the project 90 percent of the power needs of the project 100 percent of the power needs of the project	10 points 15 points 20 points 28 points 35 points 38 points 42 points 46 points 52 points 58 points	
Off-site renewable energy project	<p>The applicant may submit a proposal to supply an off-site renewable energy project such as renewable energy retrofits of existing homes that will help implement renewable energy within the City. These off-site renewable energy retrofit project proposals will be determined on a case by case basis and must be accompanied by a detailed plan that documents the quantity of renewable energy the proposal will generate. Point values will be determined based upon the energy generated by the proposal.</p>	TBD	
Other Renewable Energy Generation	<p>The applicant may have innovative designs or unique site circumstances (such as geothermal) that allow the project to generate electricity from renewable energy not provided in the table. The ability to supply other renewable energy and the point values allowed will be decided based upon engineering data documenting the ability to generate electricity.</p>	TBD	

Feature	Description	Assigned Point Values	Project Points
Reduction Measure PS W1: Residential Water Conservation			
Irrigation and Landscaping			
Water Efficient Landscaping	Limit conventional turf to < 50% of required landscape area	0 points	
	No conventional turf (warm season turf to < 50% of required landscape area and/or low water using plants are allowed)	4 points	
	Only California Native Plants that requires no irrigation or some supplemental irrigation	6 points	
Water Efficient irrigation systems	Low precipitation spray heads < .75"/hr or drip irrigation	8 points	
	Weather based irrigation control systems or moisture sensors (demonstrate 20% reduced water use)	2 point	
Recycled Water	Recycled connections (purple pipe) to irrigation system on site	3 points	
Water Reuse	Gray water Reuse System collects Gray water from clothes washers, showers and faucets for irrigation use,	6 points	
Storm water Reuse Systems	Innovative on-site stormwater collection, filtration and reuse systems are being developed that provide supplemental irrigation water and provide vector control. These systems can greatly reduce the irrigation needs of a project. Point values for these types of systems will be determined based upon design and engineering data documenting the water savings.	12 points	
Potable Water			
Showers	Water Efficient Showerheads (2.0 gpm)	TBD	
Toilets	Water Efficient Toilets (1.5 gpm)	3 points	3
Faucets	Water Efficient faucets (1.28 gpm)	3 points	3
Dishwasher	Water Efficient Dishwasher (6 gallons per cycle or less)	3 points	
Washing Machine	Water Efficient Washing Machine (Water factor <5.5)	1	
WaterSense	EPA WaterSense Certification	1	
Reduction Measure PS T1: Land Use Based Trips and VMT Reduction			
Mixed Use	Mixes of land uses that complement one another in a way that reduces the need for vehicle trips can greatly reduce GHG emissions. The point value of mixed use projects will be determined based upon a Transportation Impact Analysis (TIA) demonstrating trip reductions and/or reductions in vehicle	12 points	

Feature	Description	Assigned Point Values	Project Points
	miles traveled. Suggested ranges: Diversity of land uses complementing each other (2-28 points) Increased destination accessibility other than transit (1-18 points) Increased transit accessibility (1-25 points) Infill location that reduces vehicle trips or VMT beyond the measures described above (points TBD based on traffic data).		
Residential Near Local Retail (Residential only Projects)	Having residential developments within walking and biking distance of local retail helps to reduce vehicle trips and/or vehicle miles traveled. The point value of residential projects in close proximity to local retail will be determined based upon traffic studies that demonstrate trip reductions and/or reductions in vehicle miles traveled (VMT)	TBD	
Other Trip Reduction Measures	Other trip or VMT reduction measures not listed above with TIA and/or other traffic data supporting the trip and/or VMT for the project.	TBD	
Reduction Measure PS T2: Bicycle Infrastructure			
Bicycle Infrastructure	. Provide bicycle paths within project boundaries. Provide bicycle path linkages between residential and other land uses. Provide bicycle path linkages between residential and transit.	TBD 2 points 5 points	
Reduction Measure PS T3: Neighborhood Electric Vehicle Infrastructure			
Electric Vehicle Recharging	Provide circuit and capacity in garages of residential units for use by an electric vehicle. Charging stations are for on-road electric vehicles legally able to drive on all roadways including Interstate Highways and freeways. Install electric vehicle charging stations in the garages of residential units	1 point 8 points	
Total Points Earned by Residential Project:			70

-Residential Section Ends-

Commercial/Industrial Section

Feature	Description	Assigned Point Values	Project Points
Reduction Measure PS E3: Commercial/Industrial Energy Efficiency Development			
Building Envelope			
Insulation	2008 baseline (walls R-13; roof/attic R-30)	0 points	
	Modestly Enhanced Insulation (walls R-13, roof/attic R-38))	15 points	
	Enhanced Insulation (rigid wall insulation R-13, roof/attic R-38)	18 points	
	Greatly Enhanced Insulation (spray foam insulated walls R-15 or higher, roof/attic R-38 or higher)	20 points	
Windows	2008 Baseline Windows (0.57 U-factor, 0.4 solar heat gain coefficient [SHGC])	0 points	
	Modestly Enhanced Window Insulation (0.4 U-factor, 0.32 SHGC)	7 points	
	Enhanced Window Insulation (0.32 U-factor, 0.25 SHGC)	8 points	
	Greatly Enhanced Window Insulation (0.28 or less U-factor, 0.22 or less SHGC)	12 points	
Cool Roof	Modest Cool Roof (CRRR Rated 0.15 aged solar reflectance, 0.75 thermal emittance)	12 points	
	Enhanced Cool Roof (CRRR Rated 0.2 aged solar reflectance, 0.75 thermal emittance)	14 points	
	Greatly Enhanced Cool Roof (CRRR Rated 0.35 aged solar reflectance, 0.75 thermal emittance)	16 points	
Air Infiltration	Minimizing leaks in the building envelope is as important as the insulation properties of the building. Insulation does not work effectively if there is excess air leakage.		
	Air barrier applied to exterior walls, calking, and visual inspection such as the HERS Verified Quality Insulation Installation (QII or equivalent)	12 points	
	Blower Door HERS Verified Envelope Leakage or equivalent	10 points	
Thermal Storage of Building	Thermal storage is a design characteristic that helps keep a constant temperature in the building. Common thermal storage devices include strategically placed water filled columns, water storage tanks, and thick masonry walls.		
	Modest Thermal Mass (10% of floor or 10% of walls 12" or more thick exposed concrete or masonry with no permanently installed floor covering such as carpet, linoleum, wood or other insulating materials)	4 points	
	Enhanced Thermal Mass (20% of floor or 20% of walls 12" or more thick	6 points	

Feature	Description	Assigned Point Values	Project Points
	<p>exposed concrete or masonry with no permanently installed floor covering such as carpet, linoleum, wood or other insulating materials)</p> <p>Enhanced Thermal Mass (80% of floor or 80% of walls 12" or more thick exposed concrete or masonry with no permanently installed floor covering such as carpet, linoleum, wood or other insulating materials)</p>	24 points	
Indoor Space Efficiencies			
Heating/ Cooling Distribution System	<p>Minimum Duct Insulation (R-4.2 required)</p> <p>Modest Duct insulation (R-6)</p> <p>Enhanced Duct Insulation (R-8)</p> <p>Distribution loss reduction with inspection (HERS Verified Duct Leakage or equivalent)</p>	<p>0 points</p> <p>8 points</p> <p>10 points</p> <p>14 points</p>	
Space Heating/ Cooling Equipment	<p>2008 Minimum HVAC Efficiency (EER 13/75% AFUE or 7.7 HSPF)</p> <p>Improved Efficiency HVAC (EER 14/78% AFUE or 8 HSPF)</p> <p>High Efficiency HVAC (EER 15/80% AFUE or 8.5 HSPF)</p> <p>Very High Efficiency HVAC (EER 16/82% AFUE or 9 HSPF)</p>	<p>0 points</p> <p>7 points</p> <p>8 points</p> <p>12 points</p>	
Commercial Heat Recovery Systems	Heat recovery strategies employed with commercial laundry, cooking equipment, and other commercial heat sources for reuse in HVAC air intake or other appropriate heat recovery technology. Point values for these types of systems will be determined based upon design and engineering data documenting the energy savings.	TBD	
Water Heaters	<p>2008 Minimum Efficiency (0.57 Energy Factor)</p> <p>Improved Efficiency Water Heater (0.675 Energy Factor)</p> <p>High Efficiency Water Heater (0.72 Energy Factor)</p>	<p>0 points</p> <p>14 points</p> <p>16 points</p>	
	<p>Very High Efficiency Water Heater (0.92 Energy Factor)</p> <p>Solar Pre-heat System (0.2 Net Solar Fraction)</p> <p>Enhanced Solar Pre-heat System (0.35 Net Solar Fraction)</p>	<p>19 points</p> <p>4 points</p> <p>8 points</p>	
Daylighting	<p>Daylighting is the ability of each room within the building to provide outside light during the day reducing the need for artificial lighting during daylight hours.</p> <p>All peripheral rooms within building have at least one window or skylight</p> <p>All rooms within building have daylight (through use of windows, solar tubes, skylights, etc.)</p> <p>All rooms daylighted</p>	<p>1 points</p> <p>5 points</p> <p>7 points</p>	

Feature	Description	Assigned Point Values	Project Points
Artificial Lighting	2008 Minimum (required) Efficient Lights (25% of in-unit fixtures considered high efficacy. High efficacy is defined as 40 lumens/watt for 15 watt or less fixtures; 50 lumens/watt for 15-40 watt fixtures, 60 lumens/watt for fixtures >40watt) High Efficiency Lights (50% of in-unit fixtures are high efficacy) Very High Efficiency Lights (100% of in-unit fixtures are high efficacy)	0 points 9 points 12 points 14 points	
Appliances	Star Commercial Refrigerator (new) Energy Star Commercial Dish Washer (new) Energy Star Commercial Cloths Washing	4 points 4 points 4 points	
Miscellaneous Commercial/Industrial Building Efficiencies			
Building Placement	North/South alignment of building or other building placement such that the orientation of the buildings optimizes conditions for natural heating, cooling, and lighting.	6 point	
Shading	At least 90% of south-facing glazing will be shaded by vegetation or overhangs at noon on Jun 21st.	6 Points	
Other	This allows innovation by the applicant to provide design features that increases the energy efficiency of the project not provided in the table. Note that engineering data will be required documenting the energy efficiency of innovative designs and point values given based upon the proven efficiency beyond Title 24 Energy Efficiency Standards.	TBD	
Existing Commercial building Retrofits	<p>The applicant may wish to provide energy efficiency retrofit projects to existing commercial buildings to further the point value of their project. Retrofitting existing commercial buildings within the City is a key reduction measure that is needed to reach the reduction goal. The potential for an applicant to take advantage of this program will be decided on a case by case basis and must have the approval of the City Planning Department. The decision to allow applicants to ability to participate in this program will be evaluated based upon, but not limited to the following:</p> <p>Will the energy efficiency retrofit project benefit low income or disadvantaged communities?</p> <p>Does the energy efficiency retrofit project fit within the overall assumptions in the reduction measure associated with commercial building energy efficiency retrofits?</p>	TBD	

Feature	Description	Assigned Point Values	Project Points
	<p>Does the energy efficiency retrofit project provide co-benefits important to the City?</p> <p>Point value will be determined based upon engineering and design criteria of the energy efficiency retrofit project.</p>		
Reduction Measure PS E4: Commercial/Industrial Renewable Energy			
Photovoltaic	<p>Solar Photovoltaic panels installed on commercial buildings or in collective arrangements within a commercial development such that the total power provided augments:</p> <p>Solar Ready Roofs (sturdy roof and electric hookups)</p> <p>10 percent of the power needs of the project</p> <p>20 percent of the power needs of the project</p> <p>30 percent of the power needs of the project</p> <p>40 percent of the power needs of the project</p> <p>50 percent of the power needs of the project</p> <p>60 percent of the power needs of the project</p> <p>70 percent of the power needs of the project</p> <p>80 percent of the power needs of the project</p> <p>90 percent of the power needs of the project</p> <p>100 percent of the power needs of the project</p>	<p>2 points</p> <p>8 points</p> <p>14 points</p> <p>20 points</p> <p>26 points</p> <p>32 points</p> <p>38 points</p> <p>44 points</p> <p>50 points</p> <p>56 points</p> <p>60 points</p>	
Wind turbines	<p>Some areas of the City lend themselves to wind turbine applications. Analysis of the areas capability to support wind turbines should be evaluated prior to choosing this feature.</p> <p>Wind turbines as part of the commercial development such that the total power provided augments:</p>		
	<p>10 percent of the power needs of the project</p> <p>20 percent of the power needs of the project</p> <p>30 percent of the power needs of the project</p> <p>40 percent of the power needs of the project</p> <p>50 percent of the power needs of the project</p> <p>60 percent of the power needs of the project</p> <p>70 percent of the power needs of the project</p> <p>80 percent of the power needs of the project</p> <p>90 percent of the power needs of the project</p> <p>100 percent of the power needs of the project</p>	<p>8 points</p> <p>14 points</p> <p>20 points</p> <p>26 points</p> <p>32 points</p> <p>38 points</p> <p>44 points</p> <p>50 points</p> <p>56 points</p> <p>60 points</p>	

Feature	Description	Assigned Point Values	Project Points
Off-site renewable energy project	The applicant may submit a proposal to supply an off-site renewable energy project such as renewable energy retrofits of existing commercial/industrial that will help implement reduction measures associated with existing buildings. These off-site renewable energy retrofit project proposals will be determined on a case by case basis accompanied by a detailed plan documenting the quantity of renewable energy the proposal will generate. Point values will be based upon the energy generated by the proposal.	TBD	
Other Renewable Energy Generation	The applicant may have innovative designs or unique site circumstances (such as geothermal) that allow the project to generate electricity from renewable energy not provided in the table. The ability to supply other renewable energy and the point values allowed will be decided based upon engineering data documenting the ability to generate electricity.	TBD	
Reduction Measure PS W2: Commercial/Industrial Water Conservation			
Irrigation and Landscaping			
Water Efficient Landscaping	Eliminate conventional turf from landscaping Only moderate water using plants Only low water using plants Only California Native landscape that requires no or only supplemental irrigation	0 points 3 points 4 points 8 points	
Trees	Increase tree planting in parking areas 50% beyond City Code requirements	TBD	
Water Efficient irrigation systems	Low precipitation spray heads < .75"/hr or drip irrigation Weather based irrigation control systems combined with drip irrigation (demonstrate 20 reduced water use)	1 point 5 points	
Recycled Water	Recycled water connection (purple pipe) to irrigation system on site	5 points	
Storm water Reuse Systems	Innovative on-site stormwater collection, filtration and reuse systems are being developed that provide supplemental irrigation water and provide vector control. These systems can greatly reduce the irrigation needs of a project. Point values for these types of systems will be determined based upon design and engineering data documenting the water savings.	TBD	

Feature	Description	Assigned Point Values	Project Points
Potable Water			
Showers	Water Efficient Showerheads (2.0 gpm)	3 points	
Toilets	Water Efficient Toilets/Urinals (1.5gpm) Waterless Urinals (note that commercial buildings having both waterless urinals and high efficiency toilets will have a combined point value of 6 points)	3 points 4 points	
Faucets	Water Efficient faucets (1.28gpm)	3 points	
Commercial Dishwashers	Water Efficient dishwashers (20% water savings)	4 points	
Commercial Laundry Washers	Water Efficient laundry (15% water savings) High Efficiency laundry Equipment that captures and reuses rinse water (30% water savings)	3 points 6 points	
Commercial Water Operations Program	Establish an operational program to reduce water loss from pools, water features, etc., by covering pools, adjusting fountain operational hours, and using water treatment to reduce draw down and replacement of water. Point values for these types of plans will be determined based upon design and engineering data documenting the water savings.	TBD	
Reduction Measure PS T1: Land Use Based Trips and VMT Reduction			
Mixed Use	Mixes of land uses that complement one another in a way that reduces the need for vehicle trips can greatly reduce GHG emissions. The point value of mixed use projects will be determined based upon traffic studies that demonstrate trip reductions and/or reductions in vehicle miles traveled	TBD	
Local Retail Near Residential (Commercial only Projects)	Having residential developments within walking and biking distance of local retail helps to reduce vehicle trips and/or vehicle miles traveled. The point value of residential projects in close proximity to local retail will be determined based upon traffic studies that demonstrate trip reductions and/or reductions in vehicle miles traveled	TBD	
Reduction Measure PS T2: Bicycle Infrastructure			
Bicycle Infrastructure	Provide bicycle paths within project boundaries. Provide bicycle path linkages between project site and other land uses. Provide bicycle path linkages between project site and transit.	TBD 2 points 5 points	
Reduction Measure PS T3: Electric Vehicle Infrastructure			
Electric Vehicles	Provide public charging station for use by an electric vehicle (ten points for each charging station within the facility).	10 points	

Feature	Description	Assigned Point Values	Project Points
Reduction Measure PS T4: Employee Based Trip &VMT Reduction Policy			
Compressed Work Week	<p>Reduce the number of days per week that employees need to be on site will reduce the number of vehicle trips associated with commercial/industrial development. Compressed work week such that full time employees are on site:</p> <p>5 days per week</p> <p>4 days per week on site</p> <p>3 days per week on site</p>	TBD	
Car/Vanpools	<p>Car/vanpool program</p> <p>Car/vanpool program with preferred parking</p> <p>Car/vanpool with guaranteed ride home program</p> <p>Subsidized employee incentive car/vanpool program</p> <p>Combination of all the above</p>	TBD	
Employee Bicycle/ Pedestrian Programs	<p>Complete sidewalk to residential within ½ mile</p> <p>Complete bike path to residential within 3 miles</p> <p>Bike lockers and secure racks</p> <p>Showers and changing facilities</p> <p>Subsidized employee walk/bike program</p> <p>(Note combine all applicable points for total value)</p>	TBD	
Shuttle/Transit Programs	<p>Local transit within ¼ mile</p> <p>Light rail transit within ½ mile</p> <p>Shuttle service to light rail transit station</p> <p>Guaranteed ride home program</p> <p>Subsidized Transit passes</p> <p>Note combine all applicable points for total value</p>	TBD	
CRT	<p>Employer based Commute Trip Reduction (CRT). CRTs apply to commercial, offices, or industrial projects that include a reduction of vehicle trip or VMT goal using a variety of employee commutes trip reduction methods. The point value will be determined based upon a TIA that demonstrates the trip/VMT reductions. Suggested point ranges:</p> <p>Incentive based CRT Programs (1-8 points)</p> <p>Mandatory CRT programs (5-20 points)</p>	TBD	
Other Trip Reductions	<p>Other trip or VMT reduction measures not listed above with TIA and/or other traffic data supporting the trip and/or VMT for the project.</p>	TBD	

Feature	Description	Assigned Point Values	Project Points
Total Points from Commercial/Industrial Project:			

-Commercial/Industrial Section Ends-