

REVISED TRAFFIC ASSESSMENT

**THE COVE AT EL NIGUEL**

Laguna Niguel, California

June 9, 2021

(Original dated January 14, 2021)

June 9, 2021

Michael Recupero  
Recupero & Associates, Inc.  
31877 Del Obispo Street, Suite 204  
San Juan Capistrano, CA 92675

LLG Reference: 2.20.4357.1

Subject: **Revised Traffic Assessment for The Cove at El Niguel**  
Laguna Niguel, California (original report dated January 14, 2021)

Dear Mr. Recupero:

Linscott, Law & Greenspan, Engineers (LLG) is pleased to submit this Revised Traffic Assessment associated with The Cove at El Niguel (hereinafter referred to as “Project”) in the City of Laguna Niguel, California. The project site is located along Crown Valley Parkway, opposite of Paseo del Niguel, and is proposing to construct a 22-unit townhome residential community. This traffic assessment includes the following:

- Project trip generation assessment,
- VMT screening assessment,
- Sight distance analysis,
- Internal circulation evaluation,
- Queueing evaluation for the northbound left-turn lane at the project driveway,
- Traffic signal warrant analysis at the project driveway, and
- Construction assessment.

Further, this traffic assessment has been updated to address applicable comments/recommendations on the January 14, 2021 analysis as outlined in the *The Cove at El Niguel Traffic Assessment Peer Review, City of Laguna Niguel, dated March 24, 2021, prepared by RK engineering group, inc.*, on behalf of the City of Laguna Niguel.

## PROJECT LOCATION AND DESCRIPTION

The Project site is located along Crown Valley Parkway, opposite of Paseo Del Niguel, and is currently a vacant 4.2± acre parcel of land located in the City of Laguna Niguel, California. Access to the Project site is currently provided via an existing private driveway located opposite Paseo Del Niguel. **Figure 1**, located at the

### Engineers & Planners

Traffic  
Transportation  
Parking

### Linscott, Law & Greenspan, Engineers

2 Executive Circle  
Suite 250  
Irvine, CA 92614  
949.825.6175 T  
949.825.6173 F  
www.llgengineers.com

Pasadena  
Irvine  
San Diego  
Woodland Hills

Philip M. Linscott, PE (1924-2000)  
Jack M. Greenspan, PE (Ret.)  
William A. Law, PE (Ret.)  
Paul W. Wilkinson, PE  
John P. Keating, PE  
David S. Shender, PE  
John A. Boorman, PE  
Clare M. Look-Jaeger, PE  
Richard E. Barretto, PE  
Keil D. Maberry, PE

rear of this letter report, presents a vicinity map which illustrates the general location of the project and the surrounding street system.

The proposed Project includes the construction of a 22-unit townhome residential community within eight (8) buildings. Parking for the Project includes 44 garage spaces (2 spaces per unit) and nineteen (19) surface lot spaces. Access to the Project site will remain the same as the existing private driveway that currently serves the site, located along Crown Valley Parkway. **Figure 2** presents an existing aerial photograph of the Project site. **Figure 3** presents the proposed Project site plan prepared by Hunsaker & Associates in November 2020.

## EXISTING TRAFFIC CONDITIONS

### Existing Street Network

The principal local network of streets serving the project site includes Crown Valley Parkway. The following discussion provides a brief synopsis of the key area roadway:

**Crown Valley Parkway** is primarily a six-lane, divided roadway oriented in the north-south direction that borders the project site to the east. On-street parking is not permitted on either side of this roadway. The posted speed limit on Crown Valley Parkway is 50 miles per hour (mph). Daily traffic volumes on the section of Crown Valley Parkway, adjacent to the Project site, totals 23,133 vehicles per day based on traffic volumes collected on Thursday, December 3, 2020. However, the anticipated pre-Covid-19 volumes is 27,083 vehicles per day based on the adjustment methodology identified in the Existing Traffic Volume Section noted below.

**Figure 4** presents the existing roadway conditions for at the project driveway located along Crown Valley Parkway. This figure identifies the number of travel lanes along Crown Valley Parkway as well as intersection configurations and controls at the project driveway.

### Existing Traffic Volumes

Due to the COVID-19 virus, the Governor of California has issued a state-wide “stay at home” order which has ultimately resulted in a decrease in traffic. Based on these current conditions, the ability to collect traffic counts to establish baseline conditions that would be reflective of traffic conditions without “stay at home” orders in effect is not possible. As such, to establish “baseline” traffic conditions, pre-COVID-19 (i.e. under normal circumstances without “stay at home” orders in effect), LLG has researched historical data and was able to obtain Year 2019 ADT counts on Crown

Valley Parkway, between Hillhurst Drive and Clubhouse Drive. Given the availability of historic data, the following steps were used to establish pre-COVID-19 traffic conditions:

- (1) Historic data is available on Crown Valley Parkway, between Hillhurst Drive and Clubhouse Drive, for Year 2019.
- (2) LLG has collected Year 2020 COVID-19 traffic counts on Crown Valley Parkway, between Hillhurst Drive and Clubhouse Drive, for use in establishing traffic counts/turning movement percentages. These traffic counts were collected in December 2020 by National Data and Surveying Services, Inc.
- (3) Using information from (1) and (2), compare 2019 to 2020 to establish change in traffic counts due to the current COVID-19 environment.
- (4) Apply the rate calculated in (3) to 2020 COVID-19 traffic counts and forecast 2019 traffic conditions.
- (5) Lastly, apply an annual growth factor of 0.75% per year to the Year 2019 traffic conditions to establish Year 2020 pre-COVID-19 baseline traffic conditions. The annual growth factor is consistent with Section 4.2 of the *City of Laguna Niguel Transportation Assessment Guidelines*, dated November 2020.

**Figure 5** illustrates the adjusted existing (Year 2020) weekday AM and PM peak hour traffic volumes at the Crown Valley Parkway/Project Driveway-Paseo del Niguel intersection. **Appendix A** contains the summary tables for the adjusted Year 2020 baseline volume development as well as the existing and historic traffic count sheets.

## PROJECT TRAFFIC CHARACTERISTICS

### Trip Generation Forecast

Traffic generation is expressed in vehicle trip ends, defined as one-way vehicular movements, either entering or exiting the generating land use. Generation factors and/or equations used in this analysis are based on information found in the 10<sup>th</sup> Edition of *Trip Generation*, published by the Institute of Transportation Engineers (ITE) [Washington, D.C., 2017].

As presented in the upper portion of **Table 1**, the trip generation potential of the proposed Project has been estimated using the average rates for ITE Land Use 220: Multifamily Housing Low Rise<sup>1</sup>.

The lower portion of **Table 1** presents the trip generation forecast for the proposed Project. As shown, the proposed Project is forecast to generate 161 daily trips, with 10 trips (2 inbound, 8 outbound) produced in the AM peak hour and 12 trips (8 inbound, 4 outbound) produced in the PM peak hour.

Based on Section 4.0 of the *City of Laguna Niguel Transportation Assessment Guidelines*, a LOS Traffic Impact Study is required for all projects that will add 51 or more trips during the AM or PM peak hours to any intersection. Given the results of the proposed Project's trip generation forecast, the proposed Project trips are expected to generate less than 50 trips during both the weekday AM and PM peak hours. Therefore, LLG concludes that the added Project trips, which amounts to 10 weekday AM peak hour trips and 12 weekday PM peak hour trips, would have minimal to no traffic impacts on the surrounding street network and no further analysis is needed.

### **Traffic Distribution and Assignment**

Project trips have been further distributed and assigned to the adjacent street system based on the following considerations:

- the orientation of the site and the proximity to key area roadways (i.e. Crown Valley Parkway),
- expected localized traffic patterns based on adjacent street channelization and presence of traffic signals, and
- ingress/egress availability at the Project site driveways.

**Figure 6** presents the Project trip distribution pattern at the project driveway. **Figure 7** presents the anticipated peak hour traffic volumes associated with proposed Project for the AM and PM peak hours at the project driveway. The AM and PM peak hour traffic volume assignments presented in **Figure 7** reflect the Project trip distribution characteristics illustrated in **Figure 6** and the Project trip generation forecast presented in **Table 1**.

**Figure 8** presents the AM and PM peak hour traffic volumes at the project driveway with the addition of trips generated by the proposed Project to existing traffic volumes.

---

<sup>1</sup> Low-rise multifamily housing includes buildings that have one or two levels (floors).

## **VMT SCREENING ASSESSMENT**

The purpose of a VMT assessment is to evaluate the Project based on Senate Bill 743 (SB 743) requirements consistent with *Technical Advisory on Evaluating Transportation Impacts in California Environmental Quality Act (CEQA)*, December 2018 prepared by State of California Governor's Office of Planning and Research (OPR) and the CEQA VMT Analysis guidelines identified within the *City of Laguna Niguel Transportation Assessment Guidelines*.

The City's VMT Guidelines provides guidance for analysis of VMT assessments under SB743. The City documents provides screening thresholds to assess whether further VMT analysis is required based on project location, size, or consistency with the SCAG Regional Transportation Plan/Sustainable Communities Strategy.

Section 3.2 of the *City of Laguna Niguel Transportation Assessment Guidelines dated November 2020* indicate that projects generating less than 500 vehicle trips per day based on the latest ITE Trip Generation Manual are presumed to be less than significant. Given the results of the proposed Project's trip generation forecast, the proposed Project trips are expected to generate less than 500 daily trips during the weekday. Therefore, LLG concludes that the Project would be screened out from a VMT assessment and its VMT impact are presumed to be less than significant.

## **SITE ACCESS EVALUATION**

### **Sight Distance Analysis**

At intersections and/or project driveways, a substantially clear line of sight should be maintained between the driver of a vehicle waiting at the crossroad and the driver of an approaching vehicle. Adequate time must be provided for the waiting vehicle to either cross all lanes of through traffic, cross the near lanes and turn left, or turn right, without requiring through traffic to radically alter their speed. A sight distance evaluation has been performed for the project driveway located on Crown Valley Parkway as well as the northbound left-turn into the project site on Crown Valley Parkway.

The Sight Distance Evaluation for the project driveway as included in the January 14, 2021 analysis utilized the criteria and procedures set forth by the California Department of Transportation (Caltrans) in the State's *Highway Design Manual (HDM)* for "Private Road Intersections" consistent with standard traffic engineering practice and as discussed with City staff prior to initiation of the Project traffic assessment. However, based on recommendations outlined in the March 24, 2021

RKE Peer Review, the line of sight evaluation for the proposed private roadway was also evaluated based using *Orange County Public Works Department (OCPDW) Standard Plan No. 1117 – Intersection Sight Distance*.

### ***Orange County Sight Distance Criteria***

Per OCPWD Standard Plan No. 1117, the intersection sight distance is measured along the centerline of the roadway and is defined as the distance required to allow 7.5 seconds for the driver on the crossroad (or left-turn pocket) to safely cross the main roadway or turn left while the approach vehicle travels at the assumed design speed of the main roadway. The sight distance is measured from a driver's line of sight (3.5-foot eye height) to oncoming vehicles (4.25-foot object height) while in a vehicle at an intersection 10 feet back from the projection of the curb line.

Crown Valley Parkway is defined as a Major roadway in the City of Laguna Niguel Circulation Element and the Orange County Master Plan of Arterial Highways (MPAH). Per OCPWD Standard Plan No. 1117, the intersection sight distance for an unsignalized intersection along a Major roadway is 660 feet.

The project site has been visited to determine the existing provided sight distance at the project driveway. The existing provided sight distance on Crown Valley Parkway is 1,390 feet for vehicles approaching from the right and 620 feet for vehicles approaching from the left at the project driveway.

**Figure 9** presents the results of the sight distance evaluation at the project driveway for left and right-turning vehicles based on the application of the required sight distance OCPWD Standard Plan No. 1117 and actual sight distances. This figure also illustrates the limited use areas. As shown, the existing provided sight lines would be short 40 feet and thus would not satisfy the intersection sight distance for vehicles approaching from the left per the OCPWD Standard Plan No. 1117 (620 feet provided vs. a need of 660 feet).

To verify the adequacy of sight lines at the Project driveway, the criteria set forth in the most current Highway Design Manual (HDM) was utilized. The use of the Caltrans HDM is consistent with standard engineering practice and is widely accepted by most jurisdictions. As such, the sight lines based on the HDM criteria has been included as well and is considered applicable for the Project driveway.

### ***Highway Design Manual (HDM) Sight Distance Criteria***

The Sight Distance Evaluation for the Project driveway to verify the adequacy of sight lines was also based on the criteria and procedures set forth by the California Department of Transportation (Caltrans) in the State's *Highway Design Manual (HDM)* for "Private Road Intersections". Both stopping sight distance and corner sight distance was utilized for the evaluation, although the Caltrans HDM, in Section 405.1(2)(c), page 400-27, indicates that for Private Road Intersections, "The minimum corner sight distance shall be equal to the stopping sight distance as given in Table 201.1...". Stopping sight distance is measured from the driver's eyes, which are assumed to be 3.5 feet above the pavement surface, to an object 0.5-foot high on the roadway.

Stopping sight distance is defined in the Caltrans HDM to be the distance required by the driver of a vehicle, traveling at a given speed, to bring the vehicle to a stop after an object ½ foot high on the road becomes visible. Stopping sight distance is measured from the driver's eyes, which is assumed to be 3 ½ feet above the pavement surface, to an object ½ foot high on the road.

Corner sight distance is defined in the Caltrans HDM to be the distance required by the driver of a vehicle, traveling at a given speed, to maneuver their vehicle and avoid an object without radically altering their speed. Line of sight for corner sight distance is to be determined from a 3½ foot height at the location of the driver of a vehicle on a minor road to a 3½ foot object height in the center of the approaching lane of the major road.

The speed used in determining stopping sight distance is defined as the "critical speed" or 85th percentile speed which is the speed at which 85% of the vehicles are traveling at or less. The critical speed is the single most important factor in determining stopping sight distance. Table 201.1 in the HDM is used in determining stopping sight distance based on the critical speed of vehicles on the affected roadway. The posted speed limit on Crown Valley Parkway is 50 miles per hour (mph). For this analysis, a design speed of 60 mph for Crown Valley Parkway was utilized consistent with that which was required per OCPWD Standard Plan No. 1117. This design speed was based on speed surveys that were collected on Crown Valley Parkway at the project driveway, which indicated an 85<sup>th</sup> percentile speed of 60 mph.

Based on Table 201.1 of the Caltrans HDM and a speed of 60 mph on Crown Valley Parkway, a stopping sight distance of 580 feet is required for both a left-turning and right-turning vehicle at the project driveway.



To provide a conservative assessment, the “corner sight distance” criteria in Section 405.1(2)(b) of the *HDM* was also utilized. Based on the criteria set forth in Table 405.1A of the Caltrans HDM and a speed of 60 mph on Crown Valley Parkway, the corner sight distance required for a left-turning vehicle is 827 feet for vehicles approaching from the right and 739 feet for vehicles approaching from the left.

As previously noted, the existing provided sight distance on Crown Valley Parkway is 1,390 feet for vehicles approaching from the right and 620 feet for vehicles approaching from the left at the project driveway.

#### *Project Driveway Outbound Left-Turn Evaluation*

**Figure 10** presents the results of the sight distance evaluation at the project driveway for left-turning vehicles based on the application of the stopping sight distance, corner sight distance and the actual sight distance. This figure also illustrates the limited use areas. As shown, the existing provided sight lines do not satisfy the required corner sight distance for vehicles approaching from the left and is therefore considered inadequate per the HDM standards, although the required stopping sight distance is met.

#### *Project Driveway Outbound Right-Turn Evaluation*

**Figure 11** presents the results of the sight distance evaluation at the project driveway for right-turning vehicles based on the application of the stopping sight distance, corner sight distance and the actual sight distance. This figure also illustrates the limited use areas. As shown, the existing provided sight lines are expected to be adequate per the HDM standards as long as obstructions within the sight triangles are minimized. Adequate sight lines give the motorist the ability to see gaps in traffic to help with egress from the site. Due to these sight lines, a deceleration lane or an acceleration lane is not required for the right-turning vehicles either entering the site or exiting the site, respectively.

#### *Project Driveway Inbound Left-Turn Evaluation*

**Figure 12** presents the sight distance evaluation for the northbound left-turn movement on Crown Valley Parkway based on the application of the stopping sight distance criteria. Based on Table 201.1 of the Caltrans HDM and a speed of 60 mph on Crown Valley Parkway, a stopping sight distance of 580 feet is required for the left-turn movement. The figure illustrates the limited use areas. As shown, the sight lines for the northbound left-turn movement are expected to be adequate as long as obstructions within the sight triangles are minimized.

Based on the above, it is recommended that the project driveway be limited to right turn in/out and left turn in only; outbound left-turn movements are recommended to be prohibited.

### **Internal Circulation Evaluation**

The on-site circulation was evaluated in terms of vehicle-pedestrian conflicts. Based on our review of the proposed site plan, the overall layout does not create any unsafe vehicle-pedestrian conflict points and the driveway throating is sufficient such that access to parking spaces is not impacted by internal vehicle queuing/stacking. The on-site circulation is very good based on our review of the proposed site plan, whereas the alignment, spacing, and throating of the Project driveways is adequate. The circulation around the buildings is adequate with sufficient sight distance along the drive aisles. The turning template requirements of small service/delivery trucks (i.e., UPS, FedEx, and trash trucks), fire trucks and passenger vehicles were utilized to ensure these vehicles could properly access and circulate through the Project site. As such, vehicles entering the site via Crown Valley Parkway can do so unimpeded.

In addition, five years of crash data was researched at the intersection of Crown Valley Parkway at Paseo del Niguel via SWITRS, which is a statewide traffic data system used for collecting traffic collisions. Review of this data shows that the northbound right-turn movement had no rear end collision during the last five years. Since the southbound lane configuration is similar to that of the northbound approach it can be assumed that the potential conflicts between the southbound right-turn and the southbound through movement would have similar conflicts to that of the northbound movements which resulted in no collisions. As such, a deceleration lane into the site is not required.

### **Queueing Evaluation**

A queueing evaluation was completed for the northbound left-turn lane at the project driveway to validate that the existing storage provided is adequate to accommodate the proposed Project traffic. The queueing evaluation was conducted based on Existing Plus Project peak hour traffic volumes and the HCM 95<sup>th</sup> Percentile methodology.

**Table 2** presents the queueing results for the northbound left-turn pocket at the project driveway. Review of **Table 2** indicates that the anticipated queues do not exceed more than one (1) vehicle during both the AM and PM peak hours, and therefore the existing storage is considered adequate. **Appendix B** presents the queueing worksheets.

## TRAFFIC SIGNAL WARRANT ANALYSIS

A signal warrant assessment has been completed for the Project driveway to determine whether the installation of a traffic signal is justified. This assessment is made on the basis of signal warrant criteria adopted by Caltrans. For this study, the need for signalization is assessed on the basis of the peak-hour traffic signal warrant as described in the *California Manual on Uniform Traffic Control Devices (MUTCD)*.

Warrant #3 has two parts:

- (1) *Part A* evaluates peak hour vehicle delay for traffic on the minor street approach with the highest delay, and
- (2) *Part B* evaluates peak-hour traffic volumes on the major and minor streets.

This method provides an indication of whether peak-hour traffic conditions or peak-hour traffic volume levels are, or would be, sufficient to justify installation of a traffic signal.

The decision to install a traffic signal should not be based purely on the warrants alone. Instead, the installation of a signal should be considered and further analysis performed when one or more of the warrants are met. Additionally, engineering judgment is exercised on a case-by-case basis to evaluate the effect a traffic signal will have on certain types of accidents and traffic conditions at the subject intersection as well as at adjacent intersections.

**Table 3** presents the results of the peak-hour traffic signal warrant analysis (Warrant #3) for Existing Plus Project traffic conditions. Column (1) of *Table 3* indicates that the project driveway does not satisfy the criteria for a traffic signal. As such, the installation of a traffic signal at the project driveway is not recommended.

For informational purposes, a signal warrant analysis has also been completed to include the east leg (Paseo del Niguel) as part of the traffic signal. Currently, Paseo del Niguel allows for ingress only and would be converted to full access with the installation of a traffic signal. Column (2) of *Table 3* presents the results of the peak-hour traffic signal warrant analysis for Existing Plus Project conditions with full access<sup>2</sup> on Paseo del Niguel. The results indicate that the intersection does not satisfy the criteria for a traffic signal.

**Appendix C** presents the signal warrant analysis worksheets.

---

<sup>2</sup> The westbound volumes have been estimated based on the number of homes that would be serviced by the potential signal in combination with ITE trip rates.

## RECOMMENDED PROJECT IMPROVEMENTS

### Restrict Left-Turn Egress at Project Driveway

Currently, access to the Project site is anticipated to remain the same as the existing full-access driveway that currently serves the site, located along Crown Valley Parkway. However, the sight distance analysis presented earlier in this report indicate that the existing sight lines are not adequate to safely accommodate left-turn egress at the project driveway based on the corner sight distance requirements in comparison to the actual sight lines now provided. Additionally, the current travel speeds on Crown Valley Parkway will pose a challenge for vehicles leaving the project site to complete a left-turn. Since a traffic signal is not justified at this location, it is recommended to restrict left-turn egress at the project driveway as a safety enhancement. **Figure 13** presents the conceptual improvement plan related to the installation of a median diverter on Crown Valley Parkway to restrict outbound left-turn movements from the project driveway.

As a result, vehicles that were originally anticipated to complete a left-turn would be required to instead make a right-turn out of the project driveway and complete a U-turn at the intersection of Crown Valley Parkway/Club House Drive. The forecast number of project trips anticipated to complete this movement amount to five (5) trips in the AM peak hour and two (2) trips in the PM peak hour on a typical weekday. Therefore, LLG concludes that the added volume to Crown Valley Parkway/Club House Drive is considered nominal and would have minimal impacts to the surrounding street system, inclusive of the operations of the Crown Valley Parkway/Club House Drive intersection.

**Appendix D** contains the project trip distribution pattern based on the restriction of left-turn egress at the project driveway, the AM and PM peak hour traffic volumes associated with the proposed Project, and the AM and PM peak hour Existing Plus Project traffic volumes. **Appendix D** also contains the corresponding level of service and queueing calculation worksheets at the project driveway, which indicate that the proposed Project driveway is forecast to operate at acceptable service levels with the left-turn egress restriction, and the northbound left-turn queues are also expected to be adequate.

### Northbound Left-Turn Pocket on Crown Valley Parkway at Project Driveway

Review of existing roadway conditions on Crown Valley Parkway indicates that the existing northbound left-turn pocket at the Project Driveway provides 115-feet of storage with a transition area of 60-feet. While the northbound left-turn pocket is designed appropriately per Section 400-34 of the Caltrans HDM, it is recommended

to modify the transition area of the turn pocket to better accommodate the high speeds along Crown Valley Parkway which have an 85<sup>th</sup> percentile speed of 60 mph.

*Figure 12* also presents the conceptual improvement plan for modifying the left-turn pocket. It is recommended that, in conjunction with the installation of a median diverter, the left-turn pocket be modified, as shown, to provide a 100-foot left-turn lane with a transition area of 120-feet. The queueing results presented earlier in this report indicate that the anticipated queues do not exceed more than one (1) vehicle during the weekday peak hours, therefore, this improvement is not expected to impact vehicles entering the project site.

## GAP ANALYSIS

A gap analysis has been completed for the northbound left-turn ingress and eastbound right-turn egress at the Project driveway to determine if the existing gaps along Crown Valley Parkway are considered adequate to accommodate the Project traffic volumes. For the purposes of this study, it is assumed that the minimum time for one vehicle to safely complete the eastbound right-turn movement and northbound left-turn movement is 7 seconds and 10 seconds, respectively.

*Table 4* presents a summary of the gap survey performed in May 2021 for the eastbound right-turn egress from the Project site onto Crown Valley Parkway. Based on the project trips presented in *Figure D-2 (Appendix D)*, a total of 8 trips and 4 trips are forecast to make the eastbound right-turn egress movement during the AM peak hour and PM peak hour, respectively. Review of *Table 4* indicates that a total of 215 vehicles during the AM peak hour and 196 vehicles during the PM peak hour may be accommodated within the existing gaps on Crown Valley Parkway. Therefore, it can be concluded that the existing gaps along Crown Valley Parkway are considered adequate to accommodate the project traffic volumes.

*Table 5* presents a summary of the gap survey performed in May 2021 for the northbound left-turn ingress to the Project site onto Crown Valley Parkway. Based on the project trips presented in *Figure D-2 (Appendix D)*, a total of 1 trip and 3 trips are forecast to make the northbound left-turn ingress movement during the AM peak hour and PM peak hour, respectively. Review of *Table 5* indicates that a total of 128 vehicles during the AM peak hour and 115 vehicles during the PM peak hour may be accommodated within the existing gaps on Crown Valley Parkway. Therefore, it can be concluded that the existing gaps along Crown Valley Parkway are considered adequate to accommodate the project traffic volumes.

## CONSTRUCTION ASSESSMENT

A construction assessment has been completed to determine the potential traffic impacts due to construction activities at the Project site. Generally, construction activities include site grading/excavation, building foundation/framing/construction and paving/concrete/landscaping. The following section describes the potential construction-related trips associated with each construction activity and provides an assessment as to whether or not the forecast construction trips will have an impact on the existing street system. It should be noted that a majority of the construction information for the proposed Project is currently unknown, therefore, the following information has been estimated based on LLG's prior knowledge related to construction activities.

### Construction Traffic Trip Generation

In order to forecast the potential construction related trips associated with the construction activities at the project site, the following assumptions have been utilized for the following three construction components:

#### Site Grading/Excavation

- A five-day workweek (Monday through Friday) and nine-hour workday was assumed.
- The Project site is generally considered near-balanced and will require approximately 130 cubic yards (CY) of soil to be exported for grading. Based on a capacity of 10 CY per truck, the site would require approximately 13 truckloads for soil export (i.e. 26 total daily truck trips).
- A total of 5 workers per day was assumed.

#### Building Foundation/Framing/Construction

- A five-day workweek (Monday through Friday) and nine-hour workday was assumed.
- A total of 7 trucks per day was assumed (i.e. 14 total daily truck trips).
- A total of 6 workers per day was assumed.

#### Paving/Concrete/Landscape

- A five-day workweek (Monday through Friday) and nine-hour workday was assumed.
- A total of 3 trucks per day was assumed (i.e. 6 total daily truck trips).
- A total of 6 workers per day was assumed.

In addition to the aforementioned assumptions for each construction component, the following assumptions were utilized for truck and employee trips:

- Each truckload requires an inbound trip and an outbound trip.
- The daily number of truck trips was averaged over the nine-hour workday to obtain the number of peak hour truck trips (50% entering and 50% exiting).
- All truck trips were converted to passenger car equivalents (P.C.E.'s) using a P.C.E factor of 3.0.
- Each worker would make 2 trips per day (one during the AM peak hour and one during the PM peak hour).

Based on the aforementioned assumptions, **Table 6** provides a summary of the forecast construction peak hour and daily traffic volumes for each of the three construction components. Review of the first row of **Table 6** shows that the site grading/excavation construction component is expected to generate 88 daily trips with 14 trips produced during the AM peak hour and 14 trips produced during the PM peak hour. Review of the second row of **Table 6** shows that the building foundation/framing/construction component is expected to generate 54 daily trips with 12 trips produced during the AM peak hour and 12 trips produced during the PM peak hour. Review of the last row of **Table 6** shows that the paving/concrete/landscaping component is expected to generate 30 daily trips with 9 trips produced during the AM peak hour and 9 trips produced during the PM peak hour.

It can be concluded that all three construction components will generate less than 50 trips during both the weekday AM and PM peak hours. Therefore, the added construction trips would have minimal impacts on the surrounding street network. As such no further analysis is recommended. Nevertheless, to reduce the impact of construction-related traffic the implementation of a Construction Management Plan is recommended to minimize traffic impacts upon the local circulation system in the area and improve ingress/egress to the construction site.

### **Construction Management Plan**

To help minimize any potential congestion along Crown Valley Parkway related to the Project construction trips associated with trucks and employees traveling to and from the Project site in the morning and afternoon during Project construction activities, a Construction Management Plan is recommended to mitigate any potential short-term traffic impacts.

To ensure impacts to the surrounding street system are kept to a minimum, it is recommended that the Construction Management Plan for the proposed Project be developed in coordination with the City of Laguna Niguel prior to the start of construction and, at a minimum, address the following:

- Ingress and egress for the construction truck and worker traffic would be via Playa Blanca at Crown Valley Parkway. It is recommended to coordinate with the City to determine if a flagman would be required to assist with ingress and egress for trucks and construction equipment.
- Traffic control for any street closure, detour or other disruption to traffic circulation.
- Identify the routes that construction vehicles will utilize for the delivery of construction materials (i.e. lumber, tiles piping, windows, etc.), to access the site, traffic controls and detours and proposed construction phasing plan for the Project.
- Coordinate with the City to identify parking needs and parking areas for construction related equipment and workman support. Review of the existing site suggests that parking may potentially be available on site. As an alternative parking may be allowed along Crown Valley Parkway or near-by off-street parking lots such as City Hall and/or Laguna Niguel Racquet Club.
- Specify the hours during which transport activities can occur and methods to mitigate construction-related impacts to adjacent streets.
- Require the Applicant to keep all haul routes clean and free of debris including but not limited to gravel and dirt as a result of its operations. The Applicant shall clean adjacent streets, as directed by the City Engineer (or representative of the City Engineer) of any material which may have been spilled, tracked or blown onto adjacent streets or areas.
- Hauling or transport of oversize loads will be coordinated with the City as to the haul route as well as the hours allowed. Hauling or transport may be permitted/required during nighttime hours, weekends or Federal holidays, at the discretion of the City Engineer. All hauling/delivery access to and from the site will be from Crown Valley Parkway. An approved Haul Route Permit will be required from the City.
- Haul trucks entering or exiting public streets shall at all times yield to public traffic.



- If hauling operations cause any damage to existing pavement, street, curb and/or gutter along the haul route, the applicant will be fully responsible for repairs. The repairs shall be completed to the satisfaction of the City Engineer.
- This Plan shall meet standards established in the current *California Manual on Uniform Traffic Control Device (MUTCD)* as well as City of Laguna Niguel requirements.

## CONCLUSION

When assessing the need for further analysis at study intersections, a “50 peak hour trip” threshold is applied based on the *City of Laguna Niguel Transportation Assessment Guidelines*. Given the results of the trip generation forecast, the proposed Project trips are expected to generate less than 50 trips during both the weekday AM and PM peak hours. Therefore, it can be concluded that the added Project trips would have minimal impacts on the surrounding street network and no further analysis is needed. In addition, the proposed Project trips are expected to generate less than 500 daily trips during the weekday, and therefore, it can also be concluded that the Project would be screened out from a VMT assessment and its VMT impact are presumed to be less than significant.

Review of the Project Driveway located on Crown Valley Parkway indicates that the existing sight lines at the project driveway are considered adequate for right-turning vehicles but insufficient for left-turning vehicles per the HDM standards. Therefore, an acceleration lane to help with right-turn egress from the site is not required. Review of the proposed site plan indicates that on-site circulation is adequate and therefore a deceleration lane into the site is not required. Additionally, a queueing evaluation for the northbound left-turn pocket at the project driveway indicates that the existing storage is adequate to accommodate the projected Project traffic.

A signal warrant assessment was completed for the Project driveway at Crown Valley Parkway and the installation of a traffic signal is not recommended.

It is recommended to implement improvements as part of the proposed Project, which include the installation of a median diverter on Crown Valley Parkway to restrict left-turn egress at the project driveway as a safety enhancement. Recommended improvements also include modifying the northbound left-turn at the project driveway to provide a storage of 100-feet with a transition area of 120-feet to better accommodate the 85<sup>th</sup> percentile speed of 60 mph on Crown Valley Parkway.

A gap analysis was completed for the northbound left-turn ingress and the eastbound right-turn egress at the Project driveway which indicates that the existing gaps along

Crown Valley Parkway are considered adequate to accommodate the project traffic volumes.

Lastly, the construction assessment indicates that the three construction components, including site grading/excavation, building foundation/framing/construction, and paving/concrete/landscape, will generate less than 50 trips during both the weekday AM and PM peak hours. Therefore, the added construction trips would have minimal impacts to the surrounding street network. However, to reduce any potential impacts of the construction-related traffic, it is recommended that a Construction Management Plan for the proposed Project be developed in coordination with the City of Laguna Niguel prior to the start of construction.

\* \* \* \* \*

We appreciate the opportunity to be of service on this Project. Should you need further assistance, or have any questions regarding this analysis, please call us at (949) 825-6175.

Sincerely,

**Linscott, Law & Greenspan, Engineers**




Richard E. Barretto, P.E.  
Principal


Cc. Shane S. Green, P.E., LLG

Attachments





n:\4300\2204357 - crowne cove, laguna hills\dwg\4357 f-1.dwg LDP 10:58:03 01-14-2021 co



SOURCE: GOOGLE

KEY

 = PROJECT SITE

# FIGURE 1

VICINITY MAP  
THE COVE AT EL NIGUEL, LAGUNA NIGUEL



n:\4300\2204357 - crowns cove, laguna hills\dwg\4357 f-2.dwg LDP 10:58:22 01-14-2021 co

LINSCOTT  
LAW &  
GREENSPAN  
engineers




SOURCE: GOOGLE

KEY

 = PROJECT SITE

## FIGURE 2

**EXISTING SITE AERIAL**  
THE COVE AT EL NIGUEL, LAGUNA NIGUEL



n:\4300\2204357 - crown cove, laguna hills\dwg\4357 f-3.dwg LDP 15:23:08 05-27-2021 aguilan

SOURCE: HUNSAKER & ASSOCIATES


# FIGURE 3

## PROPOSED SITE PLAN

THE COVE AT EL NIGUEL, LAGUNA NIGUEL

LINSCOTT  
LAW &  
GREENSPAN  
engineers

NO SCALE




n:\4300\2204357 - crowne cove, laguna hills\dwg\4357 f-4.dwg LDP 10:59:09 01-14-2021 co


- KEY**
- ← = APPROACH LANE ASSIGNMENT
  - ▼ = STOP SIGN
  - NP = NO PARKING
  - D = DIVIDED
  - 2 = NUMBER OF TRAVEL LANES
  - (XX) = POSTED SPEED LIMIT (MPH)
  - = PROJECT SITE


**FIGURE 4**

**EXISTING ROADWAY CONDITIONS  
AND INTERSECTION CONTROLS**  
THE COVE AT EL NIGUEL, LAGUNA NIGUEL




n:\4300\2204357 - crowne cove, laguna hills\dwg\4357 f-5.dwg LDP 10:59:20 01-14-2021 co

**LINSCOTT  
LAW &  
GREENSPAN**  
  
 NO SCALE  
**engineers**

**KEY**  
 = PROJECT SITE

**FIGURE 5**  
**EXISTING (YEAR 2020)**  
**AM AND PM PEAK HOUR TRAFFIC VOLUMES**  
 THE COVE AT EL NIGUEL, LAGUNA NIGUEL



n:\4300\2204357 - crowne cove, laguna hills\dwg\4357 f-6.dwg LDP 10:59:46 01-14-2021 co

KEY





-  = INBOUND PERCENTAGE
-  = OUTBOUND PERCENTAGE
-  = PROJECT SITE


FIGURE 6


PROJECT TRIP DISTRIBUTION PATTERN  
THE COVE AT EL NIGUEL, LAGUNA NIGUEL






ni:\4300\2204357 - crowne cove, laguna hills\dwg\4357 f-7.dwg LDP 10:59:57 01-14-2021 co



**KEY**  
 = PROJECT SITE

# FIGURE 7

**AM AND PM PEAK HOUR PROJECT TRAFFIC VOLUMES**  
 THE COVE AT EL NIGUEL, LAGUNA NIGUEL



n:\4300\2204357 - crowne cove, laguna hills\dwg\4357 f-8.dwg LDP 11:00:11 01-14-2021 co

**LINSCOTT  
LAW &  
GREENSPAN**  
engineers

**KEY**  
 = PROJECT SITE

# FIGURE 8

**EXISTING PLUS PROJECT  
AM AND PM PEAK HOUR TRAFFIC VOLUMES**  
THE COVE AT EL NIGUEL, LAGUNA NIGUEL



**SIGHT DISTANCE**


DESIGN SPEED LIMIT: 60 MPH

REQUIRED STOPPING SIGHT DISTANCE: 660 FEET

EXISTING PROVIDED SIGHT DISTANCE FOR VEHICLES APPROACHING FROM THE RIGHT: 1,390 FEET

EXISTING PROVIDED SIGHT DISTANCE FOR VEHICLES APPROACHING FROM THE LEFT: 620 FEET

**LEGEND**

 PUBLIC RIGHT-OF-WAY LIMITED USE AREA: TO ENSURE ADEQUATE SIGHT DISTANCE, HARDSCAPE AND/OR LANDSCAPE SHALL NOT BE HIGHER THAN 6 INCHES ABOVE THE CURB/SIDEWALK. NO FENCES OR WALLS IN LIMITED USE AREA.


n:\4300\2204357 - crowne cove, laguna hills\dwg\4357 f-9.dwg LDP 14:13:43 05-27-2021 aguilar

SOURCE: HUNSAKER & ASSOCIATES

**FIGURE 9**

**SIGHT DISTANCE ANALYSIS AT THE PROJECT DRIVEWAY PER OC STANDARD PLAN**

THE COVE AT EL NIGUEL, LAGUNA NIGUEL





n:\4300\2204357 - crowne cove, laguna hills\dwg\4357 f-10.dwg LDP 14:16:38 05-27-2021 aguilera

SOURCE: HUNSAKER & ASSOCIATES


## FIGURE 10

SIGHT DISTANCE ANALYSIS FOR LEFT-TURNING VEHICLE AT THE PROJECT DRIVEWAY PER HDM STANDARDS

THE COVE AT EL NIGUEL, LAGUNA NIGUEL

LINSCOTT  
LAW &  
GREENSPAN  
engineers






**SIGHT DISTANCE**

DESIGN SPEED LIMIT:	60 MPH
REQUIRED STOPPING SIGHT DISTANCE:	580 FEET
REQUIRED CORNER SIGHT DISTANCE:	573 FEET
EXISTING PROVIDED SIGHT DISTANCE:	620 FEET

**LEGEND**

 PUBLIC RIGHT-OF-WAY LIMITED USE AREA: TO ENSURE ADEQUATE SIGHT DISTANCE, HARDSCAPE AND/OR LANDSCAPE SHALL NOT BE HIGHER THAN 6 INCHES ABOVE THE CURB/SIDEWALK. NO FENCES OR WALLS IN LIMITED USE AREA.

n:\4300\2204357 - crowne cove, laguna hills\dwg\4357 f-11.dwg LDP 14:19:11 05-27-2021 aguilera




n:\4300\2204357 - crowne cove, laguna hills\dwg\4357 f-12.dwg LDP 14:21:48 05-27-2021 aguilan


SOURCE: HUNSAKER & ASSOCIATES

**FIGURE 12**

**SIGHT DISTANCE ANALYSIS FOR NORTHBOUND LEFT ON CROWN VALLEY PARKWAY PER HDM STANDARDS**

THE COVE AT EL NIGUEL, LAGUNA NIGUEL






n:\4300\2204357 - crowne cove, laguna hills\dwg\4357 f-13.dwg LDP 10:12:36 05-28-2021 aguilar

SOURCE: HUNSAKER & ASSOCIATES

**FIGURE 13**

**CONCEPT PLAN FOR MEDIAN DIVERTER AND FOR NORTHBOUND LEFT-TURN POCKET**

THE COVE AT EL NIGUEL, LAGUNA NIGUEL



SCALE: 1"=30'

TABLE 1  
PROJECT TRAFFIC GENERATION FORECAST<sup>3</sup>  
THE COVE AT EL NIGUEL, LAGUNA NIGUEL

Project Description	Daily 2-Way	AM Peak Hour			PM Peak Hour		
		Enter	Exit	Total	Enter	Exit	Total
<b><u>Trip Generation Rates</u></b>							
▪ 220: Multifamily Housing Low Rise <sup>4</sup> (TE/DU)	7.32	23%	77%	0.46	63%	37%	0.56
<b><u>Trip Generation Forecast</u></b>							
▪ The Cove at El Niguel (22 DU)	161	2	8	10	8	4	12

Notes:  
TE/DU = Trip ends per dwelling unit

<sup>3</sup> Source: *Trip Generation*, 10<sup>th</sup> Edition, Institute of Transportation Engineers (ITE), Washington, D.C. (2017).

<sup>4</sup> Low-rise multifamily housing includes buildings that have one or two levels (floors).



**TABLE 2**  
**EXISTING PLUS PROJECT QUEUEING ANALYSIS**  
**THE COVE AT EL NIGUEL, LAGUNA NIGUEL**

Key Intersection	(1) Existing Plus Project Traffic Conditions				
	Provided Storage	AM Peak Hour		PM Peak Hour	
		Max. Queue/ Min. Storage Required <sup>5</sup>	Adequate Storage (Yes / No)	Max. Queue/ Min. Storage Required <sup>5</sup>	Adequate Storage (Yes / No)
A. Crown Valley Parkway at Project Driveway/Paseo del Niguel Northbound Left-Turn	115'	25'	Yes	25'	Yes

<sup>5</sup> Maximum queue in feet (ft) is based on the HCM 95<sup>th</sup> percentile methodology.

**TABLE 3  
EXISTING PLUS PROJECT TRAFFIC SIGNAL WARRANT ANALYSIS SUMMARY<sup>6</sup>  
THE COVE AT EL NIGUEL, LAGUNA NIGUEL**

<b>Key Intersection</b>	<b>Time Period</b>	<b>(1) Existing Plus Project Traffic Conditions</b>		<b>(2) Existing Plus Project Traffic Conditions including full access for Paseo del Niguel</b>	
		<b>Part A of Warrant 3 Satisfied?</b>	<b>Part B of Warrant 3 Satisfied?</b>	<b>Part A of Warrant 3 Satisfied?</b>	<b>Part B of Warrant 3 Satisfied?</b>
A. Crown Valley Parkway at Project Driveway/Paseo del Niguel	AM	No	No	No	No
	PM	No	No	No	No

<sup>6</sup> Signal warrant checks based on Warrant 3, Part A - Peak-Hour Delay Warrant and Part B - Peak-Hour Volume Warrant are contained in the California MUTCD.

**TABLE 4**  
**PROJECT DRIVEWAY RIGHT-TURN EGRESS VEHICLE GAP ANALYSIS**  
**THE COVE AT EL NIGUEL, LAGUNA NIGUEL**

Gap <sup>7</sup> (seconds)	AM Peak Hour (7:45AM – 8:45AM)			PM Peak Hour (4PM – 5PM)		
	Vehicles Served by Gap <sup>8</sup>	Gaps Occurring During Peak Hour <sup>9</sup>	Total Vehicles Served <sup>10</sup>	Vehicles Served by Gap <sup>8</sup>	Gaps Occurring During Peak Hour <sup>9</sup>	Total Vehicles Served <sup>10</sup>
7 – 13	1	74	74	1	62	62
14 – 20	2	25	50	2	24	48
21 – 27	3	9	27	3	14	42
≥ 28	4	16	64	4	11	44
	<b>Total Accommodated Vehicles</b>		<b>215</b>	<b>Total Accommodated Vehicles</b>		<b>196</b>

<sup>7</sup> A gap is defined as the time interval between cars crossing the Project driveway.

<sup>8</sup> For purposes of this study, it is assumed the minimum time for one vehicle to safely complete a turning movement out of the Project driveway is 7 seconds. For each vehicle subsequently following the first, the time to complete a turn is 7 seconds.

<sup>9</sup> Values are based on gap survey performed on Tuesday, May 11, 2021.

<sup>10</sup> Total Vehicles Served = (Number of Vehicles Served) x (Number of Gaps During Peak Hour)

**TABLE 5**  
**PROJECT DRIVEWAY LEFT-TURN INGRESS VEHICLE GAP ANALYSIS**  
**THE COVE AT EL NIGUEL, LAGUNA NIGUEL**

Gap <sup>11</sup> (seconds)	AM Peak Hour (7:45AM – 8:45AM)			PM Peak Hour (4PM – 5PM)		
	Vehicles Served by Gap <sup>12</sup>	Gaps Occurring During Peak Hour <sup>13</sup>	Total Vehicles Served <sup>14</sup>	Vehicles Served by Gap <sup>8</sup>	Gaps Occurring During Peak Hour <sup>9</sup>	Total Vehicles Served <sup>10</sup>
10-19	1	57	57	1	47	47
20-29	2	13	26	2	19	38
30-39	3	7	21	3	6	18
≥ 40	4	6	24	4	3	12
	<b>Total Accommodated Vehicles</b>		<b>128</b>	<b>Total Accommodated Vehicles</b>		<b>115</b>

<sup>11</sup> A gap is defined as the time interval between cars crossing the Project driveway.

<sup>12</sup> For purposes of this study, it is assumed the minimum time for one vehicle to safely complete a turning movement into the Project driveway is 10 seconds. For each vehicle subsequently following the first, the time to complete a turn is 10 seconds.

<sup>13</sup> Values are based on gap survey performed on Tuesday, May 11, 2021.

<sup>14</sup> Total Vehicles Served = (Number of Vehicles Served) x (Number of Gaps During Peak Hour)

TABLE 6  
PROJECT CONSTRUCTION TRAFFIC GENERATION FORECAST  
THE COVE AT EL NIGUEL, LAGUNA NIGUEL

Project Description	Daily	AM Peak Hour			PM Peak Hour		
	2-Way	Enter	Exit	Total	Enter	Exit	Total
<b><u>Site Grading/Excavation Generation Forecast</u></b>							
▪ Construction Truck Traffic (13 trucks)	26	2	1	3	1	2	3
Passenger Car Equivalent Factor <sup>15</sup>	<u>3</u>	<u>3</u>	<u>3</u>	<u>3</u>	<u>3</u>	<u>3</u>	<u>3</u>
Subtotal	78	6	3	9	3	6	9
▪ Employees (5 workers)	<u>10</u>	<u>5</u>	<u>0</u>	<u>5</u>	<u>0</u>	<u>5</u>	<u>5</u>
<b>Total Site Grading/Excavation Trip Generation Potential</b>	<b>88</b>	<b>11</b>	<b>3</b>	<b>14</b>	<b>3</b>	<b>11</b>	<b>14</b>
<b><u>Building Foundation/Framing/Construction Generation Forecast</u></b>							
▪ Construction Truck Traffic (7 trucks)	14	1	1	2	1	1	2
Passenger Car Equivalent Factor	<u>3</u>	<u>3</u>	<u>3</u>	<u>3</u>	<u>3</u>	<u>3</u>	<u>3</u>
Subtotal	42	3	3	6	3	3	6
▪ Employees (6 workers)	<u>12</u>	<u>6</u>	<u>0</u>	<u>6</u>	<u>0</u>	<u>6</u>	<u>6</u>
<b>Total Building Foundation/Framing/Construction Trip Generation Potential</b>	<b>54</b>	<b>9</b>	<b>3</b>	<b>12</b>	<b>3</b>	<b>9</b>	<b>12</b>
<b><u>Paving/Concrete/Landscape Generation Forecast</u></b>							
▪ Construction Truck Traffic (3 trucks)	6	1	0	1	0	1	1
Passenger Car Equivalent Factor	<u>3</u>	<u>3</u>	<u>3</u>	<u>3</u>	<u>3</u>	<u>3</u>	<u>3</u>
Subtotal	18	3	0	3	0	3	3
▪ Employees (6 workers)	<u>12</u>	<u>6</u>	<u>0</u>	<u>6</u>	<u>0</u>	<u>6</u>	<u>6</u>
<b>Total Paving/Concrete/Landscape Trip Generation Potential</b>	<b>30</b>	<b>9</b>	<b>0</b>	<b>9</b>	<b>0</b>	<b>9</b>	<b>9</b>

<sup>15</sup> A passenger car equivalent factor of 3.0 was applied to the truck trips to convert them into passenger car trips.  
N:\4300\2204357 - Crowne Cove, Laguna Hills\Report\4357 The Cove at El Niguel Traffic Assessment and Site Access Evaluation Letter 6-9-2021.doc

**APPENDIX A**  
**EXISTING TRAFFIC COUNT DATA**

**Table A-1**  
**2020 COVID-19 Growth Rate Calculation**

	(1)	(2)	(3)
<b>Roadway Segment</b>	<b>2019 ADT Volume</b>	<b>2020 COVID-19 ADT Volume</b>	<b>2020 COVID-19 Growth Per Year (%) [1]</b>
A. Crown Valley Parkway between Via Valle and Clubhouse Drive	26,887	23,133	16.2%

Notes

[1] (Column 1 - Column 2) / Column 2

**Table A-2  
Year 2020 Pre-COVID-19 Baseline Volume Development [1]**

Study Intersection	Time Period	(1)	(2)	(3)	(4)	(5)	(6)	(7)
		2020 COVID-19 NBT Volume [2]	2020 COVID-19 SBT Volume [3]	2020 COVID-19 Growth Per Year (%) [4]	2019 Adjusted Baseline NBT Volume [5]	2019 Adjusted Baseline SBT Volume [5]	2020 Pre-COVID-19 Baseline NBT Volume [6]	2020 Pre-COVID-19 Baseline SBT Volume [6]
1. Crown Valley Parkway at Paseo del Niguel	AM	639	879	16.2%	743	1,021	749	1,029
	PM	1,028	1,020		1,195	1,185	1,204	1,194

Notes

[1] Volume entering Paseo del Niguel (i.e. the northbound right-turn and southbound left-turn volumes) was developed based on Google Earth observations of the existing residential area to the east of the intersection. There is approximately 65 DU single-family residential homes in the area which would utilize the intersection. Trips were forecasted based on ITE *Trip Generation* 10th Edition and distributed to the intersection, which resulted in the following volume estimations:

AM Peak Hour: NBR = 5, SBL = 4  
PM Peak Hour: NBR = 18, SBL = 12

It should be noted that since volumes were estimated for the residential area east of the intersection, adjustments to the NBR and SBL volumes for COVID-19 are not required.

[2] NBT volumes are derived from the ADT counts and adjusted to account for the existing residential area to the east of the intersection, which resulted in the following volume estimations:

AM Peak Hour: 644 - 5 = 639  
PM Peak Hour: 1,046 - 18 = 1,028

[3] SBT volumes are derived from the ADT counts and adjusted to account for the existing residential area to the east of the intersection, which resulted in the following volume estimations:

AM Peak Hour: 883 - 4 = 879  
PM Peak Hour: 1,032 - 12 = 1,020

[4] The 2020 COVID-19 growth per year is referenced from Column 3 of Table A-1.

[5] 2019 Adjusted Baseline Volumes were developed by applying the growth rate from Column 3 to the 2020 COVID-19 Volumes:

NBT: Column 1 + (Column 1 × Column 3)  
SBT: Column 2 + (Column 2 × Column 3)

[6] 2020 Pre-COVID-19 Baseline Volumes were developed by applying an additional growth of 0.75% to the 2019 Adjusted Baseline Volumes:

NBT: Column 4 + (Column 4 × 0.75%)  
SBT: Column 5 + (Column 5 × 0.75%)



### VOLUME

Crown Valley Pkwy Bet. Hillhurst Dr & Via Valle

Day: Thursday  
Date: 4/18/2019

City: Laguna Niguel  
Project #: CA19\_1074\_005

DAILY TOTALS					NB	SB	EB	WB	Total		
					12,012	14,875	0	0	26,887		
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL
00:00	14	12			26	12:00	235	253			488
00:15	6	14			20	12:15	204	247			451
00:30	6	14			20	12:30	213	236			449
00:45	9	35	7	47	16 82	12:45	191	843	274	1010	465 1853
01:00	8	6			14	13:00	188	250			438
01:15	3	3			6	13:15	210	270			480
01:30	2	5			7	13:30	188	270			458
01:45	1	14	3	17	4 31	13:45	208	794	276	1066	484 1860
02:00	4	4			8	14:00	209	250			459
02:15	4	2			6	14:15	196	248			444
02:30	3	5			8	14:30	223	281			504
02:45	3	14	2	13	5 27	14:45	233	861	270	1049	503 1910
03:00	2	4			6	15:00	253	261			514
03:15	4	7			11	15:15	224	288			512
03:30	7	6			13	15:30	243	261			504
03:45	5	18	4	21	9 39	15:45	228	948	278	1088	506 2036
04:00	3	3			6	16:00	248	264			512
04:15	5	4			9	16:15	266	309			575
04:30	14	10			24	16:30	234	289			523
04:45	11	33	14	31	25 64	16:45	256	1004	327	1189	583 2193
05:00	14	14			28	17:00	237	310			547
05:15	24	39			63	17:15	252	311			563
05:30	33	54			87	17:30	224	288			512
05:45	34	105	66	173	100 278	17:45	217	930	298	1207	515 2137
06:00	49	57			106	18:00	195	267			462
06:15	59	80			139	18:15	204	255			459
06:30	91	124			215	18:30	172	271			443
06:45	87	286	150	411	237 697	18:45	162	733	230	1023	392 1756
07:00	122	184			306	19:00	137	215			352
07:15	155	201			356	19:15	133	164			297
07:30	173	235			408	19:30	156	164			320
07:45	198	648	253	873	451 1521	19:45	131	557	154	697	285 1254
08:00	196	254			450	20:00	134	130			264
08:15	219	230			449	20:15	96	136			232
08:30	211	253			464	20:30	103	128			231
08:45	204	830	201	938	405 1768	20:45	67	400	118	512	185 912
09:00	173	176			349	21:00	99	132			231
09:15	210	191			401	21:15	82	103			185
09:30	184	232			416	21:30	69	129			198
09:45	182	749	223	822	405 1571	21:45	81	331	81	445	162 776
10:00	173	208			381	22:00	69	69			138
10:15	192	214			406	22:15	64	52			116
10:30	222	249			471	22:30	63	67			130
10:45	187	774	231	902	418 1676	22:45	45	241	40	228	85 469
11:00	173	236			409	23:00	44	27			71
11:15	215	242			457	23:15	21	36			57
11:30	180	261			441	23:30	20	34			54
11:45	193	761	247	986	440 1747	23:45	18	103	30	127	48 230
<b>TOTALS</b>	<b>4267</b>	<b>5234</b>			<b>9501</b>	<b>TOTALS</b>	<b>7745</b>	<b>9641</b>			<b>17386</b>
<b>SPLIT %</b>	<b>44.9%</b>	<b>55.1%</b>			<b>35.3%</b>	<b>SPLIT %</b>	<b>44.5%</b>	<b>55.5%</b>			<b>64.7%</b>

DAILY TOTALS					NB	SB	EB	WB	Total
					12,012	14,875	0	0	26,887
AM Peak Hour	11:45	11:30			11:45	PM Peak Hour	16:00	16:30	16:15
AM Pk Volume	845	1008			1828	PM Pk Volume	1004	1237	2228
Pk Hr Factor	0.899	0.966			0.936	Pk Hr Factor	0.944	0.946	0.955
7 - 9 Volume	1478	1811	0	0	3289	4 - 6 Volume	1934	2396	0 0 4330
7 - 9 Peak Hour	08:00	07:45			07:45	4 - 6 Peak Hour	16:00	16:30	16:15
7 - 9 Pk Volume	830	990	0	0	1814	4 - 6 Pk Volume	1004	1237	0 0 2228
Pk Hr Factor	0.947	0.974	0.000	0.000	0.977	Pk Hr Factor	0.944	0.946	0.000 0.000 0.955

**VOLUME**

Crown Valley Pkwy Bet. Club House Dr & Via Valle

Day: Thursday  
 Date: 12/3/2020

City: Laguna Niguel  
 Project #: CA20\_010035\_001

DAILY TOTALS					NB	SB	EB	WB	Total		
					11,004	12,129	0	0	23,133		
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL
00:00	7	4	0	0	11	12:00	189	251	0	0	440
00:15	8	7	0	0	15	12:15	200	235	0	0	435
00:30	3	5	0	0	8	12:30	206	271	0	0	477
00:45	6	24	7	23	13	12:45	221	816	209	966	430
01:00	3	3	0	0	6	13:00	215	256	0	0	471
01:15	8	1	0	0	9	13:15	204	221	0	0	425
01:30	4	3	0	0	7	13:30	204	206	0	0	410
01:45	4	19	0	7	4	13:45	213	836	247	930	460
02:00	2	4	0	0	6	14:00	220	213	0	0	433
02:15	0	2	0	0	2	14:15	248	240	0	0	488
02:30	2	4	0	0	6	14:30	206	215	0	0	421
02:45	1	5	3	13	4	14:45	269	943	274	942	543
03:00	2	2	0	0	4	15:00	266	258	0	0	524
03:15	3	3	0	0	6	15:15	252	257	0	0	509
03:30	1	8	0	0	9	15:30	255	274	0	0	529
03:45	6	12	8	21	14	15:45	307	1080	285	1074	592
04:00	5	3	0	0	8	16:00	253	271	0	0	524
04:15	4	6	0	0	10	16:15	264	260	0	0	524
04:30	10	8	0	0	18	16:30	254	287	0	0	541
04:45	6	25	14	31	20	16:45	275	1046	214	1032	489
05:00	16	19	0	0	35	17:00	250	222	0	0	472
05:15	21	31	0	0	52	17:15	257	227	0	0	484
05:30	22	43	0	0	65	17:30	201	221	0	0	422
05:45	29	88	52	145	81	17:45	188	896	211	881	399
06:00	32	45	0	0	77	18:00	189	207	0	0	396
06:15	47	80	0	0	127	18:15	138	156	0	0	294
06:30	65	107	0	0	172	18:30	130	173	0	0	303
06:45	56	200	149	381	205	18:45	117	574	136	672	253
07:00	90	155	0	0	245	19:00	107	128	0	0	235
07:15	111	165	0	0	276	19:15	81	112	0	0	193
07:30	140	191	0	0	331	19:30	99	110	0	0	209
07:45	150	491	239	750	389	19:45	74	361	89	439	163
08:00	151	192	0	0	343	20:00	76	83	0	0	159
08:15	161	238	0	0	399	20:15	75	64	0	0	139
08:30	182	214	0	0	396	20:30	72	68	0	0	140
08:45	151	645	196	840	347	20:45	84	307	54	269	138
09:00	169	195	0	0	364	21:00	66	51	0	0	117
09:15	154	196	0	0	350	21:15	65	43	0	0	108
09:30	166	193	0	0	359	21:30	48	54	0	0	102
09:45	190	679	206	790	396	21:45	51	230	36	184	87
10:00	158	168	0	0	326	22:00	49	34	0	0	83
10:15	185	183	0	0	368	22:15	45	40	0	0	85
10:30	181	196	0	0	377	22:30	45	38	0	0	83
10:45	184	708	206	753	390	22:45	37	176	23	135	60
11:00	202	175	0	0	377	23:00	25	14	0	0	39
11:15	201	202	0	0	403	23:15	16	16	0	0	32
11:30	169	213	0	0	382	23:30	19	8	0	0	27
11:45	205	777	223	813	428	23:45	6	66	0	38	6
<b>TOTALS</b>	<b>3673</b>	<b>4567</b>			<b>8240</b>	<b>TOTALS</b>	<b>7331</b>	<b>7562</b>			<b>14893</b>
<b>SPLIT %</b>	<b>44.6%</b>	<b>55.4%</b>			<b>35.6%</b>	<b>SPLIT %</b>	<b>49.2%</b>	<b>50.8%</b>			<b>64.4%</b>

DAILY TOTALS					NB	SB	EB	WB	Total
					11,004	12,129	0	0	23,133
AM Peak Hour	11:45	11:45			11:45	PM Peak Hour	15:00	15:45	15:45
AM Pk Volume	800	980			1780	PM Pk Volume	1080	1103	2181
Pk Hr Factor	0.971	0.904			0.933	Pk Hr Factor	0.879	0.961	0.921
7 - 9 Volume	1136	1590	0	0	2726	4 - 6 Volume	1942	1913	3855
7 - 9 Peak Hour	08:00	07:45			07:45	4 - 6 Peak Hour	16:00	16:00	16:00
7 - 9 Pk Volume	645	883	0	0	1527	4 - 6 Pk Volume	1046	1032	2078
Pk Hr Factor	0.886	0.924	0.000	0.000	0.957	Pk Hr Factor	0.951	0.899	0.960

# SPEED

## Crown Valley Pkwy Bet. Club House Dr & Via Valle

Day: Thursday  
Date: 12/3/2020

City: Laguna Niguel  
Project #: CA20\_010035\_001n

### North Bound

Time	< 15	15 - 19	20 - 24	25 - 29	30 - 34	35 - 39	40 - 44	45 - 49	50 - 54	55 - 59	60 - 64	65 - 69	70 +	Total
00:00 AM	0	0	0	0	0	0	1	6	5	3	5	2	2	24
01:00	0	0	0	0	0	0	1	5	3	3	6	1	0	19
02:00	0	0	0	0	0	1	0	0	2	1	1	0	0	5
03:00	0	0	0	0	0	0	0	3	2	2	2	3	0	12
04:00	0	0	0	0	0	0	1	2	7	9	2	2	2	25
05:00	0	0	0	0	0	3	6	8	17	24	17	6	7	88
06:00	0	0	0	1	1	1	10	27	57	60	30	10	3	200
07:00	0	0	0	0	2	2	9	54	169	166	69	14	6	491
08:00	0	0	0	0	0	3	24	82	202	228	89	13	4	645
09:00	0	0	0	0	1	2	18	117	239	216	67	15	4	679
10:00	0	0	0	0	0	4	28	114	219	219	93	23	8	708
11:00	0	0	0	0	0	1	33	122	275	224	90	23	9	777
12:00 PM	0	0	0	0	0	2	25	158	300	205	96	23	7	816
13:00	0	0	0	0	3	7	23	152	297	233	89	26	6	836
14:00	0	0	0	0	1	7	55	226	360	181	89	19	5	943
15:00	0	0	0	1	0	12	43	194	399	291	107	25	8	1080
16:00	0	0	0	1	0	4	30	184	375	289	124	32	7	1046
17:00	0	0	0	0	1	5	43	192	336	220	72	16	11	896
18:00	0	0	0	1	0	6	25	95	202	165	59	15	6	574
19:00	0	0	0	1	0	4	12	59	117	107	38	13	10	361
20:00	0	0	0	0	1	2	15	52	93	95	37	8	4	307
21:00	0	0	0	0	0	1	7	36	76	68	22	13	7	230
22:00	0	0	0	0	1	0	4	23	51	52	26	11	8	176
23:00	0	0	0	0	0	1	6	10	21	18	7	3	0	66
<b>Totals</b>				5	11	68	419	1921	3824	3079	1237	316	124	11004
<b>% of Totals</b>				0%	0%	1%	4%	17%	35%	28%	11%	3%	1%	100%

AM Volumes	0	0	0	1	4	17	131	540	1197	1155	471	112	45	3673	
% AM				0%	0%	0%	1%	5%	11%	10%	4%	1%	0%	33%	
AM Peak Hour				06:00	07:00	10:00	11:00	11:00	11:00	08:00	10:00	10:00	11:00	11:00	
Volume				1	2	4	33	122	275	228	93	23	9	777	
PM Volumes	0	0	0	4	7	51	288	1381	2627	1924	766	204	79	7331	
% PM				0%	0%	0%	3%	13%	24%	17%	7%	2%	1%	67%	
PM Peak Hour				15:00	13:00	15:00	14:00	14:00	15:00	15:00	16:00	16:00	17:00	15:00	
Volume				1	3	12	55	226	399	291	124	32	11	1080	
<b>Directional Peak Periods</b>				<b>AM 7-9</b>			<b>NOON 12-2</b>			<b>PM 4-6</b>			<b>Off Peak Volumes</b>		
<b>All Speeds</b>	Volume			%			Volume			%			Volume		
	1136			↔ 10%			1652			↔ 15%			1942		
													↔ 18%		
													↔ 57%		

Street Name	Direction	Percentiles					
		15th	50th	Average	85th	95th	ADT
Crown Valley Pkwy	North Bound	48	54	A-6 54	60	65	11004
Crown Valley Pkwy	South Bound	48	54	54	60	64	12129

**SPEED**

## Crown Valley Pkwy Bet. Club House Dr &amp; Via Valle

Day: Thursday  
Date: 12/3/2020

City: Laguna Niguel  
Project #: CA20\_010035\_001s

## South Bound

Time	< 15	15 - 19	20 - 24	25 - 29	30 - 34	35 - 39	40 - 44	45 - 49	50 - 54	55 - 59	60 - 64	65 - 69	70 +	Total
00:00 AM	0	0	0	0	0	0	1	2	12	6	1	1	0	23
01:00	0	0	0	0	0	0	1	2	2	1	1	0	0	7
02:00	0	0	0	0	1	0	1	1	5	5	0	0	0	13
03:00	0	0	0	0	0	1	1	2	7	5	2	3	0	21
04:00	0	0	0	0	0	0	4	4	6	8	4	3	2	31
05:00	0	0	0	0	0	3	6	28	38	41	19	6	4	145
06:00	0	0	0	0	1	5	12	44	110	119	64	19	7	381
07:00	0	0	0	1	0	1	17	112	248	250	95	18	8	750
08:00	0	0	0	0	2	5	17	134	288	283	85	19	7	840
09:00	0	0	0	0	2	3	39	134	261	230	100	17	4	790
10:00	0	0	0	0	1	7	27	133	277	228	69	7	4	753
11:00	0	0	0	0	3	3	27	155	312	232	64	14	3	813
12:00 PM	0	0	0	0	1	6	31	150	399	274	86	14	5	966
13:00	0	0	0	0	0	4	34	186	328	257	93	21	7	930
14:00	0	0	0	0	2	6	45	197	319	276	85	8	4	942
15:00	0	0	0	0	1	3	26	212	405	307	99	16	5	1074
16:00	0	0	0	0	1	5	39	209	383	274	98	21	2	1032
17:00	0	0	0	0	2	6	37	147	334	241	95	17	2	881
18:00	0	0	0	0	0	2	32	125	237	185	68	20	3	672
19:00	0	0	0	0	0	4	22	91	154	111	43	11	3	439
20:00	0	0	0	0	0	3	11	43	95	79	29	4	5	269
21:00	0	0	0	0	0	3	9	29	63	53	21	6	0	184
22:00	0	0	0	0	0	2	9	20	41	39	13	6	5	135
23:00	0	0	0	0	0	0	4	6	8	9	7	1	3	38
<b>Totals</b>				1	17	72	452	2166	4332	3513	1241	252	83	12129
<b>% of Totals</b>				0%	0%	1%	4%	18%	36%	29%	10%	2%	1%	100%

AM Volumes	0	0	0	1	10	28	153	751	1566	1408	504	107	39	4567																						
% AM				0%	0%	0%	1%	6%	13%	12%	4%	1%	0%	38%																						
AM Peak Hour				07:00	11:00	10:00	09:00	11:00	11:00	08:00	09:00	06:00	07:00	08:00																						
Volume				1	3	7	39	155	312	283	100	19	8	840																						
PM Volumes	0	0	0	0	7	44	299	1415	2766	2105	737	145	44	7562																						
% PM					0%	0%	2%	12%	23%	17%	6%	1%	0%	62%																						
PM Peak Hour					14:00	12:00	14:00	15:00	15:00	15:00	15:00	13:00	13:00	15:00																						
Volume					2	6	45	212	405	307	99	21	7	1074																						
<b>Directional Peak Periods</b>				<b>AM 7-9</b>			<b>NOON 12-2</b>			<b>PM 4-6</b>			<b>Off Peak Volumes</b>																							
<b>All Speeds</b>	Volume			%			Volume			%			Volume			%																				
	1590			↔			13%			1896			↔			16%			1913			↔			16%			6730			↔			55%		

Street Name	Direction	Percentiles					
		15th	50th	Average	85th	95th	ADT
Crown Valley Pkwy	North Bound	48	54	A-7 54	60	65	11004
Crown Valley Pkwy	South Bound	48	54	54	60	64	12129

**SPEED**

## Crown Valley Pkwy Bet. Club House Dr &amp; Via Valle

Day: Thursday  
Date: 12/3/2020

City: Laguna Niguel  
Project #: CA20\_010035\_001

**Summary**

Time	< 15	15 - 19	20 - 24	25 - 29	30 - 34	35 - 39	40 - 44	45 - 49	50 - 54	55 - 59	60 - 64	65 - 69	70 +	Total
00:00 AM	0	0	0	0	0	0	2	8	17	9	6	3	2	47
01:00	0	0	0	0	0	0	2	7	5	4	7	1	0	26
02:00	0	0	0	0	0	1	1	1	7	6	1	0	0	18
03:00	0	0	0	0	0	1	1	5	9	7	4	6	0	33
04:00	0	0	0	0	0	0	5	6	13	17	6	5	4	56
05:00	0	0	0	0	0	6	12	36	55	65	36	12	11	233
06:00	0	0	0	1	2	6	22	71	167	179	94	29	10	581
07:00	0	0	0	1	2	3	26	166	417	416	164	32	14	1241
08:00	0	0	0	0	2	8	41	216	490	511	174	32	11	1485
09:00	0	0	0	0	3	5	57	251	500	446	167	32	8	1469
10:00	0	0	0	0	1	11	55	247	496	447	162	30	12	1461
11:00	0	0	0	0	3	4	60	277	587	456	154	37	12	1590
12:00 PM	0	0	0	0	1	8	56	308	699	479	182	37	12	1782
13:00	0	0	0	0	3	11	57	338	625	490	182	47	13	1766
14:00	0	0	0	0	3	13	100	423	679	457	174	27	9	1885
15:00	0	0	0	1	1	15	69	406	804	598	206	41	13	2154
16:00	0	0	0	1	1	9	69	393	758	563	222	53	9	2078
17:00	0	0	0	0	3	11	80	339	670	461	167	33	13	1777
18:00	0	0	0	1	0	8	57	220	439	350	127	35	9	1246
19:00	0	0	0	1	0	8	34	150	271	218	81	24	13	800
20:00	0	0	0	0	1	5	26	95	188	174	66	12	9	576
21:00	0	0	0	0	0	4	16	65	139	121	43	19	7	414
22:00	0	0	0	0	1	2	13	43	92	91	39	17	13	311
23:00	0	0	0	0	0	1	10	16	29	27	14	4	3	104
<b>Totals</b>				6	28	140	871	4087	8156	6592	2478	568	207	23133
<b>% of Totals</b>				0%	0%	1%	4%	18%	35%	28%	11%	2%	1%	100%

<b>AM Volumes</b>	0	0	0	2	14	45	284	1291	2763	2563	975	219	84	8240	
<b>% AM</b>				0%	0%	0%	1%	6%	12%	11%	4%	1%	0%	36%	
<b>AM Peak Hour</b>				06:00	09:00	10:00	11:00	11:00	11:00	08:00	08:00	11:00	07:00	11:00	
<b>Volume</b>				1	3	11	60	277	587	511	174	37	14	1590	
<b>PM Volumes</b>	0	0	0	4	14	95	587	2796	5393	4029	1503	349	123	14893	
<b>% PM</b>				0%	0%	0%	3%	12%	23%	17%	6%	2%	1%	64%	
<b>PM Peak Hour</b>				15:00	13:00	15:00	14:00	14:00	15:00	15:00	16:00	16:00	13:00	15:00	
<b>Volume</b>				1	3	15	100	423	804	598	222	53	13	2154	
<b>Directional Peak Periods</b>			<b>AM 7-9</b>				<b>NOON 12-2</b>				<b>PM 4-6</b>		<b>Off Peak Volumes</b>		
<b>All Speeds</b>			Volume	↔	%	Volume	↔	%	Volume	↔	%	Volume	↔	%	
			2726		12%	3548		15%	3855		17%	13004		56%	

Street Name	Direction	Percentiles					
		15th	50th	Average	85th	95th	ADT
Crown Valley Pkwy	Summary	48	54	A-8 54	60	64	23133

**APPENDIX B**  
**QUEUEING WORKSHEETS**

**Intersection Level Of Service Report**

**Intersection 1: Crown Valley Parkway at Project Driveway/Paseo del Niguel**

Control Type:	Two-way stop	Delay (sec / veh):	30.2
Analysis Method:	HCM 6th Edition	Level Of Service:	D
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.034

**Intersection Setup**

Name	Crown Valley Pkwy			Crown Valley Pkwy			Project Dwy			Paseo del Niguel		
Approach	Northbound			Southbound			Eastbound			Westbound		
Lane Configuration												
Turning Movement	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right
Lane Width [ft]	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00
No. of Lanes in Entry Pocket	1	0	0	1	0	0	0	0	0	0	0	0
Entry Pocket Length [ft]	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [ft]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [mph]	50.00			50.00			30.00			30.00		
Grade [%]	0.00			0.00			0.00			0.00		
Crosswalk	No			No			No			No		

**Volumes**

Name	Crown Valley Pkwy			Crown Valley Pkwy			Project Dwy			Paseo del Niguel		
Base Volume Input [veh/h]	1	749	5	4	1029	1	5	0	3	0	0	0
Base Volume Adjustment Factor	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Heavy Vehicles Percentage [%]	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00
Growth Factor	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	1	749	5	4	1029	1	5	0	3	0	0	0
Peak Hour Factor	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	1.0000	1.0000	1.0000
Other Adjustment Factor	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Total 15-Minute Volume [veh/h]	0	195	1	1	268	0	1	0	1	0	0	0
Total Analysis Volume [veh/h]	1	780	5	4	1072	1	5	0	3	0	0	0
Pedestrian Volume [ped/h]	0			0			0			0		

**Intersection Settings**

Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	
Number of Storage Spaces in Median	0	0	0	0

**Movement, Approach, & Intersection Results**

V/C, Movement V/C Ratio	0.00	0.01	0.00	0.01	0.01	0.00	0.03	0.00	0.01	0.00	0.00	0.00
d_M, Delay for Movement [s/veh]	15.00	0.00	0.00	12.31	0.00	0.00	30.21	56.55	14.39	0.00	0.00	0.00
Movement LOS	C	A	A	B	A	A	D	F	B			
95th-Percentile Queue Length [veh/ln]	0.01	0.00	0.00	0.02	0.00	0.00	0.13	0.13	0.13	0.00	0.00	0.00
95th-Percentile Queue Length [ft/ln]	0.21	0.00	0.00	0.61	0.00	0.00	3.20	3.20	3.20	0.00	0.00	0.00
d_A, Approach Delay [s/veh]	0.02			0.05			24.28			0.00		
Approach LOS	A			A			C			A		
d_I, Intersection Delay [s/veh]	0.14											
Intersection LOS	D											



**Intersection Level Of Service Report**

**Intersection 1: Crown Valley Parkway at Project Driveway/Paseo del Niguel**

Control Type:	Two-way stop	Delay (sec / veh):	49.7
Analysis Method:	HCM 6th Edition	Level Of Service:	E
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.024

**Intersection Setup**

Name	Crown Valley Pkwy			Crown Valley Pkwy			Project Dwy			Paseo del Niguel		
Approach	Northbound			Southbound			Eastbound			Westbound		
Lane Configuration	↵ ↑ ↘			↘ ↑ ↵			⊕					
Turning Movement	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right
Lane Width [ft]	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00
No. of Lanes in Entry Pocket	1	0	0	1	0	0	0	0	0	0	0	0
Entry Pocket Length [ft]	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [ft]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [mph]	50.00			50.00			30.00			30.00		
Grade [%]	0.00			0.00			0.00			0.00		
Crosswalk	No			No			No			No		

**Volumes**

Name	Crown Valley Pkwy			Crown Valley Pkwy			Project Dwy			Paseo del Niguel		
Base Volume Input [veh/h]	3	1204	18	12	1194	5	2	0	2	0	0	0
Base Volume Adjustment Factor	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Heavy Vehicles Percentage [%]	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00
Growth Factor	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	3	1204	18	12	1194	5	2	0	2	0	0	0
Peak Hour Factor	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	1.0000	1.0000	1.0000
Other Adjustment Factor	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Total 15-Minute Volume [veh/h]	1	314	5	3	311	1	1	0	1	0	0	0
Total Analysis Volume [veh/h]	3	1254	19	13	1244	5	2	0	2	0	0	0
Pedestrian Volume [ped/h]	0			0			0			0		

**Intersection Settings**

Priority Scheme	Free	Free	Stop	Stop
Flared Lane			No	
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	
Number of Storage Spaces in Median	0	0	0	0

**Movement, Approach, & Intersection Results**

V/C, Movement V/C Ratio	0.01	0.01	0.00	0.05	0.01	0.00	0.02	0.00	0.01	0.00	0.00	0.00
d_M, Delay for Movement [s/veh]	17.28	0.00	0.00	18.08	0.00	0.00	49.68	150.74	15.64	0.00	0.00	0.00
Movement LOS	C	A	A	C	A	A	E	F	C			
95th-Percentile Queue Length [veh/ln]	0.03	0.00	0.00	0.14	0.00	0.00	0.09	0.09	0.09	0.00	0.00	0.00
95th-Percentile Queue Length [ft/ln]	0.77	0.00	0.00	3.53	0.00	0.00	2.29	2.29	2.29	0.00	0.00	0.00
d_A, Approach Delay [s/veh]	0.04			0.19			32.66			0.00		
Approach LOS	A			A			D			A		
d_I, Intersection Delay [s/veh]	0.16											
Intersection LOS	E											

**APPENDIX C**  
**TRAFFIC SIGNAL WARRANT WORKSHEETS**

Signal Warrants Report For Intersection 1: Crown Valley Parkway at Project Driveway/Paseo del Niguel

Warrants Summary

Warrant	Name	Met?
#1	Eight Hour Vehicular Volume	No
#2	Four Hour Vehicular Volume	No
#3	Peak Hour	No

Intersection Warrants Parameters

Major Approaches	S, N
Minor Approaches	W
Speed > 40mph	Yes
Population < 10,000	No
Warrant Factor	70%

Warrant Analysis Traffic Volumes

Hour	Major Streets		Minor Streets
	S	N	W
1	755	1034	8
2	732	1003	8
3	717	982	8
4	672	920	7
5	596	817	6
6	589	807	6
7	581	796	6
8	529	724	6
9	521	713	6
10	513	703	5
11	445	610	5
12	415	569	4
13	408	558	4
14	302	414	3
15	302	414	3
16	211	290	2
17	121	165	1
18	121	165	1
19	68	93	1
20	38	52	0
21	23	31	0
22	8	10	0
23	8	10	0
24	8	10	0

**Warrant Analysis by Hour**

Hour	Major Lanes		Minor Lanes		Warrant 1 Condition A				Warrant 1 Condition B				Warrant 2	Warrant 3 Condition B
	Number	Volume	Number	Volume	100%	80%	70%	56%	100%	80%	70%	56%		
1	8	1789	1	8	No	No	No	No	No	No	No	No	No	No
2	8	1735	1	8	No	No	No	No	No	No	No	No	No	No
3	8	1699	1	8	No	No	No	No	No	No	No	No	No	No
4	8	1592	1	7	No	No	No	No	No	No	No	No	No	No
5	8	1413	1	6	No	No	No	No	No	No	No	No	No	No
6	8	1396	1	6	No	No	No	No	No	No	No	No	No	No
7	8	1377	1	6	No	No	No	No	No	No	No	No	No	No
8	8	1253	1	6	No	No	No	No	No	No	No	No	No	No
9	8	1234	1	6	No	No	No	No	No	No	No	No	No	No
10	8	1216	1	5	No	No	No	No	No	No	No	No	No	No
11	8	1055	1	5	No	No	No	No	No	No	No	No	No	No
12	8	984	1	4	No	No	No	No	No	No	No	No	No	No
13	8	966	1	4	No	No	No	No	No	No	No	No	No	No
14	8	716	1	3	No	No	No	No	No	No	No	No	No	No
15	8	716	1	3	No	No	No	No	No	No	No	No	No	No
16	8	501	1	2	No	No	No	No	No	No	No	No	No	No
17	8	286	1	1	No	No	No	No	No	No	No	No	No	No
18	8	286	1	1	No	No	No	No	No	No	No	No	No	No
19	8	161	1	1	No	No	No	No	No	No	No	No	No	No
20	8	90	1	0	No	No	No	No	No	No	No	No	No	No
21	8	54	1	0	No	No	No	No	No	No	No	No	No	No
22	8	18	1	0	No	No	No	No	No	No	No	No	No	No
23	8	18	1	0	No	No	No	No	No	No	No	No	No	No
24	8	18	1	0	No	No	No	No	No	No	No	No	No	No
Hours Met					0	0	0	0	0	0	0	0	0	0

**Warrant 3 Condition A**

Orientation	W
Total Stopped Delay Per Vehicle on Minor Approach (s)	22.9
Number of Lanes on Minor Street Approach	1
VehicleHours of Stopped Delay on Minor Approach (h:mm)	0:03
Delay Condition Met	No
Volume on Minor Street Approach During Same Hour	8
High Minor Volume Condition Met	No
Total Entering Volume on All Approaches During Same Hour	1797
Number of Approaches on Intersection	3
Total Volume Condition Met	Yes
Warrant Met for Approach	No
<b>Warrant Met for Intersection</b>	<b>No</b>

## Signal Warrants Report For Intersection 1: Crown Valley Parkway at Project Driveway/Paseo del Niguel

## Warrants Summary

Warrant	Name	Met?
#1	Eight Hour Vehicular Volume	No
#2	Four Hour Vehicular Volume	No
#3	Peak Hour	No

## Intersection Warrants Parameters

Major Approaches	S, N
Minor Approaches	W
Speed > 40mph	Yes
Population < 10,000	No
Warrant Factor	70%

## Warrant Analysis Traffic Volumes

Hour	Major Streets		Minor Streets
	S	N	W
1	1225	1211	4
2	1188	1175	4
3	1164	1150	4
4	1090	1078	4
5	968	957	3
6	956	945	3
7	943	932	3
8	858	848	3
9	845	836	3
10	833	823	3
11	723	714	2
12	674	666	2
13	662	654	2
14	490	484	2
15	490	484	2
16	343	339	1
17	196	194	1
18	196	194	1
19	110	109	0
20	61	61	0
21	37	36	0
22	12	12	0
23	12	12	0
24	12	12	0

**Warrant Analysis by Hour**

Hour	Major Lanes		Minor Lanes		Warrant 1 Condition A				Warrant 1 Condition B				Warrant 2	Warrant 3 Condition B
	Number	Volume	Number	Volume	100%	80%	70%	56%	100%	80%	70%	56%		
1	8	2436	1	4	No	No	No	No	No	No	No	No	No	No
2	8	2363	1	4	No	No	No	No	No	No	No	No	No	No
3	8	2314	1	4	No	No	No	No	No	No	No	No	No	No
4	8	2168	1	4	No	No	No	No	No	No	No	No	No	No
5	8	1925	1	3	No	No	No	No	No	No	No	No	No	No
6	8	1901	1	3	No	No	No	No	No	No	No	No	No	No
7	8	1875	1	3	No	No	No	No	No	No	No	No	No	No
8	8	1706	1	3	No	No	No	No	No	No	No	No	No	No
9	8	1681	1	3	No	No	No	No	No	No	No	No	No	No
10	8	1656	1	3	No	No	No	No	No	No	No	No	No	No
11	8	1437	1	2	No	No	No	No	No	No	No	No	No	No
12	8	1340	1	2	No	No	No	No	No	No	No	No	No	No
13	8	1316	1	2	No	No	No	No	No	No	No	No	No	No
14	8	974	1	2	No	No	No	No	No	No	No	No	No	No
15	8	974	1	2	No	No	No	No	No	No	No	No	No	No
16	8	682	1	1	No	No	No	No	No	No	No	No	No	No
17	8	390	1	1	No	No	No	No	No	No	No	No	No	No
18	8	390	1	1	No	No	No	No	No	No	No	No	No	No
19	8	219	1	0	No	No	No	No	No	No	No	No	No	No
20	8	122	1	0	No	No	No	No	No	No	No	No	No	No
21	8	73	1	0	No	No	No	No	No	No	No	No	No	No
22	8	24	1	0	No	No	No	No	No	No	No	No	No	No
23	8	24	1	0	No	No	No	No	No	No	No	No	No	No
24	8	24	1	0	No	No	No	No	No	No	No	No	No	No
Hours Met					0	0	0	0	0	0	0	0	0	0


**Warrant 3 Condition A**

Orientation	W
Total Stopped Delay Per Vehicle on Minor Approach (s)	30.1
Number of Lanes on Minor Street Approach	1
VehicleHours of Stopped Delay on Minor Approach (h:mm)	0:02
Delay Condition Met	No
Volume on Minor Street Approach During Same Hour	4
High Minor Volume Condition Met	No
Total Entering Volume on All Approaches During Same Hour	2440
Number of Approaches on Intersection	3
Total Volume Condition Met	Yes
Warrant Met for Approach	No
<b>Warrant Met for Intersection</b>	<b>No</b>

## APPENDIX D

### RESTRICT LEFT-TURN EGRESS AT PROJECT DRIVEWAY






n:\4300\2204357 - crowne cove, laguna hills\dwg\4357 d-1.dwg LDP 14:25:13 05-27-2021 aguilan

LINSCOTT  
LAW &  
GREENSPAN  
engineers

- KEY**
- ← = INBOUND PERCENTAGE
  - = OUTBOUND PERCENTAGE
  - = PROJECT SITE

**FIGURE D-1**  
**PROJECT TRIP DISTRIBUTION PATTERN**  
**(RESTRICT LEFT-TURN ENGRESS)**  
THE COVE AT EL NIGUEL, LAGUNA NIGUEL



ri:\4300\2204357 - crowne cove, laguna hills\dwg\4357 d-2.dwg LDP 14:37:57 05-27-2021 aguilera


LINSCOTT  
LAW &  
GREENSPAN  
engineers

NO SCALE


KEY  
 = PROJECT SITE


## FIGURE D-2

AM AND PM PEAK HOUR PROJECT TRAFFIC VOLUMES  
 (RESTRICT LEFT-TURN EGRESS)  
 THE COVE AT EL NIGUEL, LAGUNA NIGUEL




n:\4300\2204357 - crowne cove, laguna hills\dwg\4357 d-3.dwg LDP 14:41:00 05-27-2021 aguilera





NO SCALE

**KEY**

 = PROJECT SITE

## FIGURE D-3

**EXISTING PLUS PROJECT AM AND PM PEAK HOUR TRAFFIC VOLUMES  
(RESTRICT LEFT-TURN EGRESS)**  
THE COVE AT EL NIGUEL, LAGUNA NIGUEL

**Intersection Level Of Service Report**

**Intersection 1: Crown Valley Parkway at Project Driveway/Paseo del Niguel**

Control Type:	Two-way stop	Delay (sec / veh):	15.0
Analysis Method:	HCM 6th Edition	Level Of Service:	C
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.003

**Intersection Setup**

Name	Crown Valley Pkwy			Crown Valley Pkwy			Project Dwy			Paseo del Niguel		
Approach	Northbound			Southbound			Eastbound			Westbound		
Lane Configuration												
Turning Movement	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right
Lane Width [ft]	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00
No. of Lanes in Entry Pocket	1	0	0	1	0	0	0	0	0	0	0	0
Entry Pocket Length [ft]	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [ft]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [mph]	50.00			50.00			30.00			30.00		
Grade [%]	0.00			0.00			0.00			0.00		
Crosswalk	No			No			No			No		

**Volumes**

Name	Crown Valley Pkwy			Crown Valley Pkwy			Project Dwy			Paseo del Niguel		
Base Volume Input [veh/h]	1	749	5	4	1029	1	0	0	8	0	0	0
Base Volume Adjustment Factor	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Heavy Vehicles Percentage [%]	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00
Growth Factor	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	1	749	5	4	1029	1	0	0	8	0	0	0
Peak Hour Factor	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	1.0000	1.0000	1.0000
Other Adjustment Factor	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Total 15-Minute Volume [veh/h]	0	195	1	1	268	0	0	0	2	0	0	0
Total Analysis Volume [veh/h]	1	780	5	4	1072	1	0	0	8	0	0	0
Pedestrian Volume [ped/h]	0			0			0			0		

**Intersection Settings**

Priority Scheme	Free	Free	Stop	Stop
Flared Lane				
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	
Number of Storage Spaces in Median	0	0	0	0

**Movement, Approach, & Intersection Results**

V/C, Movement V/C Ratio	0.00	0.01	0.00	0.01	0.01	0.00	0.00	0.00	0.02	0.00	0.00	0.00
d_M, Delay for Movement [s/veh]	15.00	0.00	0.00	12.31	0.00	0.00	0.00	0.00	13.77	0.00	0.00	0.00
Movement LOS	C	A	A	B	A	A			B			
95th-Percentile Queue Length [veh/ln]	0.01	0.00	0.00	0.02	0.00	0.00	0.00	0.00	0.06	0.00	0.00	0.00
95th-Percentile Queue Length [ft/ln]	0.21	0.00	0.00	0.61	0.00	0.00	0.00	0.00	1.46	0.00	0.00	0.00
d_A, Approach Delay [s/veh]	0.02			0.05			13.77			0.00		
Approach LOS	A			A			B			A		
d_I, Intersection Delay [s/veh]	0.09											
Intersection LOS	C											

**Intersection Level Of Service Report**

**Intersection 1: Crown Valley Parkway at Project Driveway/Paseo del Niguel**

Control Type:	Two-way stop	Delay (sec / veh):	18.1
Analysis Method:	HCM 6th Edition	Level Of Service:	C
Analysis Period:	15 minutes	Volume to Capacity (v/c):	0.045

**Intersection Setup**

Name	Crown Valley Pkwy			Crown Valley Pkwy			Project Dwy			Paseo del Niguel		
Approach	Northbound			Southbound			Eastbound			Westbound		
Lane Configuration												
Turning Movement	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right
Lane Width [ft]	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00
No. of Lanes in Entry Pocket	1	0	0	1	0	0	0	0	0	0	0	0
Entry Pocket Length [ft]	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00
No. of Lanes in Exit Pocket	0	0	0	0	0	0	0	0	0	0	0	0
Exit Pocket Length [ft]	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Speed [mph]	50.00			50.00			30.00			30.00		
Grade [%]	0.00			0.00			0.00			0.00		
Crosswalk	No			No			No			No		

**Volumes**

Name	Crown Valley Pkwy			Crown Valley Pkwy			Project Dwy			Paseo del Niguel		
Base Volume Input [veh/h]	3	1204	18	12	1194	5	0	0	4	0	0	0
Base Volume Adjustment Factor	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Heavy Vehicles Percentage [%]	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00
Growth Factor	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
In-Process Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Site-Generated Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Diverted Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Pass-by Trips [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Existing Site Adjustment Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Other Volume [veh/h]	0	0	0	0	0	0	0	0	0	0	0	0
Total Hourly Volume [veh/h]	3	1204	18	12	1194	5	0	0	4	0	0	0
Peak Hour Factor	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	0.9600	1.0000	1.0000	1.0000
Other Adjustment Factor	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Total 15-Minute Volume [veh/h]	1	314	5	3	311	1	0	0	1	0	0	0
Total Analysis Volume [veh/h]	3	1254	19	13	1244	5	0	0	4	0	0	0
Pedestrian Volume [ped/h]	0			0			0			0		

**Intersection Settings**

Priority Scheme	Free	Free	Stop	Stop
Flared Lane				
Storage Area [veh]	0	0	0	0
Two-Stage Gap Acceptance			No	
Number of Storage Spaces in Median	0	0	0	0

**Movement, Approach, & Intersection Results**

V/C, Movement V/C Ratio	0.01	0.01	0.00	0.05	0.01	0.00	0.00	0.00	0.01	0.00	0.00	0.00
d_M, Delay for Movement [s/veh]	17.28	0.00	0.00	18.08	0.00	0.00	0.00	0.00	14.92	0.00	0.00	0.00
Movement LOS	C	A	A	C	A	A			B			
95th-Percentile Queue Length [veh/ln]	0.03	0.00	0.00	0.14	0.00	0.00	0.00	0.00	0.03	0.00	0.00	0.00
95th-Percentile Queue Length [ft/ln]	0.77	0.00	0.00	3.53	0.00	0.00	0.00	0.00	0.83	0.00	0.00	0.00
d_A, Approach Delay [s/veh]	0.04			0.19			14.92			0.00		
Approach LOS	A			A			B			A		
d_I, Intersection Delay [s/veh]	0.14											
Intersection LOS	C											