



January 22, 2019

Mr. Shawn Knapp  
Town of Moraga  
329 Rheem Boulevard  
Moraga, CA 94556

**RE: *St. Marys Road Roundabout Project, Moraga, CA  
Draft Traffic Letter***

Dear Mr. Knapp:

The St. Marys Road Roundabout Project (“Project”) is proposing to construct roundabouts at two existing side street stop controlled (SSSC) intersections in the Town of Moraga (Town) in Contra Costa County, CA to improve the physical and operational characteristics of St. Marys Road. After discussions with the Town, this memorandum evaluated the traffic impacts of the proposed roundabouts. The following discusses the methodology, analysis, and results of the comparison.

## **BACKGROUND**

The proposed roundabouts are to be located along St. Marys Road at the intersections of Rheem Boulevard and Bollinger Canyon Road. **Figure 1** illustrates the location of the study intersections in relation to the adjacent roadway network in Moraga. The existing lane geometry configuration lacks acceptable sight distance due to horizontal and vertical constraints. Therefore, roundabouts are proposed to replace the existing SSSC of the two study intersections.

## **METHODOLOGY**

### **Study Intersections**

As part of this evaluation, study intersections were reviewed to determine the existing traffic operations at the following study intersections:


1. St. Marys Road / Rheem Boulevard – SSSC
2. St. Marys Road / Bollinger Canyon Road – SSSC

AM and PM peak hour traffic volumes for all study scenarios at the two study intersections were derived from the *Bollinger Valley Project Final EIR*<sup>1</sup> and are provided in the **Attachments**.

---

<sup>1</sup> *Bollinger Valley Project Final EIR, Appendix B: 2014 Traffic Analysis*, January 2017.

Figure 1 – Study Intersections



**Analysis Scenarios**

To determine the potential project impacts, multiple scenarios were analyzed in the AM and PM peak hours:

- Existing (2017) Conditions – Based on traffic counts derived from the *Bollinger Valley Project Final EIR* and existing roadway geometry and traffic control.
- Existing (2017) Plus Project Conditions – Based on existing traffic volumes added to the proposed roadway geometry and traffic control assumed for this scenario.
- Cumulative (2040) Conditions – Based on future year traffic projections which are derived from the *Bollinger Valley Project Final EIR*. This scenario assumes roadway geometry and traffic control present in the forecast horizon.
- Cumulative (2040) Plus Project Conditions – Based on future year traffic projections added to the proposed roadway geometry and traffic control assumed for this scenario.

**Level of Service Standards**

Analysis of significant environmental impacts at intersections were based on the concept of Level of Service (LOS). The LOS of an intersection is a qualitative measure used to describe operational conditions. LOS ranges from A (best), which represents minimal delay, to F (worst), which represents heavy delay and a facility that is operating at or near its functional capacity. **Table 1** provides a definition for each level of service category. Levels of service for this study were determined using methods defined in the Highway Capacity Manual, 2010 (HCM) and appropriate traffic analysis software.

The HCM includes procedures for analyzing side-street stop-controlled (SSSC), all-way stop-controlled (AWSC), roundabouts, and signalized intersections. The SSSC procedure defines LOS as a function of average control delay for the worst minor street movement or major street left-turn. Conversely, the AWSC and signalized intersection procedures define LOS as a function of average control delay for the intersection as a whole. **Table 2** relates the operational characteristics associated with each LOS category for signalized and unsignalized intersections.

**Table 1 - Level of Service Definitions**

| Level of Service | Description   |
|------------------|---|
| A                | Free flow with no delays. Users are virtually unaffected by others in the traffic stream. At signalized intersections, turning movements are easily made and all queues clear in a single signal cycle.                             |
| B                | Stable traffic. Traffic flows smoothly with few delays. An occasional approach phase is fully utilized. Drivers begin to feel somewhat restricted within platoons of vehicles.  |
| C                | Stable flow but the operation of individual users becomes affected by other vehicles. Modest delays. Major approach phases fully utilized. Backups may develop behind turning vehicles.   |
| D                | Approaching unstable flow. Operation of individual users becomes significantly affected by other vehicles. Delays may be more than one cycle during peak hours. Queues may develop but dissipate rapidly, without excessive delays. |
| E                | Unstable flow with operating conditions at or near the capacity level. Long delays and vehicle queuing.   |
| F                | Forced or breakdown flow that causes reduced capacity. Traffic demand exceeds the capacity. Stop and go traffic conditions. Excessive long delays and vehicle queuing.  |

Source: Transportation Research Board, *Highway Capacity Manual 2010*, National Research Council, 2010

**Table 2 – Signalized and Unsignalized Intersection Level of Service Definitions**

| Level of Service | Signalized<br>(Avg. control delay per vehicle sec/veh.) | Unsignalized<br>(Avg. control delay per vehicle sec/veh.) |
|------------------|---|---|
| A                | ≤ 10.0  | ≤ 10.0  |
| B                | > 10.0 – 20.0   | > 10.0 – 15.0   |
| C                | > 20.0 – 35.0   | > 15.0 – 25.0   |
| D                | > 35.0 – 55.0   | > 25.0 – 35.0   |
| E                | > 55.0 – 80.0   | > 35.0 – 50.0   |
| F                | > 80.0  | > 50.0  |

The intersection level of service (LOS) standards are outlined in the Moraga General Plan. The LOS standards for the Town of Moraga is LOS C for all intersections.

Based on the *Saint Mary’s College Campus Master Plan DEIR*, a significant impact would occur if the proposed project caused the following to unsignalized intersections:

- For unsignalized intersections operating at LOS C or better without the project, a significant impact would occur if the project degrades the intersection from an acceptable LOS to an unacceptable LOS D or worse and if the intersection meets the peak hour signal warrant in plus project conditions.

The Contra Costa Transportation Authority (CCTA) and its subsequent Regional Transportation Planning Committees have also set various standards on specific roadways, called Multi-Modal Transportation Service Objectives (MTSO’s). These MTSO’s are specific to each region and regulate the routes of regional significance. However, all study intersections are not designated as regionally significant and therefore no MTSO’s were evaluated.

**Analysis Methodology**

The study intersections for Existing and Cumulative conditions were analyzed in Synchro software using Highway Capacity Manual (HCM) 2010 methodology for the AM and PM peak periods.

The study intersections for Existing Plus Project and Cumulative Plus Project were evaluated in Sidra Intersection software using the HCM 2010 methodology with the exception of parameters A and B resulting in a change in the default capacity. Parameters A and B were modified based on the recommended factors in the Caltrans *Roundabout Geometric Design Guidance* to adjust for the driver characteristics in California. **Table 3** presents the comparison between the default HCM 2010 parameters in Sidra and the recommended adjusted factors.

**Table 3 – Roundabout Model Parameters for Entry Capacity**

| Roundabout Type                         | Default HCM 2010 Parameters |         | Modified HCM Parameters |         |
|---|-----------------------------|---------|-------------------------|---------|
|   | A                           | B       | A                       | B       |
| Single-Lane Circulating System          |                             |         |                         |         |
| • Single-Lane Entry                     | 1130                        | 0.00100 | 1440                    | 0.00100 |
| • Multi-Lane Entry (apply to all lanes) | 1130                        | 0.00100 | 1440                    | 0.00100 |
| Multi-Lane Circulating System           |                             |         |                         |         |
| • Single-Lane Entry                     | 1130                        | 0.00070 | –                       | –       |
| • Multi-Lane Entry                      |                             |         |                         |         |
| o Dominate Lane (right lane)            | 1130                        | 0.00070 | 1640                    | 0.00090 |
| o Dominate Lane (left lane)             | 1130                        | 0.00075 | 1640                    | 0.00100 |

**EXISTING (2017) CONDITIONS**

Traffic operations were evaluated at the study intersections under Existing traffic conditions. Results of the analysis are presented in **Table 4**. **Table 4** shows the existing LOS and delay for each of the study intersections. All study intersections operate at an acceptable level of service in the Existing scenario. Analysis sheets are provided in the **Attachments**.

**Table 4 – Existing Intersection Level of Service Summary**

| # | Intersection                            | LOS Criteria <sup>1</sup> | Jurisdiction | Control | Existing |       |         |       |
|---|---|---------------------------|--------------|---------|----------|-------|---------|-------|
|   |   |                           |              |         | AM Peak  |       | PM Peak |       |
|   |   |                           |              |         | LOS      | Delay | LOS     | Delay |
| 1 | St. Mary's Road / Rheem Boulevard       | C                         | Town         | SSSC    | A        | 3.6   | A       | 3.9   |
|   | <i>Worst Approach</i>                   |                           |              |         | C        | 18.5  | C       | 20.4  |
| 2 | St. Mary's Road / Bollinger Canyon Road | C                         | Town         | SSSC    | A        | 1.5   | A       | 0.9   |
|   | <i>Worst Approach</i>                   |                           |              |         | C        | 16.5  | B       | 16.2  |

Note: Intersections that are operating below acceptable levels are shown in **BOLD**. Intersections were analyzed using HCM2010 methodology within Synchro software

<sup>1</sup>Town = Town of Moraga

**Existing Transit Facilities**

The County Connection provides transit services within Moraga and nearby cities in Central Contra Costa County. The following County Connection routes operate near the proposed project but do not operate through the study intersections:

**Route 6** is a bus service that operates between the Orinda BART station and the Lafayette BART station while serving St. Mary's College along its route. Within the vicinity of the project site, Route 6 travels on St. Marys Road. On weekdays, Route 6 operates between 5:40 AM and 8:45 PM on 40-minute to 120-minute headways. On weekends, Route 6 operates between 9:24 AM to 6:09 PM on 80-minute headways.

**Route 250** is a bus route that operates between the Pittsburg/Bay Point BART station and St. Mary's College. Within the vicinity of the project site, Route 250 travels on St. Marys Road. On weekdays, Route 250 operates between 9:20 PM to 1:25 AM (of the following day). On weekends, Route 250 operates between 6:20 PM to 1:25 AM (of the following day).

**Existing Pedestrian Facilities**

There is a lack of sidewalks and crosswalks provided near the study intersections for pedestrians to walk to and from nearby land uses. A crosswalk is provided on the west side of the intersection of St Marys Road and Rheem Boulevard and provides access to the Lafayette/Moraga Regional Trail.

**Existing Bicycle Facilities**

The Lafayette/Moraga Regional Trail is a Class I bicycle path that runs near the project area. The Lafayette/Moraga Regional Trail runs adjacent to St Marys Road between the intersection of Moraga Road and St Marys Road and extends beyond the town's limits into the City of Lafayette. A bicycle route is proposed along St Marys Road between Stafford Road to the outside of the Moraga town

limits. Bicycle routes are also proposed along Rheem Boulevard between St Marys Road and Moraga Road and along Bollinger Canyon Road between St Marys Road and north of Valley Hill Drive.

### EXISTING (2017) PLUS PROJECT CONDITIONS

Existing Plus Project traffic conditions were evaluated at the study intersections based on the following roadway improvements:

1. St. Marys Road / Rheem Boulevard – Intersection control to be changed from a SSSC to a roundabout
2. St. Marys Road / Bollinger Canyon Road – Intersection control to be changed from a SSSC to a mini-roundabout

The concept layout for the proposed roundabouts are provided in the **Attachments**.

Existing Plus Project volumes were assumed to be the same as Existing volumes since traffic is not expected to be redirected or changed with the addition of the roundabouts at the study intersections. Results of the analysis are presented in **Table 5**. As shown in **Table 5**, all study intersections would operate at acceptable levels of service in the Existing Plus Project scenario. Analysis sheets are provided in the **Attachments**.

**Table 5 – Existing Plus Project Intersection Level of Service Summary**

| # | Intersection                           | LOS Criteria <sup>1</sup> | Jurisdiction | Control <sup>2</sup>   | Existing |       |         |       | Existing + Project |       |        |         |       |        |
|---|--|---------------------------|--------------|------------------------|----------|-------|---------|-------|--------------------|-------|--------|---------|-------|--------|
|   |  |                           |              |                        | AM Peak  |       | PM Peak |       | AM Peak            |       |        | PM Peak |       |        |
|   |  |                           |              |                        | LOS      | Delay | LOS     | Delay | LOS                | Delay | ΔDelay | LOS     | Delay | ΔDelay |
| 1 | St. Marys Road / Rheem Boulevard       | C                         | Town         | SSSC / Roundabout      | A        | 3.6   | A       | 3.9   | A                  | 5.6   | -12.9  | A       | 6.0   | -14.4  |
|   | <i>Worst Approach</i>                  |                           |              |                        | C        | 18.5  | C       | 20.4  |                    |       |        |         |       |        |
| 2 | St. Marys Road / Bollinger Canyon Road | C                         | Town         | SSSC / Mini-Roundabout | A        | 1.5   | A       | 0.9   | A                  | 5.6   | -10.9  | A       | 5.8   | -10.4  |
|   | <i>Worst Approach</i>                  |                           |              |                        | C        | 16.5  | B       | 16.2  |                    |       |        |         |       |        |

Note: Intersections that are operating below acceptable levels are shown in **BOLD** and significant impacts are highlighted.

Intersections were analyzed using HCM2010 methodology within Sidra software

<sup>1</sup> Town = Town of Moraga

<sup>2</sup> With the addition of the project, Intersection #1 becomes a roundabout and Intersection #2 becomes a mini-roundabout

### CUMULATIVE (2040) CONDITIONS

Traffic operations were evaluated at the study intersections under Cumulative traffic conditions. Cumulative traffic volumes were derived from the *Bollinger Valley Project Final EIR*. Under Cumulative traffic conditions, there is no new lane geometry improvements to the study intersections, therefore Existing lane geometry was assumed in the Cumulative conditions. Results of the analysis are presented in **Table 6**. As shown in **Table 6**, the following intersections operate at unacceptable levels of service in the Cumulative scenario:

- #1 – St. Marys Road / Rheem Boulevard (AM and PM Peak Hours)
- #2 – St. Marys Road / Bollinger Canyon Road (AM and PM Peak Hours)

Analysis sheets are provided in the **Attachments**.



**Table 6 – Cumulative Intersection Level of Service Summary**

| # | Intersection                            | LOS Criteria <sup>1</sup> | Jurisdiction | Control | Long-term (2035) |             |          |             |
|---|---|---------------------------|--------------|---------|------------------|-------------|----------|-------------|
|   |   |                           |              |         | AM Peak          |             | PM Peak  |             |
|   |   |                           |              |         | LOS              | Delay       | LOS      | Delay       |
| 1 | St. Mary's Road / Rheem Boulevard       | C                         | Town         | SSSC    | A                | 5.3         | A        | 9.4         |
|   | <i>Worst Approach</i>                   |                           |              |         | <b>D</b>         | <b>30.6</b> | <b>F</b> | <b>57.7</b> |
| 2 | St. Mary's Road / Bollinger Canyon Road | C                         | Town         | SSSC    | A                | 3.8         | A        | 2.4         |
|   | <i>Worst Approach</i>                   |                           |              |         | <b>D</b>         | <b>26.2</b> | <b>D</b> | <b>26.4</b> |

Note: Intersections that are operating below acceptable levels are shown in **BOLD**.  
 Intersections were analyzed using HCM 2010 methodology within Synchro software

<sup>1</sup>Town = Town of Moraga

### CUMULATIVE (2040) PLUS PROJECT CONDITIONS

Traffic operations were evaluated at the study intersections under Cumulative Plus project traffic conditions based on the lane geometry proposed by the project. Cumulative Plus Project volumes were assumed to be the same as Cumulative volumes since traffic is not expected to be redirected or changed with the addition of the roundabouts at the study intersections. Results of the analysis are presented in **Table 7**. As shown in **Table 7**, all study intersections would operate at acceptable levels of service in the Cumulative Plus Project scenario. Analysis sheets are provided in the **Attachments**.

**Table 7 – Cumulative Plus Project Intersection Level of Service Summary**

| # | Intersection                            | LOS Criteria | Jurisdiction <sup>1</sup> | Control <sup>2</sup>   | Long-term (2035) |             |          |             | Long-term (2035) + Project |        |         |        |     |       |
|---|---|--------------|---------------------------|------------------------|------------------|-------------|----------|-------------|----------------------------|--------|---------|--------|-----|-------|
|   |   |              |                           |                        | AM Peak          |             | PM Peak  |             | AM Peak                    |        | PM Peak |        |     |       |
|   |   |              |                           |                        | LOS              | Delay       | LOS      | Delay       | LOS                        | ΔDelay | LOS     | ΔDelay |     |       |
| 1 | St. Mary's Road / Rheem Boulevard       | C            | Town                      | SSSC / Roundabout      | A                | 5.3         | A        | 9.4         | A                          | 7.1    | -23.5   | A      | 7.8 | -49.9 |
|   | <i>Worst Approach</i>                   |              |                           |                        | <b>D</b>         | <b>30.6</b> | <b>F</b> | <b>57.7</b> |                            |        |         |        |     |       |
| 2 | St. Mary's Road / Bollinger Canyon Road | C            | Town                      | SSSC / Mini-Roundabout | A                | 3.8         | A        | 2.4         | A                          | 6.8    | -19.4   | A      | 7.7 | -18.7 |
|   | <i>Worst Approach</i>                   |              |                           |                        | <b>D</b>         | <b>26.2</b> | <b>D</b> | <b>26.4</b> |                            |        |         |        |     |       |

Note: Intersections that are operating below acceptable levels are shown in **BOLD** and significant impacts are highlighted.  
 Intersections were analyzed using HCM2010 methodology within Sidra software

<sup>1</sup>Town = Town of Moraga

<sup>2</sup>With the addition of the project, Intersection #1 becomes a roundabout and Intersection #2 becomes a mini-roundabout

### BICYCLE AND PEDESTRIAN FACILITIES

As noted in the Existing condition, there is a lack of sidewalks and crosswalks near the two study intersections. Pedestrians can cross the intersection of St Marys Road and Rheem Boulevard using the west crosswalk to access the Lafayette/Moraga Regional Trail. With the addition of the roundabout at the intersection of St Marys Road and Rheem Boulevard, vehicles approach the intersection at a lower speed and the pedestrian crosswalk is located further from the main roadway, thereby improving the safety of pedestrians. There is also a pedestrian refuge island separating the inbound and outbound vehicles on the Rheem Boulevard leg of the intersection, making it safer for pedestrians to cross one direction of travel at a time. Since the proposed project does not conflict with any adopted policies or plans related to pedestrian activity, the proposed project will have **less than significant impact** on pedestrian circulation.

Bicycles have access to the study intersection of St Marys Road and Rheem Boulevard using the Lafayette/Moraga Regional Trail. The existing trail crosses Rheem Boulevard using the western

crosswalk. The proposed roundabout will relocate this crosswalk to the west and improve the safety of bicyclists by improving the visibility of bicyclists in the crosswalk and reducing vehicle speeds through the roundabout. The proposed project would improve the safety of bicyclists. Since the proposed project does not conflict with any adopted policies or plans related to bicycle activity, the proposed project will have a **less than significant impact** on bicycle circulation.

## CONSTRUCTION TRAFFIC

The day-to-day construction operations associated with demolition and construction of the roundabouts will generate traffic related to construction employees and construction equipment. This will also include heavy vehicles hauling construction material to and from the site. In addition, the construction of these roundabouts will result in either a partial or full closure of these two intersections. Since alternative detour paths are limited in this area, appropriate communication to users will need to be planned and implemented. Therefore, a traffic control plan is recommended to be developed and instituted during construction activities as a mitigation.

## CONCLUSIONS

The results of the traffic evaluation demonstrated that the proposed project is not expected to create any significant impacts at the study intersections or on pedestrian and bicycle access and circulation. All study intersections are expected to operate at acceptable levels of service in the Existing Plus Project and Cumulative Plus Project conditions. However, there may be construction impacts related to partial or full closures of the two intersections, and a traffic control plan will be needed for mitigation of this impact.

Sincerely,




Ben Huie, P.E.  
California Professional Engineer #C76682

Attachments:

- Attachment A – Traffic Counts
- Attachment B – Concept Layout
- Attachment C – LOS Outputs





**LEGEND**

XX (YY) AM (PM) Peak Hour Traffic Volumes


Signalized Intersection

Stop Sign

Figure 2A

Existing Conditions  
Peak Hour Traffic Volumes





**LEGEND**

XX (YY) AM (PM) Peak Hour Traffic Volumes


Signalized Intersection

Stop Sign

Figure 2B

Existing Conditions  
Peak Hour Traffic Volumes





**LEGEND**

XX (YY) AM (PM) Peak Hour Traffic Volumes


Signalized Intersection

Stop Sign

Figure 7A

Cumulative Plus Project Conditions  
Peak Hour Traffic Volumes





**LEGEND**

XX (YY) AM (PM) Peak Hour Traffic Volumes

Signalized Intersection

Stop Sign


Figure 7B



Cumulative Plus Project Conditions  
Peak Hour Traffic Volumes





**LEGEND:**  
 HMA PAVEMENT WIDENING



Maraga St. Mary Roundabout  
1: St. Mary's Rd & Rheem Blvd

Existing  
AM Peak Hour

Intersection

Int Delay, s/veh 3.6

| Movement                 | EBL  | EBT  | WBT  | WBR  | SBL  | SBR  |
|--------------------------|------|------|------|------|------|------|
| Lane Configurations      |      | ↕    | ↕    |      | ↕    | ↕    |
| Traffic Vol, veh/h       | 32   | 312  | 341  | 129  | 109  | 71   |
| Future Vol, veh/h        | 32   | 312  | 341  | 129  | 109  | 71   |
| Conflicting Peds, #/hr   | 0    | 0    | 0    | 0    | 0    | 0    |
| Sign Control             | Free | Free | Free | Free | Stop | Stop |
| RT Channelized           | -    | None | -    | None | -    | None |
| Storage Length           | -    | -    | -    | -    | 50   | 0    |
| Veh in Median Storage, # | -    | 0    | 0    | -    | 0    | -    |
| Grade, %                 | -    | 0    | 0    | -    | 0    | -    |
| Peak Hour Factor         | 92   | 92   | 92   | 92   | 92   | 92   |
| Heavy Vehicles, %        | 2    | 2    | 2    | 2    | 2    | 2    |
| Mvmt Flow                | 35   | 339  | 371  | 140  | 118  | 77   |

| Major/Minor          | Major1 | Major2 | Minor2 |
|----------------------|--------|--------|--------|
| Conflicting Flow All | 511    | 0      | 850    |
| Stage 1              | -      | -      | 441    |
| Stage 2              | -      | -      | 409    |
| Critical Hdwy        | 4.12   | -      | 6.42   |
| Critical Hdwy Stg 1  | -      | -      | 5.42   |
| Critical Hdwy Stg 2  | -      | -      | 5.42   |
| Follow-up Hdwy       | 2.218  | -      | 3.518  |
| Pot Cap-1 Maneuver   | 1054   | -      | 331    |
| Stage 1              | -      | -      | 648    |
| Stage 2              | -      | -      | 671    |
| Platoon blocked, %   | -      | -      | -      |
| Mov Cap-1 Maneuver   | 1054   | -      | 317    |
| Mov Cap-2 Maneuver   | -      | -      | 317    |
| Stage 1              | -      | -      | 648    |
| Stage 2              | -      | -      | 643    |

| Approach             | EB  | WB | SB   |
|----------------------|-----|----|------|
| HCM Control Delay, s | 0.8 | 0  | 18.5 |
| HCM LOS              |     |    | C    |

| Minor Lane/Major Mvmt | EBL   | EBT | WBT | WBR | SBLn1 | SBLn2 |
|-----------------------|-------|-----|-----|-----|-------|-------|
| Capacity (veh/h)      | 1054  | -   | -   | -   | 317   | 616   |
| HCM Lane V/C Ratio    | 0.033 | -   | -   | -   | 0.374 | 0.125 |
| HCM Control Delay (s) | 8.5   | 0   | -   | -   | 23    | 11.7  |
| HCM Lane LOS          | A     | A   | -   | -   | C     | B     |
| HCM 95th %tile Q(veh) | 0.1   | -   | -   | -   | 1.7   | 0.4   |



Maraga St. Mary Roundabout  
2: Bollinger Canyon Rd & St. Mary's Rd

Existing  
AM Peak Hour

| Intersection             |      |      |      |      |      |      |
|--------------------------|------|------|------|------|------|------|
| Int Delay, s/veh         | 1.5  |      |      |      |      |      |
| Movement                 | EBT  | EBR  | WBL  | WBT  | NBL  | NBR  |
| Lane Configurations      | ↑    | ↗    |      | ↖    | ↖    | ↗    |
| Traffic Vol, veh/h       | 394  | 27   | 5    | 414  | 54   | 26   |
| Future Vol, veh/h        | 394  | 27   | 5    | 414  | 54   | 26   |
| Conflicting Peds, #/hr   | 0    | 0    | 0    | 0    | 0    | 0    |
| Sign Control             | Free | Free | Free | Free | Stop | Stop |
| RT Channelized           | -    | Free | -    | None | -    | None |
| Storage Length           | -    | 100  | -    | -    | 0    | 20   |
| Veh in Median Storage, # | 0    | -    | -    | 0    | 0    | -    |
| Grade, %                 | 0    | -    | -    | 0    | 0    | -    |
| Peak Hour Factor         | 92   | 92   | 92   | 92   | 92   | 92   |
| Heavy Vehicles, %        | 2    | 2    | 2    | 2    | 2    | 2    |
| Mvmt Flow                | 428  | 29   | 5    | 450  | 59   | 28   |

| Major/Minor          | Major1 | Major2 | Minor1 |   |             |
|----------------------|--------|--------|--------|---|-------------|
| Conflicting Flow All | 0      | -      | 428    | 0 | 889 428     |
| Stage 1              | -      | -      | -      | - | 428 -       |
| Stage 2              | -      | -      | -      | - | 461 -       |
| Critical Hdwy        | -      | -      | 4.12   | - | 6.42 6.22   |
| Critical Hdwy Stg 1  | -      | -      | -      | - | 5.42 -      |
| Critical Hdwy Stg 2  | -      | -      | -      | - | 5.42 -      |
| Follow-up Hdwy       | -      | -      | 2.218  | - | 3.518 3.318 |
| Pot Cap-1 Maneuver   | -      | 0      | 1131   | - | 314 627     |
| Stage 1              | -      | 0      | -      | - | 657 -       |
| Stage 2              | -      | 0      | -      | - | 635 -       |
| Platoon blocked, %   | -      | -      | -      | - | -           |
| Mov Cap-1 Maneuver   | -      | -      | 1131   | - | 312 627     |
| Mov Cap-2 Maneuver   | -      | -      | -      | - | 312 -       |
| Stage 1              | -      | -      | -      | - | 657 -       |
| Stage 2              | -      | -      | -      | - | 631 -       |

| Approach             | EB | WB  | NB   |
|----------------------|----|-----|------|
| HCM Control Delay, s | 0  | 0.1 | 16.5 |
| HCM LOS              |    |     | C    |

| Minor Lane/Major Mvmt | NBLn1 | NBLn2 | EBT | WBL   | WBT |
|-----------------------|-------|-------|-----|-------|-----|
| Capacity (veh/h)      | 312   | 627   | -   | 1131  | -   |
| HCM Lane V/C Ratio    | 0.188 | 0.045 | -   | 0.005 | -   |
| HCM Control Delay (s) | 19.2  | 11    | -   | 8.2   | 0   |
| HCM Lane LOS          | C     | B     | -   | A     | A   |
| HCM 95th %tile Q(veh) | 0.7   | 0.1   | -   | 0     | -   |

Maraga St. Mary Roundabout  
1: St. Mary's Rd & Rheem Blvd

Existing  
PM Peak Hour

Intersection

Int Delay, s/veh 3.9

| Movement                 | EBL  | EBT  | WBT  | WBR  | SBL  | SBR  |
|--------------------------|------|------|------|------|------|------|
| Lane Configurations      |      | ↕    | ↕    |      | ↕    | ↕    |
| Traffic Vol, veh/h       | 64   | 424  | 233  | 90   | 104  | 55   |
| Future Vol, veh/h        | 64   | 424  | 233  | 90   | 104  | 55   |
| Conflicting Peds, #/hr   | 0    | 0    | 0    | 0    | 0    | 0    |
| Sign Control             | Free | Free | Free | Free | Stop | Stop |
| RT Channelized           | -    | None | -    | None | -    | None |
| Storage Length           | -    | -    | -    | -    | 50   | 0    |
| Veh in Median Storage, # | -    | 0    | 0    | -    | 0    | -    |
| Grade, %                 | -    | 0    | 0    | -    | 0    | -    |
| Peak Hour Factor         | 92   | 92   | 92   | 92   | 92   | 92   |
| Heavy Vehicles, %        | 2    | 2    | 2    | 2    | 2    | 2    |
| Mvmt Flow                | 70   | 461  | 253  | 98   | 113  | 60   |

| Major/Minor          | Major1 | Major2 | Minor2 |   |             |
|----------------------|--------|--------|--------|---|-------------|
| Conflicting Flow All | 351    | 0      | -      | 0 | 902 302     |
| Stage 1              | -      | -      | -      | - | 302 -       |
| Stage 2              | -      | -      | -      | - | 600 -       |
| Critical Hdwy        | 4.12   | -      | -      | - | 6.42 6.22   |
| Critical Hdwy Stg 1  | -      | -      | -      | - | 5.42 -      |
| Critical Hdwy Stg 2  | -      | -      | -      | - | 5.42 -      |
| Follow-up Hdwy       | 2.218  | -      | -      | - | 3.518 3.318 |
| Pot Cap-1 Maneuver   | 1208   | -      | -      | - | 308 738     |
| Stage 1              | -      | -      | -      | - | 750 -       |
| Stage 2              | -      | -      | -      | - | 548 -       |
| Platoon blocked, %   |        | -      | -      | - |             |
| Mov Cap-1 Maneuver   | 1208   | -      | -      | - | 284 738     |
| Mov Cap-2 Maneuver   | -      | -      | -      | - | 284 -       |
| Stage 1              | -      | -      | -      | - | 750 -       |
| Stage 2              | -      | -      | -      | - | 505 -       |

| Approach             | EB  | WB | SB   |
|----------------------|-----|----|------|
| HCM Control Delay, s | 1.1 | 0  | 20.4 |
| HCM LOS              |     |    | C    |

| Minor Lane/Major Mvmt | EBL   | EBT | WBT | WBR | SBLn1 | SBLn2 |
|-----------------------|-------|-----|-----|-----|-------|-------|
| Capacity (veh/h)      | 1208  | -   | -   | -   | 284   | 738   |
| HCM Lane V/C Ratio    | 0.058 | -   | -   | -   | 0.398 | 0.081 |
| HCM Control Delay (s) | 8.2   | 0   | -   | -   | 25.8  | 10.3  |
| HCM Lane LOS          | A     | A   | -   | -   | D     | B     |
| HCM 95th %tile Q(veh) | 0.2   | -   | -   | -   | 1.8   | 0.3   |

Maraga St. Mary Roundabout  
2: Bollinger Canyon Rd & St. Mary's Rd

Existing  
PM Peak Hour

Intersection

Int Delay, s/veh 0.9

| Movement                 | EBT  | EBR  | WBL  | WBT  | NBL  | NBR  |
|--------------------------|------|------|------|------|------|------|
| Lane Configurations      | ↑    | ↗    |      | ↖    | ↖    | ↗    |
| Traffic Vol, veh/h       | 487  | 45   | 17   | 305  | 25   | 10   |
| Future Vol, veh/h        | 487  | 45   | 17   | 305  | 25   | 10   |
| Conflicting Peds, #/hr   | 0    | 0    | 0    | 0    | 0    | 0    |
| Sign Control             | Free | Free | Free | Free | Stop | Stop |
| RT Channelized           | -    | Free | -    | None | -    | None |
| Storage Length           | -    | 100  | -    | -    | 0    | 20   |
| Veh in Median Storage, # | 0    | -    | -    | 0    | 0    | -    |
| Grade, %                 | 0    | -    | -    | 0    | 0    | -    |
| Peak Hour Factor         | 92   | 92   | 92   | 92   | 92   | 92   |
| Heavy Vehicles, %        | 2    | 2    | 2    | 2    | 2    | 2    |
| Mvmt Flow                | 529  | 49   | 18   | 332  | 27   | 11   |

Major/Minor

|                      | Major1 | Major2 | Minor1 |   |       |
|----------------------|--------|--------|--------|---|-------|
| Conflicting Flow All | 0      | -      | 529    | 0 | 897   |
| Stage 1              | -      | -      | -      | - | 529   |
| Stage 2              | -      | -      | -      | - | 368   |
| Critical Hdwy        | -      | -      | 4.12   | - | 6.42  |
| Critical Hdwy Stg 1  | -      | -      | -      | - | 5.42  |
| Critical Hdwy Stg 2  | -      | -      | -      | - | 5.42  |
| Follow-up Hdwy       | -      | -      | 2.218  | - | 3.518 |
| Pot Cap-1 Maneuver   | -      | 0      | 1038   | - | 310   |
| Stage 1              | -      | 0      | -      | - | 591   |
| Stage 2              | -      | 0      | -      | - | 700   |
| Platoon blocked, %   | -      | -      | -      | - | -     |
| Mov Cap-1 Maneuver   | -      | -      | 1038   | - | 303   |
| Mov Cap-2 Maneuver   | -      | -      | -      | - | 303   |
| Stage 1              | -      | -      | -      | - | 591   |
| Stage 2              | -      | -      | -      | - | 685   |

Approach

|                      | EB | WB  | NB   |
|----------------------|----|-----|------|
| HCM Control Delay, s | 0  | 0.5 | 16.2 |
| HCM LOS              |    |     | C    |

Minor Lane/Major Mvmt

|                       | NBLn1 | NBLn2 | EBT | WBL   | WBT |
|-----------------------|-------|-------|-----|-------|-----|
| Capacity (veh/h)      | 303   | 550   | -   | 1038  | -   |
| HCM Lane V/C Ratio    | 0.09  | 0.02  | -   | 0.018 | -   |
| HCM Control Delay (s) | 18    | 11.7  | -   | 8.5   | 0   |
| HCM Lane LOS          | C     | B     | -   | A     | A   |
| HCM 95th %tile Q(veh) | 0.3   | 0.1   | -   | 0.1   | -   |

Maraga St. Mary Roundabout  
1: St. Mary's Rd & Rheem Blvd

Cumulative  
AM Peak Hour

Intersection

Int Delay, s/veh 5.3

Movement EBL EBT WBT WBR SBL SBR

|                          |      |      |      |      |      |      |
|--------------------------|------|------|------|------|------|------|
| Lane Configurations      |      | ↕    | ↕    |      | ↕    | ↕    |
| Traffic Vol, veh/h       | 37   | 418  | 429  | 153  | 125  | 82   |
| Future Vol, veh/h        | 37   | 418  | 429  | 153  | 125  | 82   |
| Conflicting Peds, #/hr   | 0    | 0    | 0    | 0    | 0    | 0    |
| Sign Control             | Free | Free | Free | Free | Stop | Stop |
| RT Channelized           | -    | None | -    | None | -    | None |
| Storage Length           | -    | -    | -    | -    | 50   | 0    |
| Veh in Median Storage, # | -    | 0    | 0    | -    | 0    | -    |
| Grade, %                 | -    | 0    | 0    | -    | 0    | -    |
| Peak Hour Factor         | 92   | 92   | 92   | 92   | 92   | 92   |
| Heavy Vehicles, %        | 2    | 2    | 2    | 2    | 2    | 2    |
| Mvmt Flow                | 40   | 454  | 466  | 166  | 136  | 89   |

Major/Minor Major1 Major2 Minor2

|                      |       |   |   |   |       |       |
|----------------------|-------|---|---|---|-------|-------|
| Conflicting Flow All | 633   | 0 | - | 0 | 1084  | 549   |
| Stage 1              | -     | - | - | - | 549   | -     |
| Stage 2              | -     | - | - | - | 535   | -     |
| Critical Hdwy        | 4.12  | - | - | - | 6.42  | 6.22  |
| Critical Hdwy Stg 1  | -     | - | - | - | 5.42  | -     |
| Critical Hdwy Stg 2  | -     | - | - | - | 5.42  | -     |
| Follow-up Hdwy       | 2.218 | - | - | - | 3.518 | 3.318 |
| Pot Cap-1 Maneuver   | 950   | - | - | - | 240   | 535   |
| Stage 1              | -     | - | - | - | 579   | -     |
| Stage 2              | -     | - | - | - | 587   | -     |
| Platoon blocked, %   |       | - | - | - |       |       |
| Mov Cap-1 Maneuver   | 950   | - | - | - | 227   | 535   |
| Mov Cap-2 Maneuver   | -     | - | - | - | 227   | -     |
| Stage 1              | -     | - | - | - | 579   | -     |
| Stage 2              | -     | - | - | - | 554   | -     |

Approach EB WB SB

|                      |     |   |      |
|----------------------|-----|---|------|
| HCM Control Delay, s | 0.7 | 0 | 30.6 |
| HCM LOS              |     |   | D    |

Minor Lane/Major Mvmt EBL EBT WBT WBR SBLn1 SBLn2

|                       |       |   |   |   |       |       |
|-----------------------|-------|---|---|---|-------|-------|
| Capacity (veh/h)      | 950   | - | - | - | 227   | 535   |
| HCM Lane V/C Ratio    | 0.042 | - | - | - | 0.599 | 0.167 |
| HCM Control Delay (s) | 9     | 0 | - | - | 42    | 13.1  |
| HCM Lane LOS          | A     | A | - | - | E     | B     |
| HCM 95th %tile Q(veh) | 0.1   | - | - | - | 3.4   | 0.6   |

Maraga St. Mary Roundabout  
2: Bollinger Canyon Rd & St. Mary's Rd

Cumulative  
AM Peak Hour

Intersection

Int Delay, s/veh 3.8

| Movement                 | EBT  | EBR  | WBL  | WBT  | NBL  | NBR  |
|--------------------------|------|------|------|------|------|------|
| Lane Configurations      | ↑    | ↗    |      | ↖    | ↖    | ↗    |
| Traffic Vol, veh/h       | 500  | 43   | 16   | 481  | 101  | 60   |
| Future Vol, veh/h        | 500  | 43   | 16   | 481  | 101  | 60   |
| Conflicting Peds, #/hr   | 0    | 0    | 0    | 0    | 0    | 0    |
| Sign Control             | Free | Free | Free | Free | Stop | Stop |
| RT Channelized           | -    | Free | -    | None | -    | None |
| Storage Length           | -    | 100  | -    | -    | 0    | 20   |
| Veh in Median Storage, # | 0    | -    | -    | 0    | 0    | -    |
| Grade, %                 | 0    | -    | -    | 0    | 0    | -    |
| Peak Hour Factor         | 92   | 92   | 92   | 92   | 92   | 92   |
| Heavy Vehicles, %        | 2    | 2    | 2    | 2    | 2    | 2    |
| Mvmt Flow                | 543  | 47   | 17   | 523  | 110  | 65   |

Major/Minor

|                      | Major1 | Major2 | Minor1 |   |       |       |
|----------------------|--------|--------|--------|---|-------|-------|
| Conflicting Flow All | 0      | -      | 543    | 0 | 1101  | 543   |
| Stage 1              | -      | -      | -      | - | 543   | -     |
| Stage 2              | -      | -      | -      | - | 558   | -     |
| Critical Hdwy        | -      | -      | 4.12   | - | 6.42  | 6.22  |
| Critical Hdwy Stg 1  | -      | -      | -      | - | 5.42  | -     |
| Critical Hdwy Stg 2  | -      | -      | -      | - | 5.42  | -     |
| Follow-up Hdwy       | -      | -      | 2.218  | - | 3.518 | 3.318 |
| Pot Cap-1 Maneuver   | -      | 0      | 1026   | - | 235   | 540   |
| Stage 1              | -      | 0      | -      | - | 582   | -     |
| Stage 2              | -      | 0      | -      | - | 573   | -     |
| Platoon blocked, %   | -      | -      | -      | - | -     | -     |
| Mov Cap-1 Maneuver   | -      | -      | 1026   | - | 230   | 540   |
| Mov Cap-2 Maneuver   | -      | -      | -      | - | 230   | -     |
| Stage 1              | -      | -      | -      | - | 582   | -     |
| Stage 2              | -      | -      | -      | - | 560   | -     |

Approach

|                      | EB | WB  | NB   |
|----------------------|----|-----|------|
| HCM Control Delay, s | 0  | 0.3 | 26.2 |
| HCM LOS              |    |     | D    |

Minor Lane/Major Mvmt

|                       | NBLn1 | NBLn2 | EBT | WBL   | WBT |
|-----------------------|-------|-------|-----|-------|-----|
| Capacity (veh/h)      | 230   | 540   | -   | 1026  | -   |
| HCM Lane V/C Ratio    | 0.477 | 0.121 | -   | 0.017 | -   |
| HCM Control Delay (s) | 34.2  | 12.6  | -   | 8.6   | 0   |
| HCM Lane LOS          | D     | B     | -   | A     | A   |
| HCM 95th %tile Q(veh) | 2.4   | 0.4   | -   | 0.1   | -   |

Maraga St. Mary Roundabout  
1: St. Mary's Rd & Rheem Blvd

Cumulative  
PM Peak Hour

| Intersection             |      |      |      |      |      |      |
|--------------------------|------|------|------|------|------|------|
| Int Delay, s/veh         | 9.4  |      |      |      |      |      |
| Movement                 | EBL  | EBT  | WBT  | WBR  | SBL  | SBR  |
| Lane Configurations      |      | ↕    | ↕    |      | ↕    | ↕    |
| Traffic Vol, veh/h       | 74   | 540  | 360  | 116  | 136  | 62   |
| Future Vol, veh/h        | 74   | 540  | 360  | 116  | 136  | 62   |
| Conflicting Peds, #/hr   | 0    | 0    | 0    | 0    | 0    | 0    |
| Sign Control             | Free | Free | Free | Free | Stop | Stop |
| RT Channelized           | -    | None | -    | None | -    | None |
| Storage Length           | -    | -    | -    | -    | 50   | 0    |
| Veh in Median Storage, # | -    | 0    | 0    | -    | 0    | -    |
| Grade, %                 | -    | 0    | 0    | -    | 0    | -    |
| Peak Hour Factor         | 92   | 92   | 92   | 92   | 92   | 92   |
| Heavy Vehicles, %        | 2    | 2    | 2    | 2    | 2    | 2    |
| Mvmt Flow                | 80   | 587  | 391  | 126  | 148  | 67   |

| Major/Minor          | Major1 | Major2 | Minor2 |   |             |
|----------------------|--------|--------|--------|---|-------------|
| Conflicting Flow All | 517    | 0      | -      | 0 | 1202 454    |
| Stage 1              | -      | -      | -      | - | 454 -       |
| Stage 2              | -      | -      | -      | - | 748 -       |
| Critical Hdwy        | 4.12   | -      | -      | - | 6.42 6.22   |
| Critical Hdwy Stg 1  | -      | -      | -      | - | 5.42 -      |
| Critical Hdwy Stg 2  | -      | -      | -      | - | 5.42 -      |
| Follow-up Hdwy       | 2.218  | -      | -      | - | 3.518 3.318 |
| Pot Cap-1 Maneuver   | 1049   | -      | -      | - | 204 606     |
| Stage 1              | -      | -      | -      | - | 640 -       |
| Stage 2              | -      | -      | -      | - | 468 -       |
| Platoon blocked, %   |        | -      | -      | - |             |
| Mov Cap-1 Maneuver   | 1049   | -      | -      | - | 181 606     |
| Mov Cap-2 Maneuver   | -      | -      | -      | - | 181 -       |
| Stage 1              | -      | -      | -      | - | 640 -       |
| Stage 2              | -      | -      | -      | - | 415 -       |

| Approach             | EB  | WB | SB   |
|----------------------|-----|----|------|
| HCM Control Delay, s | 1.1 | 0  | 57.7 |
| HCM LOS              |     |    | F    |

| Minor Lane/Major Mvmt | EBL   | EBT | WBT | WBR | SBLn1 | SBLn2 |
|-----------------------|-------|-----|-----|-----|-------|-------|
| Capacity (veh/h)      | 1049  | -   | -   | -   | 181   | 606   |
| HCM Lane V/C Ratio    | 0.077 | -   | -   | -   | 0.817 | 0.111 |
| HCM Control Delay (s) | 8.7   | 0   | -   | -   | 78.6  | 11.7  |
| HCM Lane LOS          | A     | A   | -   | -   | F     | B     |
| HCM 95th %tile Q(veh) | 0.2   | -   | -   | -   | 5.7   | 0.4   |



Maraga St. Mary Roundabout  
2: Bollinger Canyon Rd & St. Mary's Rd

Cumulative  
PM Peak Hour

Intersection

Int Delay, s/veh 2.4

| Movement                 | EBT  | EBR  | WBL  | WBT  | NBL  | NBR  |
|--------------------------|------|------|------|------|------|------|
| Lane Configurations      | ↑    | ↗    |      | ↖    | ↖    | ↗    |
| Traffic Vol, veh/h       | 582  | 98   | 56   | 427  | 55   | 32   |
| Future Vol, veh/h        | 582  | 98   | 56   | 427  | 55   | 32   |
| Conflicting Peds, #/hr   | 0    | 0    | 0    | 0    | 0    | 0    |
| Sign Control             | Free | Free | Free | Free | Stop | Stop |
| RT Channelized           | -    | Free | -    | None | -    | None |
| Storage Length           | -    | 100  | -    | -    | 0    | 20   |
| Veh in Median Storage, # | 0    | -    | -    | 0    | 0    | -    |
| Grade, %                 | 0    | -    | -    | 0    | 0    | -    |
| Peak Hour Factor         | 92   | 92   | 92   | 92   | 92   | 92   |
| Heavy Vehicles, %        | 2    | 2    | 2    | 2    | 2    | 2    |
| Mvmt Flow                | 633  | 107  | 61   | 464  | 60   | 35   |

Major/Minor

|                      | Major1 | Major2  | Minor1  |       |  |
|----------------------|--------|---------|---------|-------|--|
| Conflicting Flow All | 0      | - 633   | 0 1219  | 633   |  |
| Stage 1              | -      | -       | - 633   | -     |  |
| Stage 2              | -      | -       | - 586   | -     |  |
| Critical Hdwy        | -      | - 4.12  | - 6.42  | 6.22  |  |
| Critical Hdwy Stg 1  | -      | -       | - 5.42  | -     |  |
| Critical Hdwy Stg 2  | -      | -       | - 5.42  | -     |  |
| Follow-up Hdwy       | -      | - 2.218 | - 3.518 | 3.318 |  |
| Pot Cap-1 Maneuver   | -      | 0 950   | - 199   | 480   |  |
| Stage 1              | -      | 0       | - 529   | -     |  |
| Stage 2              | -      | 0       | - 556   | -     |  |
| Platoon blocked, %   | -      |         | -       |       |  |
| Mov Cap-1 Maneuver   | -      | - 950   | - 182   | 480   |  |
| Mov Cap-2 Maneuver   | -      | -       | - 182   | -     |  |
| Stage 1              | -      | -       | - 529   | -     |  |
| Stage 2              | -      | -       | - 508   | -     |  |

Approach

|                      | EB | WB | NB   |
|----------------------|----|----|------|
| HCM Control Delay, s | 0  | 1  | 26.4 |
| HCM LOS              |    |    | D    |

Minor Lane/Major Mvmt

|                       | NBLn1 | NBLn2 | EBT     | WBL | WBT |
|-----------------------|-------|-------|---------|-----|-----|
| Capacity (veh/h)      | 182   | 480   | - 950   | -   | -   |
| HCM Lane V/C Ratio    | 0.328 | 0.072 | - 0.064 | -   | -   |
| HCM Control Delay (s) | 34.2  | 13.1  | - 9     | 0   |     |
| HCM Lane LOS          | D     | B     | - A     | A   |     |
| HCM 95th %tile Q(veh) | 1.3   | 0.2   | - 0.2   | -   |     |

# LANE SUMMARY

 Site: 101 [INT-01\_Existing\_AM\_Rheem at St. Marys]

Rheem at St. Marys  
Roundabout

| Lane Use and Performance |              |      |            |           |            |               |                  |                       |            |             |             |           |              |
|--------------------------|--------------|------|------------|-----------|------------|---------------|------------------|-----------------------|------------|-------------|-------------|-----------|--------------|
|                          | Demand Flows |      |            | Deg. Satn | Lane Util. | Average Delay | Level of Service | 95% Back of Queue Veh | Queue Dist | Lane Config | Lane Length | Cap. Adj. | Prob. Block. |
|                          | Total veh/h  | HV % | Cap. veh/h | v/c       | %          | sec           |                  | ft                    | ft         |             | ft          | %         | %            |
| South: NB St Marys Rd    |              |      |            |           |            |               |                  |                       |            |             |             |           |              |
| Lane 1 <sup>d</sup>      | 374          | 2.0  | 1251       | 0.299     | 100        | 5.6           | LOS A            | 1.7                   | 42.4       | Full        | 1600        | 0.0       | 0.0          |
| Approach                 | 374          | 2.0  |            | 0.299     |            | 5.6           | LOS A            | 1.7                   | 42.4       |             |             |           |              |
| North: SB St Marys Rd    |              |      |            |           |            |               |                  |                       |            |             |             |           |              |
| Lane 1 <sup>d</sup>      | 511          | 2.0  | 1363       | 0.375     | 100        | 6.1           | LOS A            | 2.4                   | 61.8       | Full        | 500         | 0.0       | 0.0          |
| Approach                 | 511          | 2.0  |            | 0.375     |            | 6.1           | LOS A            | 2.4                   | 61.8       |             |             |           |              |
| West:                    |              |      |            |           |            |               |                  |                       |            |             |             |           |              |
| Lane 1 <sup>d</sup>      | 196          | 2.0  | 1224       | 0.160     | 100        | 4.3           | LOS A            | 0.8                   | 19.4       | Full        | 750         | 0.0       | 0.0          |
| Approach                 | 196          | 2.0  |            | 0.160     |            | 4.3           | LOS A            | 0.8                   | 19.4       |             |             |           |              |
| Intersection             | 1080         | 2.0  |            | 0.375     |            | 5.6           | LOS A            | 2.4                   | 61.8       |             |             |           |              |

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Lane LOS values are based on average delay and v/c ratio (degree of saturation) per lane.

LOS F will result if v/c > 1 irrespective of lane delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all lanes (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 2010.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

<sup>d</sup> Dominant lane on roundabout approach

**SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com**

Organisation: KIMLEY-HORN & ASSOCIATES INC | Processed: Saturday, November 11, 2017 3:13:21 PM

Project: K:\SAC\_TPTO\Pleasanton Projects\Moraga St Mary Roundabout - Pleasanton\03 Analysis Files\Sidra\RAB at Rheem\_Cumulative Plus

Project Vol.sip7

# LANE SUMMARY

 Site: 101 [INT-01\_Existing\_PM\_Rheem at St. Marys]

Rheem at St. Marys  
Roundabout

| Lane Use and Performance |              |     |       |       |       |         |          |                   |      |        |        |      |        |
|--------------------------|--------------|-----|-------|-------|-------|---------|----------|-------------------|------|--------|--------|------|--------|
|                          | Demand Flows |     |       | Deg.  | Lane  | Average | Level of | 95% Back of Queue |      | Lane   | Lane   | Cap. | Prob.  |
|                          | Total        | HV  | Cap.  | Satn  | Util. | Delay   | Service  | Veh               | Dist | Config | Length | Adj. | Block. |
|                          | veh/h        | %   | veh/h | v/c   | %     | sec     |          |                   | ft   |        | ft     | %    | %      |
| South: NB St Marys Rd    |              |     |       |       |       |         |          |                   |      |        |        |      |        |
| Lane 1 <sup>d</sup>      | 530          | 2.0 | 1258  | 0.422 | 100   | 7.0     | LOS A    | 2.8               | 70.1 | Full   | 1600   | 0.0  | 0.0    |
| Approach                 | 530          | 2.0 |       | 0.422 |       | 7.0     | LOS A    | 2.8               | 70.1 |        |        |      |        |
| North: SB St Marys Rd    |              |     |       |       |       |         |          |                   |      |        |        |      |        |
| Lane 1 <sup>d</sup>      | 351          | 2.0 | 1315  | 0.267 | 100   | 5.1     | LOS A    | 1.5               | 37.3 | Full   | 500    | 0.0  | 0.0    |
| Approach                 | 351          | 2.0 |       | 0.267 |       | 5.1     | LOS A    | 1.5               | 37.3 |        |        |      |        |
| West:                    |              |     |       |       |       |         |          |                   |      |        |        |      |        |
| Lane 1 <sup>d</sup>      | 173          | 2.0 | 1090  | 0.159 | 100   | 4.7     | LOS A    | 0.7               | 18.5 | Full   | 750    | 0.0  | 0.0    |
| Approach                 | 173          | 2.0 |       | 0.159 |       | 4.7     | LOS A    | 0.7               | 18.5 |        |        |      |        |
| Intersection             | 1054         | 2.0 |       | 0.422 |       | 6.0     | LOS A    | 2.8               | 70.1 |        |        |      |        |

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Lane LOS values are based on average delay and v/c ratio (degree of saturation) per lane.

LOS F will result if v/c > 1 irrespective of lane delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all lanes (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 2010.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

<sup>d</sup> Dominant lane on roundabout approach

**SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com**

Organisation: KIMLEY-HORN & ASSOCIATES INC | Processed: Saturday, November 11, 2017 3:13:22 PM

Project: K:\SAC\_TPTO\Pleasanton Projects\Moraga St Mary Roundabout - Pleasanton\03 Analysis Files\Sidra\RAB at Rheem\_Cumulative Plus Project Vol.sip7

# LANE SUMMARY

 Site: 101 [INT-01\_CumulativePlus\_AM\_Rheem at St. Marys]

Rheem at St. Marys  
Roundabout

| Lane Use and Performance |              |     |       |       |       |         |          |                   |      |        |        |      |        |
|--------------------------|--------------|-----|-------|-------|-------|---------|----------|-------------------|------|--------|--------|------|--------|
|                          | Demand Flows |     |       | Deg.  | Lane  | Average | Level of | 95% Back of Queue |      | Lane   | Lane   | Cap. | Prob.  |
|                          | Total        | HV  | Cap.  | Satn  | Util. | Delay   | Service  | Veh               | Dist | Config | Length | Adj. | Block. |
|                          | veh/h        | %   | veh/h | v/c   | %     | sec     |          |                   | ft   |        | ft     | %    | %      |
| South: NB St Marys Rd    |              |     |       |       |       |         |          |                   |      |        |        |      |        |
| Lane 1 <sup>d</sup>      | 495          | 2.0 | 1229  | 0.402 | 100   | 6.9     | LOS A    | 2.5               | 64.2 | Full   | 1600   | 0.0  | 0.0    |
| Approach                 | 495          | 2.0 |       | 0.402 |       | 6.9     | LOS A    | 2.5               | 64.2 |        |        |      |        |
| North: SB St Marys Rd    |              |     |       |       |       |         |          |                   |      |        |        |      |        |
| Lane 1 <sup>d</sup>      | 633          | 2.0 | 1355  | 0.467 | 100   | 7.3     | LOS A    | 3.5               | 88.5 | Full   | 500    | 0.0  | 0.0    |
| Approach                 | 633          | 2.0 |       | 0.467 |       | 7.3     | LOS A    | 3.5               | 88.5 |        |        |      |        |
| West:                    |              |     |       |       |       |         |          |                   |      |        |        |      |        |
| Lane 1 <sup>d</sup>      | 225          | 2.0 | 877   | 0.256 | 100   | 6.8     | LOS A    | 1.2               | 30.1 | Full   | 750    | 0.0  | 0.0    |
| Approach                 | 225          | 2.0 |       | 0.256 |       | 6.8     | LOS A    | 1.2               | 30.1 |        |        |      |        |
| Intersection             | 1352         | 2.0 |       | 0.467 |       | 7.1     | LOS A    | 3.5               | 88.5 |        |        |      |        |

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Lane LOS values are based on average delay and v/c ratio (degree of saturation) per lane.

LOS F will result if v/c > 1 irrespective of lane delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all lanes (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 2010.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

<sup>d</sup> Dominant lane on roundabout approach

**SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com**

Organisation: KIMLEY-HORN & ASSOCIATES INC | Processed: Saturday, November 11, 2017 3:13:22 PM

Project: K:\SAC\_TPTO\Pleasanton Projects\Moraga St Mary Roundabout - Pleasanton\03 Analysis Files\Sidra\RAB at Rheem\_Cumulative Plus

Project Vol.sip7

# LANE SUMMARY

 Site: 101 [INT-01\_CumulativePlus\_PM\_Rheem at St. Marys]

Rheem at St. Marys  
Roundabout

| Lane Use and Performance |              |      |            |           |            |               |                  |                       |               |             |                |             |                |
|--------------------------|--------------|------|------------|-----------|------------|---------------|------------------|-----------------------|---------------|-------------|----------------|-------------|----------------|
|                          | Demand Flows |      |            | Deg. Satn | Lane Util. | Average Delay | Level of Service | 95% Back of Queue Veh | Queue Dist ft | Lane Config | Lane Length ft | Cap. Adj. % | Prob. Block. % |
|                          | Total veh/h  | HV % | Cap. veh/h | v/c       | %          | sec           |                  |                       |               |             |                |             |                |
| South: NB St Marys Rd    |              |      |            |           |            |               |                  |                       |               |             |                |             |                |
| Lane 1 <sup>d</sup>      | 667          | 2.0  | 1214       | 0.550     | 100        | 9.3           | LOS A            | 4.2                   | 107.0         | Full        | 1600           | 0.0         | 0.0            |
| Approach                 | 667          | 2.0  |            | 0.550     |            | 9.3           | LOS A            | 4.2                   | 107.0         |             |                |             |                |
| North: SB St Marys Rd    |              |      |            |           |            |               |                  |                       |               |             |                |             |                |
| Lane 1 <sup>d</sup>      | 517          | 2.0  | 1301       | 0.398     | 100        | 6.6           | LOS A            | 2.6                   | 65.6          | Full        | 500            | 0.0         | 0.0            |
| Approach                 | 517          | 2.0  |            | 0.398     |            | 6.6           | LOS A            | 2.6                   | 65.6          |             |                |             |                |
| West:                    |              |      |            |           |            |               |                  |                       |               |             |                |             |                |
| Lane 1 <sup>d</sup>      | 215          | 2.0  | 947        | 0.227     | 100        | 6.1           | LOS A            | 1.1                   | 26.8          | Full        | 750            | 0.0         | 0.0            |
| Approach                 | 215          | 2.0  |            | 0.227     |            | 6.1           | LOS A            | 1.1                   | 26.8          |             |                |             |                |
| Intersection             | 1400         | 2.0  |            | 0.550     |            | 7.8           | LOS A            | 4.2                   | 107.0         |             |                |             |                |

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Lane LOS values are based on average delay and v/c ratio (degree of saturation) per lane.

LOS F will result if v/c > 1 irrespective of lane delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all lanes (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 2010.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

<sup>d</sup> Dominant lane on roundabout approach

**SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com**

Organisation: KIMLEY-HORN & ASSOCIATES INC | Processed: Saturday, November 11, 2017 3:13:23 PM

Project: K:\SAC\_TPTO\Pleasanton Projects\Moraga St Mary Roundabout - Pleasanton\03 Analysis Files\Sidra\RAB at Rheem\_Cumulative Plus

Project Vol.sip7

# LANE SUMMARY

 Site: 101 [INT-02\_Existing\_AM\_Bollinger Canyon at St. Marys]

Bollinger Canyon at St. Marys  
Roundabout

| Lane Use and Performance        |              |      |            |               |              |                   |                  |                   |         |             |                |             |                |
|---------------------------------|--------------|------|------------|---------------|--------------|-------------------|------------------|-------------------|---------|-------------|----------------|-------------|----------------|
|                                 | Demand Flows |      |            | Deg. Satn v/c | Lane Util. % | Average Delay sec | Level of Service | 95% Back of Queue |         | Lane Config | Lane Length ft | Cap. Adj. % | Prob. Block. % |
|                                 | Total veh/h  | HV % | Cap. veh/h |               |              |                   |                  | Veh               | Dist ft |             |                |             |                |
| South: NB Bollinger Canyon Road |              |      |            |               |              |                   |                  |                   |         |             |                |             |                |
| Lane 1 <sup>d</sup>             | 87           | 2.0  | 912        | 0.095         | 100          | 4.8               | LOS A            | 0.4               | 10.1    | Full        | 1600           | 0.0         | 0.0            |
| Approach                        | 87           | 2.0  |            | 0.095         |              | 4.8               | LOS A            | 0.4               | 10.1    |             |                |             |                |
| East: SB/WB St Marys Road       |              |      |            |               |              |                   |                  |                   |         |             |                |             |                |
| Lane 1 <sup>d</sup>             | 455          | 2.0  | 1330       | 0.343         | 100          | 5.8               | LOS A            | 2.1               | 53.1    | Full        | 1600           | 0.0         | 0.0            |
| Approach                        | 455          | 2.0  |            | 0.343         |              | 5.8               | LOS A            | 2.1               | 53.1    |             |                |             |                |
| West: NB/EB St Marys Road       |              |      |            |               |              |                   |                  |                   |         |             |                |             |                |
| Lane 1 <sup>d</sup>             | 458          | 2.0  | 1404       | 0.326         | 100          | 5.4               | LOS A            | 2.0               | 51.1    | Full        | 450            | 0.0         | 0.0            |
| Approach                        | 458          | 2.0  |            | 0.326         |              | 5.4               | LOS A            | 2.0               | 51.1    |             |                |             |                |
| Intersection                    | 1000         | 2.0  |            | 0.343         |              | 5.6               | LOS A            | 2.1               | 53.1    |             |                |             |                |

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Lane LOS values are based on average delay and v/c ratio (degree of saturation) per lane.

LOS F will result if v/c > 1 irrespective of lane delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all lanes (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 2010.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

<sup>d</sup> Dominant lane on roundabout approach

**SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com**

Organisation: KIMLEY-HORN & ASSOCIATES INC | Processed: Saturday, November 11, 2017 3:07:53 PM

Project: K:\SAC\_TPTO\Pleasanton Projects\Moraga St Mary Roundabout - Pleasanton\03 Analysis Files\Sidra\RAB at Bollinger\_Cumulative Plus Project Vol.sip7



# LANE SUMMARY

 Site: 101 [INT-02\_Existing\_PM\_Bollinger Canyon at St. Marys]

Bollinger Canyon at St. Marys  
Roundabout

| Lane Use and Performance        |              |      |            |           |            |               |                  |                       |            |             |             |           |              |
|---------------------------------|--------------|------|------------|-----------|------------|---------------|------------------|-----------------------|------------|-------------|-------------|-----------|--------------|
|                                 | Demand Flows |      |            | Deg. Satn | Lane Util. | Average Delay | Level of Service | 95% Back of Queue Veh | Queue Dist | Lane Config | Lane Length | Cap. Adj. | Prob. Block. |
|                                 | Total veh/h  | HV % | Cap. veh/h | v/c       | %          | sec           |                  | ft                    | ft         |             | ft          | %         | %            |
| South: NB Bollinger Canyon Road |              |      |            |           |            |               |                  |                       |            |             |             |           |              |
| Lane 1 <sup>d</sup>             | 38           | 2.0  | 823        | 0.046     | 100        | 4.8           | LOS A            | 0.2                   | 4.7        | Full        | 1600        | 0.0       | 0.0          |
| Approach                        | 38           | 2.0  |            | 0.046     |            | 4.8           | LOS A            | 0.2                   | 4.7        |             |             |           |              |
| East: SB/WB St Marys Road       |              |      |            |           |            |               |                  |                       |            |             |             |           |              |
| Lane 1 <sup>d</sup>             | 350          | 2.0  | 1373       | 0.255     | 100        | 4.8           | LOS A            | 1.4                   | 35.9       | Full        | 1600        | 0.0       | 0.0          |
| Approach                        | 350          | 2.0  |            | 0.255     |            | 4.8           | LOS A            | 1.4                   | 35.9       |             |             |           |              |
| West: NB/EB St Marys Road       |              |      |            |           |            |               |                  |                       |            |             |             |           |              |
| Lane 1 <sup>d</sup>             | 578          | 2.0  | 1385       | 0.417     | 100        | 6.5           | LOS A            | 2.9                   | 74.4       | Full        | 450         | 0.0       | 0.0          |
| Approach                        | 578          | 2.0  |            | 0.417     |            | 6.5           | LOS A            | 2.9                   | 74.4       |             |             |           |              |
| Intersection                    | 966          | 2.0  |            | 0.417     |            | 5.8           | LOS A            | 2.9                   | 74.4       |             |             |           |              |

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Lane LOS values are based on average delay and v/c ratio (degree of saturation) per lane.

LOS F will result if v/c > 1 irrespective of lane delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all lanes (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 2010.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

<sup>d</sup> Dominant lane on roundabout approach

**SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com**

Organisation: KIMLEY-HORN & ASSOCIATES INC | Processed: Saturday, November 11, 2017 3:07:53 PM

Project: K:\SAC\_TPTO\Pleasanton Projects\Moraga St Mary Roundabout - Pleasanton\03 Analysis Files\Sidra\RAB at Bollinger\_Cumulative Plus Project Vol.sip7

# LANE SUMMARY

 Site: 101 [INT-02\_CumulativePlus\_AM\_Bollinger Canyon at St. Marys]

Bollinger Canyon at St. Marys  
Roundabout

| Lane Use and Performance        |              |     |       |           |            |               |                  |                   |      |             |             |           |              |
|---------------------------------|--------------|-----|-------|-----------|------------|---------------|------------------|-------------------|------|-------------|-------------|-----------|--------------|
|                                 | Demand Flows |     |       | Deg. Satn | Lane Util. | Average Delay | Level of Service | 95% Back of Queue |      | Lane Config | Lane Length | Cap. Adj. | Prob. Block. |
|                                 | Total        | HV  | Cap.  | v/c       | %          | sec           |                  | Veh               | Dist |             | ft          | %         | %            |
|                                 | veh/h        | %   | veh/h |           |            |               |                  |                   | ft   |             |             |           |              |
| South: NB Bollinger Canyon Road |              |     |       |           |            |               |                  |                   |      |             |             |           |              |
| Lane 1 <sup>d</sup>             | 175          | 2.0 | 811   | 0.216     | 100        | 6.7           | LOS A            | 0.9               | 24.0 | Full        | 1600        | 0.0       | 0.0          |
| Approach                        | 175          | 2.0 |       | 0.216     |            | 6.7           | LOS A            | 0.9               | 24.0 |             |             |           |              |
| East: SB/WB St Marys Road       |              |     |       |           |            |               |                  |                   |      |             |             |           |              |
| Lane 1 <sup>d</sup>             | 540          | 2.0 | 1262  | 0.428     | 100        | 7.1           | LOS A            | 2.8               | 72.0 | Full        | 1600        | 0.0       | 0.0          |
| Approach                        | 540          | 2.0 |       | 0.428     |            | 7.1           | LOS A            | 2.8               | 72.0 |             |             |           |              |
| West: NB/EB St Marys Road       |              |     |       |           |            |               |                  |                   |      |             |             |           |              |
| Lane 1 <sup>d</sup>             | 590          | 2.0 | 1387  | 0.426     | 100        | 6.6           | LOS A            | 3.0               | 76.9 | Full        | 450         | 0.0       | 0.0          |
| Approach                        | 590          | 2.0 |       | 0.426     |            | 6.6           | LOS A            | 3.0               | 76.9 |             |             |           |              |
| Intersection                    | 1305         | 2.0 |       | 0.428     |            | 6.8           | LOS A            | 3.0               | 76.9 |             |             |           |              |

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Lane LOS values are based on average delay and v/c ratio (degree of saturation) per lane.

LOS F will result if v/c > 1 irrespective of lane delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all lanes (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 2010.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

<sup>d</sup> Dominant lane on roundabout approach

**SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com**

Organisation: KIMLEY-HORN & ASSOCIATES INC | Processed: Saturday, November 11, 2017 3:07:54 PM

Project: K:\SAC\_TPTO\Pleasanton Projects\Moraga St Mary Roundabout - Pleasanton\03 Analysis Files\Sidra\RAB at Bollinger\_Cumulative Plus Project Vol.sip7

# LANE SUMMARY

 Site: 101 [INT-02\_CumulativePlus\_PM\_Bollinger Canyon at St. Marys]

Bollinger Canyon at St. Marys  
Roundabout

| Lane Use and Performance        |              |      |            |               |              |                   |                  |                       |               |             |                |             |                |
|---------------------------------|--------------|------|------------|---------------|--------------|-------------------|------------------|-----------------------|---------------|-------------|----------------|-------------|----------------|
|                                 | Demand Flows |      |            | Deg. Satn v/c | Lane Util. % | Average Delay sec | Level of Service | 95% Back of Queue Veh | Queue Dist ft | Lane Config | Lane Length ft | Cap. Adj. % | Prob. Block. % |
|                                 | Total veh/h  | HV % | Cap. veh/h |               |              |                   |                  |                       |               |             |                |             |                |
| South: NB Bollinger Canyon Road |              |      |            |               |              |                   |                  |                       |               |             |                |             |                |
| Lane 1 <sup>d</sup>             | 95           | 2.0  | 741        | 0.128         | 100          | 6.2               | LOS A            | 0.5                   | 13.2          | Full        | 1600           | 0.0         | 0.0            |
| Approach                        | 95           | 2.0  |            | 0.128         |              | 6.2               | LOS A            | 0.5                   | 13.2          |             |                |             |                |
| East: SB/WB St Marys Road       |              |      |            |               |              |                   |                  |                       |               |             |                |             |                |
| Lane 1 <sup>d</sup>             | 525          | 2.0  | 1328       | 0.395         | 100          | 6.4               | LOS A            | 2.6                   | 65.9          | Full        | 1600           | 0.0         | 0.0            |
| Approach                        | 525          | 2.0  |            | 0.395         |              | 6.4               | LOS A            | 2.6                   | 65.9          |             |                |             |                |
| West: NB/EB St Marys Road       |              |      |            |               |              |                   |                  |                       |               |             |                |             |                |
| Lane 1 <sup>d</sup>             | 739          | 2.0  | 1327       | 0.557         | 100          | 8.9               | LOS A            | 4.8                   | 121.2         | Full        | 450            | 0.0         | 0.0            |
| Approach                        | 739          | 2.0  |            | 0.557         |              | 8.9               | LOS A            | 4.8                   | 121.2         |             |                |             |                |
| Intersection                    | 1359         | 2.0  |            | 0.557         |              | 7.7               | LOS A            | 4.8                   | 121.2         |             |                |             |                |

Site Level of Service (LOS) Method: Delay & v/c (HCM 6). Site LOS Method is specified in the Parameter Settings dialog (Site tab).

Roundabout LOS Method: Same as Sign Control.

Lane LOS values are based on average delay and v/c ratio (degree of saturation) per lane.

LOS F will result if v/c > 1 irrespective of lane delay value (does not apply for approaches and intersection).

Intersection and Approach LOS values are based on average delay for all lanes (v/c not used as specified in HCM 6).

Roundabout Capacity Model: US HCM 2010.

HCM Delay Formula option is used. Control Delay does not include Geometric Delay since Exclude Geometric Delay option applies.

Gap-Acceptance Capacity: Traditional M1.

HV (%) values are calculated for All Movement Classes of All Heavy Vehicle Model Designation.

<sup>d</sup> Dominant lane on roundabout approach

**SIDRA INTERSECTION 7.0 | Copyright © 2000-2017 Akcelik and Associates Pty Ltd | sidrasolutions.com**

Organisation: KIMLEY-HORN & ASSOCIATES INC | Processed: Saturday, November 11, 2017 3:07:54 PM

Project: K:\SAC\_TPTO\Pleasanton Projects\Moraga St Mary Roundabout - Pleasanton\03 Analysis Files\Sidra\RAB at Bollinger\_Cumulative Plus Project Vol.sip7