

Project Specific Water Quality Management Plan

A Template for preparing Project Specific WQMPs for Priority Development Projects located within the Santa Margarita Region of Riverside County. This template does not apply to projects in other watersheds within Riverside County. It does not apply to projects in San Diego or Orange County.



Attention: This submittal package only applies to "Priority Development Projects" and does not apply to "Other Development Projects". Proceed only if the Applicabilty Checklist completed for your project categorizes project activities as a "Priority Development Project."


Project Title: Whitewood Apartments

Development No: Insert text here

Prepared for: Insert Developer Name,
Address, and Phone Number

Design Review/Case No: Insert text here

Prepared by: Alliance Land Planning and
Engineering, 2248 Faraday Avenue,
Carlsbad CA, 92008, (760) 431-9896



- Preliminary
- Final


Original Date Prepared: 4/28/21

Revision Date(s): 11/8/21

Prepared for Compliance with Regional Board Order No. R9-2013-0001 as amended by Order No. R9-2015-0001 and Order No. R9-2015-0100

A Brief Introduction

The Regional Municipal Separate Stormwater Sewer System (MS4) Permit¹ requires that a Project-Specific WQMP be prepared for all development projects within the Santa Margarita Region (SMR) that meet the 'Priority Development Project' categories and thresholds listed in the SMR Water Quality Management Plan (WQMP). This Project-Specific WQMP Template for Development Projects in the Santa Margarita Region has been prepared to help document compliance and prepare a WQMP submittal. Below is a flowchart for the layout of this Template that will provide the steps required to document compliance.



¹ Order No. R9-2013-0001 as amended by Order Nos. R9-2015-0001 and R9-2015-0100, NPDES No. CAS0109266, National Pollutant Discharge Elimination System (NPDES) Permit and Waste Discharge Requirements for Discharges from the MS4s Draining the Watersheds within the San Diego Region, California Regional Water Quality Control Board, May 8, 2013.

OWNER'S CERTIFICATION

This Project-Specific WQMP has been prepared for <Owner's Name> by Alliance for the Whitewood Apartments project.

This WQMP is intended to comply with the requirements of City of Murrieta Stormwater and Runoff Management and Discharge Controls Municipal Code Section 8.36.320, Water Quality Management Plan, which includes the requirement for the preparation and implementation of a Project-Specific WQMP.

The undersigned, while owning the property/project described in the preceding paragraph, shall be responsible for the implementation and funding of this WQMP and will ensure that this WQMP is amended as appropriate to reflect up-to-date conditions on the site. In addition, the property owner accepts responsibility for interim operation and maintenance of Stormwater Best Management Practices until such time as this responsibility is formally transferred to a subsequent owner. This WQMP will be reviewed with the facility operator, facility supervisors, employees, tenants, maintenance and service contractors, or any other party (or parties) having responsibility for implementing portions of this WQMP. At least one copy of this WQMP will be maintained at the project site or project office in perpetuity. The undersigned is authorized to certify and to approve implementation of this WQMP. The undersigned is aware that implementation of this WQMP is enforceable under the City of Murrieta Stormwater and Runoff Management and Discharge Controls (Municipal Code Section 8.36).

"I, the undersigned, certify under penalty of law that the provisions of this WQMP have been reviewed and accepted and that the WQMP will be transferred to future successors in interest."

Owner's Signature

Date

Owner's Printed Name

Owner's Title/Position

PREPARER'S CERTIFICATION

"The selection, sizing and design of stormwater treatment and other stormwater quality and quantity control Best Management Practices in this plan meet the requirements of Regional Water Quality Control Board Order No. R9-2013-0001 as amended by Order Nos. R9-2015-0001 and R9-2015-0100."

Preparer's Signature

4/28/21

Date

Jason F. Vroom

Preparer's Printed Name

Principal

Preparer's Title/Position

Preparer's Licensure:

Table of Contents

Section A: Project and Site Information	7
A.1 Maps and Site Plans.....	8
A.2 Identify Receiving Waters	8
A.3 Drainage System Susceptibility to Hydromodification	9
A.4 Additional Permits/Approvals required for the Project:.....	9
Section B: Optimize Site Utilization (LID Principles).....	11
Section C: Delineate Drainage Management Areas (DMAs).....	16
Section D: Implement LID BMPs	20
D.1 Full Infiltration Applicability.....	20
D.2 Biofiltration Applicability	22
D.3 Feasibility Assessment Summaries.....	24
D.4 LID BMP Sizing.....	26
Section E: Implement Hydrologic Control BMPs and Sediment Supply BMPs.....	28
E.1 Hydrologic Control BMP Selection.....	28
E.2 Hydrologic Control BMP Sizing	29
E.3 Implement Sediment Supply BMPs.....	29
Section F: Alternative Compliance	34
F.1 Identify Pollutants of Concern	34
F.2 Treatment Control BMP Selection	37
F.3 Sizing Criteria	37
F.4 Hydrologic Performance Standard – Alternative Compliance Approach.....	38
Section G: Implement Trash Capture BMPs.....	40
Section H: Source Control BMPs	42
Section I: Coordinate Submittal with Other Site Plans.....	43
Section J: Operation, Maintenance and Funding	44
Section K: Acronyms, Abbreviations and Definitions	45

List of Tables

Table A-1 Identification of Receiving Waters.....	8
Table A-2 Identification of Susceptibility to Hydromodification.....	9
Table A-3 Other Applicable Permits	9
Table C-1 DMA Identification.....	16
Table C-2 Type 'A', Self-Treating Areas.....	17
Table C-3 Type 'B', Self-Retaining Areas.....	18
Table C-4 Type 'C', Areas that Drain to Self-Retaining Areas.....	18
Table C-5 Type 'D', Areas Draining to BMPs	19
Table D-1 Infiltration Feasibility	21
Table D-2 Geotechnical Concerns for Onsite Infiltration.....	22
Table D-3 Evaluation of Biofiltration BMP Feasibility.....	23
Table D-4 Proprietary BMP Approval Requirement Summary	23
Table D-5 LID Prioritization Summary Matrix	24
Table D-6 DCV Calculations for LID BMPs.....	26
Table D-7 LID BMP Sizing	27
Table E-1 Hydrologic Control BMP Sizing	29
Table E-2 Triad Assessment Summary.....	32
Table F-1 Summary of Approved 2010 303(d) listed waterbodies and associated pollutants of concern for the Riverside County SMR Region and downstream waterbodies.....	35
Table F-2 Potential Pollutants by Land Use Type	36
Table F-3 Treatment Control BMP Selection	37
Table F-4 Treatment Control BMP Sizing.....	37
Table F-5 Offsite Hydrologic Control BMP Sizing	38
Table G-1 Sizing Trash Capture BMPs.....	40
Table G-2 Approximate precipitation depth/intensity values for calculation of the Trash Capture Design Storm	40
Table G-3 Trash Capture BMPs	41
Table I-1 Construction Plan Cross-reference	43
Table I-2 Other Applicable Permits	43

List of Appendices

Appendix 1: Maps and Site Plans	52
Appendix 2: Construction Plans	53
Appendix 3: Soils Information.....	55
Appendix 4: Historical Site Conditions	56
Appendix 5: LID Infeasibility.....	57

Appendix 6: BMP Design Details 58
Appendix 7: Hydromodification 59
Appendix 8: Source Control 60
Appendix 9: O&M..... 61
Appendix 10: Educational Materials..... 62

Section A: Project and Site Information

Use the table below to compile and summarize basic site information that will be important for completing subsequent steps. Subsections A.1 through A.4 provide additional detail on documentation of additional project and site information.

PROJECT INFORMATION	
Type of PDP:	New Development
Type of Project:	Residential
Planning Area:	Insert Planning Area if known
Community Name:	Insert Community Name if known
Development Name:	Insert Development Name if known
PROJECT LOCATION	
Latitude & Longitude (DMS):	33°36'13.20"N, 117° 9'42.13"W
Project Watershed and Sub-Watershed:	Santa Margarita River, Insert HSA here (see Section A.2)
24-Hour 85 th Percentile Storm Depth (inches):	0.60
Is project subject to Hydromodification requirements?	<input checked="" type="checkbox"/> Y <input type="checkbox"/> N (Select based on Section A.3)
APN(s):	392-320-014
Map Book and Page No.:	Insert text here
PROJECT CHARACTERISTICS	
Proposed or Potential Land Use(s)	Insert text here
Proposed or Potential SIC Code(s)	Insert text here
Existing Impervious Area of Project Footprint (SF)	29,739
Total area of <u>proposed</u> Impervious Surfaces within the Project Limits (SF)/or Replacement	594,779
Total Project Area (ac)	13.65
Does the project consist of offsite road improvements?	<input checked="" type="checkbox"/> Y <input type="checkbox"/> N
Does the project propose to construct unpaved roads?	<input type="checkbox"/> Y <input checked="" type="checkbox"/> N
Is the project part of a larger common plan of development (phased project)?	<input type="checkbox"/> Y <input checked="" type="checkbox"/> N
Is the project exempt from Hydromodification Performance Standards?	<input checked="" type="checkbox"/> Y <input type="checkbox"/> N
Does the project propose the use of Alternative Compliance to satisfy BMP requirements? (note, alternative compliance is not allowed for coarse sediment performance standards)	<input type="checkbox"/> Y <input checked="" type="checkbox"/> N
Has preparation of Project-Specific WQMP included coordination with other site plans?	<input type="checkbox"/> Y <input checked="" type="checkbox"/> N
EXISTING SITE CHARACTERISTICS	
Is the project located within any Multi-Species Habitat Conservation Plan area (MSHCP Criteria Cell?)	<input type="checkbox"/> Y <input type="checkbox"/> N If "Y" insert Cell Number
Are there any natural hydrologic features on the project site?	<input checked="" type="checkbox"/> Y <input type="checkbox"/> N
Is a Geotechnical Report attached?	<input checked="" type="checkbox"/> Y <input type="checkbox"/> N
If no Geotech. Report, list the Natural Resources Conservation Service (NRCS) soils type(s) present on the site (A, B, C and/or D)	Insert text here.

A.1 Maps and Site Plans

When completing your Project-Specific WQMP, include a map of the Project vicinity and existing site. In addition, include all grading, drainage, landscape/plant palette and other pertinent construction plans in Appendix 2. At a minimum, your WQMP Site Plan should include the following:

- Vicinity and location maps
- Parcel Boundary and Project Footprint
- Existing and Proposed Topography
- Drainage Management Areas (DMAs)
- Proposed Structural Best Management Practices (BMPs)
- Drainage Paths
- Drainage infrastructure, inlets, overflows
- Source Control BMPs
- Site Design BMPs
- Buildings, Roof Lines, Downspouts
- Impervious Surfaces
- Pervious Surfaces (i.e. Landscaping)
- Standard Labeling

Use your discretion on whether or not you may need to create multiple sheets or can appropriately accommodate these features on one or two sheets. Keep in mind that the Copermittee plan reviewer must be able to easily analyze your Project utilizing this template and its associated site plans and maps. Complete the checklists in Appendix 1 to verify that all exhibits and components are included.

A.2 Identify Receiving Waters

Using Table A-1 below, list in order of upstream to downstream, the Receiving Waters that the Project site is tributary to. Continue to fill each row with the Receiving Water’s 303(d) listed impairments (if any), designated Beneficial Uses, and proximity, if any, to a RARE Beneficial Use. Include a map of the Receiving Waters in Appendix 1. This map should identify the path of the stormwater discharged from the site all the way to the outlet of the Santa Margarita River to the Pacific Ocean. Use the most recent 303(d) list available from the State Water Resources Control Board Website.

(http://www.waterboards.ca.gov/sandiego/water_issues/programs/basin_plan/)

Table A-1 Identification of Receiving Waters

Receiving Waters	USEPA Approved 303(d) List Impairments	Designated Beneficial Uses	Proximity to RARE Beneficial Use
Warm Springs Creek	Chlorpyrifos, Indicator Bacteria, Iron, Manganese, Nitrogen, Phosphorus	MUN, AGR, IND, PROC, REC1, REC2, WARM, WILD	Insert distance of project to RARE-designated waters (indicate whether feet, yards, or miles)
Murrieta Creek	Above plus Copper and Toxicity	MUN, AGR, IND, PROC, REC1, REC2, WARM, WILD	Insert distance of project to RARE-designated waters (indicate whether feet, yards, or miles)
Santa Margarita River (Upper)	Indicator Bacteria, Iron, Manganese, Nitrogen, Phosphorus	MUN, AGR, IND, REC1, REC2, WARM, COLD, WILD, RARE	9.2 miles from project site to Santa Margarita River (Upper)
Santa Margarita River (Lower)	Benthic Community Effects, Chlorpyrifos, Indicator Bacteria, Nitrogen, Phosphorus, Toxicity	MUN, AGR, IND, REC1, REC2, WARM, COLD, WILD, RARE	>9.2 miles
Santa Margarita Lagoon	Eutrophic	REC1, REC2, EST, WILD, RARE, MAR, MIGR, SPWN	>9.2 miles

A.3 Drainage System Susceptibility to Hydromodification

Using Table A-2 below, list in order of the point of discharge at the project site down to the Santa Margarita River², each drainage system or receiving water that the project site is tributary to. Continue to fill each row with the material of the drainage system, and any exemption (if applicable). Based on the results, summarize the applicable hydromodification performance standards that will be documented in Section E. Exempted categories of receiving waters include:

- Existing storm drains that discharge directly to water storage reservoirs, lakes, or enclosed embayments, or
- Conveyance channels whose bed and bank are concrete lined all the way from the point of discharge to water storage reservoirs, lakes, enclosed embayments, or the Pacific Ocean.
- Other water bodies identified in an approved WMAA (See Exhibit G to the WQMP)

Include a map exhibiting each drainage system and the associated susceptibility in Appendix 1.

Table A-2 Identification of Susceptibility to Hydromodification

Drainage System	Drainage System Material	Hydromodification Exemption	Hydromodification Exempt
Warm Springs Creek (15 miles long total)	Natural Earth	NONE.	<input type="checkbox"/> Y <input checked="" type="checkbox"/> N
Insert name and length (in miles) of 2nd drainage system	Identify either (1) the type of material of bed and bank for open channels; or (2) the material of storm drain pipes and conduits	Insert exemption justification for the 2 nd receiving water may qualify for. If none, insert NONE.	<input type="checkbox"/> Y <input type="checkbox"/> N
Insert name and length (in miles) of 3rd drainage system	Identify either (1) the type of material of bed and bank for open channels; or (2) the material of storm drain pipes and conduits	Insert exemption justification for the 3 rd receiving water may qualify for. If none, insert NONE.	<input type="checkbox"/> Y <input type="checkbox"/> N
Summary of Performance Standards			
<input type="checkbox"/> Hydromodification Exempt – Select if “Y” is selected in the Hydromodification Exempt column above, project is exempt from hydromodification requirements. <input checked="" type="checkbox"/> Not Exempt-Select if “N” is selected in any row of the Hydromodification Exempt column above. Project is subject to hydrologic control requirements and may be subject to sediment supply requirements.			

A.4 Additional Permits/Approvals required for the Project:

Table A-3 Other Applicable Permits

Agency	Permit Required	
State Department of Fish and Game, 1602 Streambed Alteration Agreement	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N
State Water Resources Control Board, Clean Water Act Section 401 Water Quality Certification	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N
US Army Corps of Engineers, Clean Water Act Section 404 Permit	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N
US Fish and Wildlife, Endangered Species Act Section 7 Biological Opinion	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N

² Refer to Exhibit G of the WQMP for a map of exempt and potentially exempt areas. These maps are from the Draft SMR WMAA as of January 5, 2018 and will be replaced upon acceptance of the SMR WMAA.

Statewide Construction General Permit Coverage	<input checked="" type="checkbox"/> Y	<input type="checkbox"/> N
Statewide Industrial General Permit Coverage	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N
Western Riverside MSHCP Consistency Approval (e.g., JPR, DBESP)	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N
Other (please list in the space below as required) TBD	<input checked="" type="checkbox"/> Y	<input type="checkbox"/> N

If yes is answered to any of the questions above, the Copermitttee may require proof of approval/coverage from those agencies as applicable including documentation of any associated requirements that may affect this Project-Specific WQMP.

Section B: Optimize Site Utilization (LID Principles)

Review of the information collected in Section 'A' will aid in identifying the principal constraints on site design and selection of LID BMPs as well as opportunities to reduce imperviousness and incorporate LID Principles into the site and landscape design. For example, constraints might include impermeable soils, high groundwater, groundwater pollution or contaminated soils, steep slopes, geotechnical instability, high-intensity land use, heavy pedestrian or vehicular traffic, utility locations or safety concerns. Opportunities might include existing natural areas, low areas, oddly configured or otherwise unbuildable parcels, easements and landscape amenities including open space and buffers (which can double as locations for LID Bioretention BMPs), and differences in elevation (which can provide hydraulic head). Prepare a brief narrative for each of the site optimization strategies described below. This narrative will help you as you proceed with your Low Impact Development (LID) design and explain your design decisions to others.

Apply the following LID Principles to the layout of the PDP to the extent they are applicable and feasible. Putting thought upfront about how best to organize the various elements of a site can help to significantly reduce the PDP's potential impact on the environment and reduce the number and size of Structural LID BMPs that must be implemented. Integrate opportunities to accommodate the following LID Principles within the preliminary PDP site layout to maximize implementation of LID Principles.

Site Optimization

Complete checklist below to determine applicable Site Design BMPs for your site.

Project- Specific WQMP Site Design BMP Checklist

The following questions below are based upon Section 3.2 of the SMR WQMP will help you determine how to best optimize your site and subsequently identify opportunities and/or constraints, and document compliance.

SITE DESIGN REQUIREMENTS

Answer the following questions below by indicating "Yes," "No," or "N/A" (Not Applicable). Justify all "No" and "N/A" answers by inserting a narrative at the end of the section. The narrative should include identification and justification of any constraints that would prevent the use of those categories of LID BMPs. Upon identifying Site Design BMP opportunities, include these on your WQMP Site plan in Appendix 1.

Did you identify and preserve existing drainage patterns?
Integrating existing drainage patterns into the site plan helps to maintain the time of concentration and infiltration rates of runoff, decreasing peak flows, and may also help preserve the contribution of Critical Coarse Sediment (i.e., Bed Sediment Supply) from the PDP to the Receiving Water. Preserve existing drainage patterns by:

Yes No N/A

- Minimizing unnecessary site grading that would eliminate small depressions, where appropriate add additional "micro" storage throughout the site landscaping.
- Where possible conform the PDP site layout along natural landforms, avoid excessive grading and disturbance of vegetation and soils, preserve or replicate the sites natural drainage features and patterns.
- Set back PDP improvements from creeks, wetlands, riparian habitats and any other natural water bodies.
- Use existing and proposed site drainage patterns as a natural design element, rather than using expensive impervious conveyance systems. Use depressed landscaped areas, vegetated buffers, and bioretention areas as amenities and focal points within the site and landscape design.

Discuss how this was included or provide a discussion/justification for "No" or "N/A" answer. An existing drainage channel runs through the center of the project and will remain unchanged within the jurisdictional limits.

Did you identify and protect existing vegetation?
Identify any areas containing dense native vegetation or well-established trees, and try to avoid disturbing these areas. Soils with thick, undisturbed vegetation have a much higher capacity to store and infiltrate runoff than do disturbed soils. Reestablishment of a mature vegetative community may take decades. Sensitive areas, such as streams and floodplains should also be avoided.

Yes No N/A

- Define the development envelope and protected areas, identifying areas that are most suitable for development and areas that should be left undisturbed.
- Establish setbacks and buffer zones surrounding sensitive areas.
- Preserve significant trees and other natural vegetation where possible.

Discuss how this was included or provide a discussion/justification for "No" or "N/A" answer. All well-established/dense native vegetation is within the drainage channels jurisdictional limits and will be protected.

Project- Specific WQMP Site Design BMP Checklist	
<input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> N/A	<p>Did you identify and preserve natural infiltration capacity? A key component of LID is taking advantage of a site's natural infiltration and storage capacity. A site survey and geotechnical investigation can help define areas with high potential for infiltration and surface storage.</p> <ul style="list-style-type: none"> • Identify opportunities to locate LID Principles and Structural BMPs in highly pervious areas. Doing so will maximize infiltration and limit the amount of runoff generated. • Concentrate development on portions of the site with less permeable soils, and preserve areas that can promote infiltration.
<p>Discuss how this was included or provide a discussion/justification for "No" or "N/A" answer. Geotech says bedrock at 5ft to 11ft depending on location across site.</p>	
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	<p>Did you minimize impervious area? Look for opportunities to limit impervious cover through identification of the smallest possible land area that can be practically impacted or disturbed during site development.</p> <ul style="list-style-type: none"> • Limit overall coverage of paving and roofs. This can be accomplished by designing compact, taller structures, narrower and shorter streets and sidewalks, clustering buildings and sharing driveways, smaller parking lots (fewer stalls, smaller stalls, and more efficient lanes), and indoor or underground parking. • Inventory planned impervious areas on your preliminary site plan. Identify where permeable pavements, or other permeable materials, such as crushed aggregate, turf block, permeable modular blocks, pervious concrete or pervious asphalt could be substituted for impervious concrete or asphalt paving. This will help reduce the amount of Runoff that may need to be addressed through Structural BMPs. • Examine site layout and circulation patterns and identify areas where landscaping can be substituted for pavement, such as for overflow parking. • Consider green roofs. Green roofs are roofing systems that provide a layer of soil/vegetative cover over a waterproofing membrane. A green roof mimics pre-development conditions by filtering, absorbing, and evapotranspiring precipitation to help manage the effects of an otherwise impervious rooftop.
<p>Discuss how this was included or provide a discussion/justification for "No" or "N/A" answer. Street sections have been limited to minimum allowable widths. Landscaped area and public park area have been maximized.</p>	

Project- Specific WQMP Site Design BMP Checklist	
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	<p>Did you identify and disperse runoff to adjacent pervious areas or small collection areas? Look for opportunities to direct runoff from impervious areas to adjacent landscaping, other pervious areas, or small collection areas where such runoff may be retained. This is sometimes referred to as reducing Directly Connected Impervious Areas.</p> <ul style="list-style-type: none"> • Direct roof runoff into landscaped areas such as medians, parking islands, planter boxes, etc., and/or areas of pervious paving. Instead of having landscaped areas raised above the surrounding impervious areas, design them as depressed areas that can receive Runoff from adjacent impervious pavement. For example, a lawn or garden depressed 3"-4" below surrounding walkways or driveways provides a simple but quite functional landscape design element. • Detain and retain runoff throughout the site. On flatter sites, smaller Structural BMPs may be interspersed in landscaped areas among the buildings and paving. • On hillside sites, drainage from upper areas may be collected in conventional catch basins and piped to landscaped areas and LID BMPs and/or Hydrologic Control BMPs in lower areas. Low retaining walls may also be used to create terraces that can accommodate LID BMPs. Wherever possible, direct drainage from landscaped slopes offsite and not to impervious surfaces like parking lots. • Reduce curb maintenance and provide for allowances for curb cuts. • Design landscaped areas or other pervious areas to receive and infiltrate runoff from nearby impervious areas. • Use Tree Wells to intercept, infiltrate, and evapotranspire precipitation and runoff before it reaches structural BMPs. Tree wells can be used to limit the size of Drainage Management Areas that must be treated by structural BMPs. Guidelines for Tree Wells are included in the Tree Well Fact Sheet in the LID BMP Design Handbook.
<p>Discuss how this was included or provide a discussion/justification for "No" or "N/A" answer. Runoff from impervious areas will be routed through pervious landscaping as best as possible; 1. Rooftop downspouts will outlet to landscaping where conditions allow as opposed to directly outleting to paved areas. 2 Landscaped parkways/areas will be used to maximize pervious area on site.</p>	
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	<p>Did you utilize native or drought tolerant species in site landscaping?</p> <p>Wherever possible, use native or drought tolerant species within site landscaping instead of alternatives. These plants are uniquely suited to local soils and climate and can reduce the overall demands for potable water use associated with irrigation.</p>
<p>Discuss how this was included or provide a discussion/justification for "No" or "N/A" answer. Project will be landscaped with native or drought tolerant species wherever possible.</p>	

Project- Specific WQMP Site Design BMP Checklist	
<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> N/A	<p>Did implement harvest and use of runoff?</p> <p>Under the Regional MS4 Permit, Harvest and Use BMPs must be employed to reduce runoff on any site where they are applicable and feasible. However, Harvest and Use BMPs are effective for retention of stormwater runoff only when there is adequate demand for non-potable water during the wet season. If demand for non-potable water is not sufficiently large, the actual retention of stormwater runoff will be diminished during larger storms or during back-to-back storms.</p> <p>For the purposes of planning level Harvest and Use BMP feasibility screening, Harvest and Use is only considered to be a feasible if the total average wet season demand for non-potable water is sufficiently large to use the entire DCV within 72 hours. If the average wet season demand for non-potable water is not sufficiently large to use the entire DCV within 72 hours, then Harvest and Use is not considered to be feasible and need not be considered further.</p> <p>The general feasibility and applicability of Harvest and Use BMPs should consider:</p> <ul style="list-style-type: none"> • Any downstream impacts related to water rights that could arise from capturing stormwater (not common). • Conflicts with recycled water used – where the project is conditioned to use recycled water for irrigation, this should be given priority over stormwater capture as it is a year-round supply of water. • Code Compliance - If a particular use of captured stormwater, and/or available methods for storage of captured stormwater would be contrary to building codes in effect at the time of approval of the preliminary Project-Specific WQMP, then an evaluation of harvesting and use for that use would not be required. • Wet season demand – the applicant shall demonstrate, to the acceptance of the [Insert Jurisdiction], that there is adequate demand for harvested water during the wet season to drain the system in a reasonable amount of time.
<p>Discuss how this was included or provide a discussion/justification for "No" or "N/A" answer. Drought tolerant vegetation will be used and harvest is not feasible.</p>	
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	<p>Did you keep the runoff from sediment producing pervious area hydrologically separate from developed areas that require treatment?</p> <p>Pervious area that qualify as self-treating areas or off-site open space should be kept separate from drainage to structural BMPs whenever possible. This helps limit the required size of structural BMPs, helps avoid impacts to sediment supply, and helps reduce clogging risk to BMPs.</p>
<p>Discuss how this was included or provide a discussion/justification for "No" or "N/A" answer. Areas are to be kept separate where possible.</p>	

Section C: Delineate Drainage Management Areas (DMAs)

This section provides streamlined guidance and documentation of the DMA delineation and categorization process, for additional information refer to the procedure in Section 3.3 of the SMR WQMP which discusses the methods of delineating and mapping your project site into individual DMAs. Complete Steps 1 to 4 to successfully delineate and categorize DMAs.

Step 1: Identify Surface Types and Drainage Pathways

Carefully delineate pervious areas and impervious areas (including roofs) throughout site and identify overland flow paths and above ground and below ground conveyances. Also identify common points (such as BMPs) that these areas drain to.

Step 2: DMA Delineation

Use the information in Step 1 to divide the entire PDP site into individual, discrete DMAs. Typically, lines delineating DMAs follow grade breaks and roof ridge lines. Where possible, establish separate DMAs for each surface type (e.g., landscaping, pervious paving, or roofs). Assign each DMA a unique code and determine its size in square feet. The total area of your site should total the sum of all of your DMAs (unless water from outside the project limits comingles with water from inside the project limits, i.e. runoff). Complete Table C-1

Table C-1 DMA Identification

DMA Name or Identification	Surface Type(s) ¹	Area (Sq. Ft.)	DMA Type
Basin A North	Mixed	105,963	To be Determined in Step 3
Basin A South	Mixed	280,169	
Basin B	Mixed	203,387	
Basin E	Impervious	21,156	
Basin F	Impervious	16,064	
Enter Unique Code	Enter Pervious, Impervious, or Mixed	Enter Area in Square Feet	

Add Columns as Needed

Step 3: DMA Classification

Determine how drainage from each DMA will be handled by using information from Steps 1 and 2 and by completing Steps 3.A to 3.C. Each DMA will be classified as one of the following four types:

- Type 'A': Self-Treating Areas:
- Type 'B': Self-Retaining Areas
- Type 'C': Areas Draining to Self-Retaining Areas
- Type 'D': Areas Draining to BMPs

Step 3.A – Identify Type 'A' Self-Treating Area

Indicate if the DMAs meet the following criteria by answering "Yes" or "No".

Yes No Area is undisturbed from their natural condition OR restored with Native and/or California Friendly vegetative covers.

Yes No Area is irrigated, if at all, with appropriate low water use irrigation systems to prevent irrigation runoff.

Yes No Runoff from the area will not comeingle with runoff from the developed portion of the site, or across other landscaped areas that do not meet the above criteria.

If all answers indicate "Yes," complete Table C-2 to document the DMAs that are classified as Self-Treating Areas.

Table C-2 Type 'A', Self-Treating Areas

DMA Name or Identification	Area (Sq. Ft.)	Stabilization Type	Irrigation Type (if any)

Step 3.B – Identify Type 'B' Self-Retaining Area and Type 'C' Areas Draining to Self-Retaining Areas

Type 'B' Self-Retaining Area: A Self-Retaining Area is shallowly depressed 'micro infiltration' areas designed to retain the Design Storm rainfall that reaches the area, without producing any Runoff.

Indicate if the DMAs meet the following criteria by answering "Yes," "No," or "N/A".

- Yes No N/A Slopes will be graded toward the center of the pervious area.
- Yes No N/A Soils will be freely draining to not create vector or nuisance conditions.
- Yes No N/A Inlet elevations of area/overflow drains, if any, should be clearly specified to be three inches or more above the low point to promote ponding.
- Yes No N/A Pervious pavements (e.g., crushed stone, porous asphalt, pervious concrete, or permeable pavers) can be self-retaining when constructed with a gravel base course four or more inches deep below any underdrain discharge elevation.

If all answers indicate "Yes," DMAs may be categorized as Type 'B', proceed to identify Type 'C' Areas Draining to Self-Retaining Areas.

Type 'C' Areas Draining to Self-Retaining Areas: Runoff from impervious or partially pervious areas can be managed by routing it to Self-Retaining Areas consistent with the LID Principle discussed in SMR WQMP Section 3.2.5 for 'Dispersing Runoff to Adjacent Pervious Areas'.

Indicate if the DMAs meet the following criteria by answering "Yes" or "No".

- Yes No The drainage from the tributary area must be directed to and dispersed within the Self-Retaining Area.
- Yes No Area must be designed to retain the entire Design Storm runoff without flowing offsite.

If all answers indicate "Yes," DMAs may be categorized as Type 'C'.

Complete Table C-3 and Table C-4 to identify Type 'B' Self-Retaining Areas and Type 'C' Areas Draining to Self-Retaining Areas.

Table C-3 Type 'B', Self-Retaining Areas

Self-Retaining Area				Type 'C' DMAs that are draining to the Self-Retaining Area		
DMA Name/ ID	Post-project surface type	Area (square feet)	Storm Depth (inches)	DMA Name / ID	[C] from Table C-4=	Required Retention Depth (inches)
		[A]	[B]		[C]	$[D] = [B] + \frac{[B] \cdot [C]}{[A]}$

Table C-4 Type 'C', Areas that Drain to Self-Retaining Areas

DMA					Receiving Self-Retaining DMA		
DMA Name/ ID	Area (square feet)	Post-project surface type	Runoff factor	Product	DMA name /ID	Area (square feet)	Ratio
	[A]		[B]	$[C] = [A] \times [B]$		[D]	$[C]/[D]$

Note: (See Section 3.3 of SMR WQMP) Ensure that partially pervious areas draining to a Self-Retaining area do not exceed the following ratio:

$$\left(\frac{2}{\text{Impervious Fraction}} \right) : 1$$

(Tributary Area: Self-Retaining Area)

Step 3.C – Identify Type ‘D’ Areas Draining to BMPs

Areas draining to BMPs are those that could not be fully managed through LID Principles (DMA Types A through C) and will instead drain to an LID BMP and/or a Conventional Treatment BMP designed to manage water quality impacts from that area, and Hydromodification where necessary.

Complete Table C-5 to document which DMAs are classified as Areas Draining to BMPs

Table C-5 Type ‘D’, Areas Draining to BMPs

DMA Name or ID	BMP Name or ID Receiving Runoff from DMA
Basin A North	Basin A
Basin A South	Basin A
Basin B	Basin B
Basin E	Bioretention Vegetated Swale E
Basin F	Bioretention Vegetated Swale F

Note: More than one DMA may drain to a single LID BMP; however, one DMA may not drain to more than one BMP.

Section D: Implement LID BMPs

The Regional MS4 Permit requires the use of LID BMPs to provide retention or treatment of the DCV and includes a BMP hierarchy which requires Full Retention BMPs (Priority 1) to be considered before Biofiltration BMPs (Priority 2) and Flow-Through Treatment BMPs and Alternative Compliance BMPs (Priority 3). LID BMP selection must be based on technical feasibility and should be considered early in the site planning and design process. Use this section to document the selection of LID BMPs for each DMA. Note that feasibility is based on the DMA scale and may vary between DMAs based on site conditions.

D.1 Full Infiltration Applicability

An assessment of the feasibility of utilizing full infiltration BMPs is required for all projects, except where it can be shown that site design LID principals fully retain the DCV (i.e., all DMAs are Type A, B, or C), or where Harvest and Use BMPs fully retain the DCV. Check the following box if applicable:

- Site design LID principals fully retain the DCV (i.e., all DMAs are Type A, B, or C), (Proceed to Section E).

If the above box remains unchecked, perform a site-specific evaluation of the feasibility of Infiltration BMPs using each of the applicable criteria identified in Chapter 2.3.3 of the SMR WQMP and complete the remainder of Section D.1.

Geotechnical Report

A Geotechnical Report or Phase I Environmental Site Assessment may be required by the Copermittee to confirm present and past site characteristics that may affect the use of Infiltration BMPs. In addition, the Copermittee, at their discretion, may not require a geotechnical report for small projects as described in Chapter 2 of the SMR WQMP. If a geotechnical report has been prepared, include it in Appendix 3. In addition, if a Phase I Environmental Site Assessment has been prepared, include it in Appendix 4.

Infiltration Feasibility

Table D-1 below is meant to provide a simple means of assessing which DMAs on your site support Infiltration BMPs and is discussed in the SMR WQMP in Chapter 2.3.3. Check the appropriate box for each question and then list affected DMAs as applicable. If additional space is needed, add a row below the corresponding answer.

Table D-1 Infiltration Feasibility

Downstream Impacts (SMR WQMP Section 2.3.3.a)		
Does the project site...	YES	NO
...have any DMAs where infiltration would negatively impact downstream water rights or other Beneficial Uses ³ ?		X
If Yes, list affected DMAs:		
Groundwater Protection (SMR WQMP Section 2.3.3.b)		
Does the project site...	YES	NO
...have any DMAs with industrial, and other land uses that pose a high threat to water quality, which cannot be treated by Bioretention BMPs? Or have DMAs with active industrial process areas?		X
If Yes, list affected DMAs:		
...have any DMAs with a seasonal high groundwater mark shallower than 10 feet?		X
If Yes, list affected DMAs:		
...have any DMAs located within 100 feet horizontally of a water supply well?		X
If Yes, list affected DMAs:		
...have any DMAs that would restrict BMP locations to within a 2:1 (horizontal: vertical) influence line extending from any septic leach line?		X
If Yes, list affected DMAs:		
...have any DMAs been evaluated by a licensed Geotechnical Engineer, Hydrogeologist, or Environmental Engineer, who has concluded that the soils do not have adequate physical and chemical characteristics for the protection of groundwater, and has treatment provided by amended media layers in Bioretention BMPs been considered in evaluating this factor?	X	
If Yes, list affected DMAs:		
		All DMAs to be bio with partial infil
Public Safety and Offsite Improvements (SMR WQMP Section 2.3.3.c)		
Does the project site...	YES	NO
...have any areas identified by the geotechnical report as posing a public safety risk where infiltration of stormwater could have a negative impact?		X
If Yes, list affected DMAs:		
Infiltration Characteristics For LID BMPs (SMR WQMP Section 2.3.3.d)		
Does the project site...	YES	NO
...have factored infiltration rates of less than 0.8 inches / hour? (Note: on a case-by-case basis, the Local Jurisdiction may allow a factor of safety as low as 1.0 to support selection of full infiltration BMPs. Therefore, measured infiltration rates could be as low as 0.8 in/hr to support full infiltration. A higher factor of safety would be required for design in accordance with the LID BMP Deign Handbook).	X	
If Yes, list affected DMAs: All DMAs		
Cut/Fill Conditions (SMR WQMP Section 2.3.3.e)		
Does the project site...	YES	NO
...have significant cut and/or fill conditions that would preclude in-situ testing of infiltration rates at the final infiltration surface?	X	
If Yes, list affected DMAs: All DMAs		
Other Site-Specific Factors (SMR WQMP Section 2.3.3.f)		
Does the project site...	YES	NO
...have DMAs where the geotechnical investigation discovered other site-specific factors that would preclude effective and/or safe infiltration?	X	
Describe here: High ground water and thick layer of bedrock 5ft-11ft below surface.		

³ Such a condition must be substantiated by sufficient modeling to demonstrate an impact and would be subject to [Insert Jurisdiction] discretion. There is not a standardized method for assessing this criterion. Water rights evaluations should be site-specific.

If you answered “Yes” to any of the questions above for any DMA, Infiltration BMPs that rely solely on infiltration should not be used for those DMAs and you should proceed to the assessment for Biofiltration BMPs below. Biofiltration BMPs that provide partial infiltration may still be feasible and should be assessed in Section D.2. Summarize concerns identified in the Geotechnical Report, if any, that resulted in a “YES” response above in the table below.

Table D-2 Geotechnical Concerns for Onsite Infiltration

Type of Geotechnical Concern	DMAs Feasible (By Name or ID)	DMAs Infeasible (By Name or ID)
Collapsible Soil		
Expansive Soil		
Slopes		
Liquefaction		
Other (Hit bedrock between 5ft to 11ft down)	All DMAs	

D.2 Biofiltration Applicability

This section should document the applicability of biofiltration BMPs for Type D DMAs that are not feasible for full infiltration BMPs. The key decisions to be documented in this section include:

1. Are biofiltration BMPs with partial infiltration feasible?
 - a. Biofiltration BMPs must be designed to maximize incidental infiltration via a partial infiltration design unless it is demonstrated that this design is not feasible.
 - b. These designs can be used at sites with low infiltration rates where other feasibility factors do not preclude incidental infiltration.

Document summary in Table D-3.

2. If not, what are the factors that require the use of biofiltration with no infiltration? This may include:
 - a. Geotechnical hazards
 - b. Water rights issues
 - c. Water balance issues
 - d. Soil contamination or groundwater quality issues
 - e. Very low infiltration rates (factored rates < 0.1 in/hr)
 - f. Other factors, demonstrated to the acceptance of the local jurisdiction

If this applies to any DMAs, then rationale must be documented in Table D-3.

3. Are biofiltration BMPs infeasible?
 - a. If yes, then provide a site-specific analysis demonstrating the technical infeasibility of all LID BMPs has been performed and is included in Appendix 5. If you plan to submit an analysis demonstrating the technical infeasibility of LID BMPs, request a pre-submittal meeting with the Copermittee with jurisdiction over the Project site to discuss this option. Proceed to Section F to document your alternative compliance measures.

Table D-3 Evaluation of Biofiltration BMP Feasibility

DMA ID	Is Partial/ Incidental Infiltration Allowable? (Y/N)	Basis for Infeasibility of Partial Infiltration (provide summary and include supporting basis if partial infiltration not feasible)
Basin A North	Y	
Basin A South	Y	
Basin B	Y	
Basin E	Y	
Basin F	Y	

Proprietary Biofiltration BMP Approval Criteria

If the project will use proprietary BMPs as biofiltration BMPs, then this section is completed to document that the proprietary BMPs are selected in accordance with Section 2.3.7 of the SMR WQMP. Proprietary Biofiltration BMPs must meet both of the following approval criteria:

1. Approval Criteria for All Proprietary BMPs, and
2. Acceptance Criteria for Proprietary Biofiltration BMPs.

When the use of proprietary biofiltration BMPs is proposed to meet the Pollutant Control performance standards, use Table D-4 to document that appropriate approval criteria have been met for the proposed BMPs. Add additional rows to document approval criteria are met for each type of BMP proposed.

Table D-4 Proprietary BMP Approval Requirement Summary

Proposed Proprietary Biofiltration BMP	Approval Criteria	Notes/Comments
All onsite Bio-basins and Bioretention Vegetated Swales	<input type="checkbox"/> Proposed BMP has an active TAPE GULD Certification for the project pollutants of concern ⁴ or equivalent 3 rd party demonstrated performance.	Insert text here
	<input type="checkbox"/> The BMP is used in a manner consistent with manufacturer guidelines and conditions of its third-party certification.	Insert text here
	<input checked="" type="checkbox"/> The BMP includes biological features including vegetation supported by engineered or other growing media.	Basin with have vegetation supported by engineered/growing media
	<input checked="" type="checkbox"/> The BMP is designed to maximize infiltration, or supplemental infiltration is provided to achieve retention equivalent to Biofiltration with Partial Infiltration BMPs if factored infiltration rate is between 0.1 and 0.8 inches/hour.	Describe supplemental retention practices if applicable.

⁴ Use Table F-1 and F-2 to identify and document the pollutants of concern and include these tables in Appendix 5.

	<input checked="" type="checkbox"/> The BMP is sized using one of two Biofiltration LID sizing options in Section 2.3.2 of the SRM WQMP.	see Developed Condition WQMP Exhibit in appendix 1 for method used, resulting size (flow or volume), and provided sizes(of proposed units)
--	--	--

D.3 Feasibility Assessment Summaries

From the Infiltration, Biofiltration with Partial Infiltration and Biofiltration with No Infiltration Sections above, complete Table D-5 below to summarize which LID BMPs are technically feasible, and which are not, based upon the established hierarchy.

Table D-5 LID Prioritization Summary Matrix

DMA Name/ID	LID BMP Hierarchy			No LID (Alternative Compliance)
	1. Infiltration	2. Biofiltration with Partial Infiltration	3. Biofiltration with No Infiltration	
Basin A	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Basin B	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Basin E	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Basin F	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Insert text here	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Insert text here	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

For those DMAs where LID BMPs are not feasible, provide a narrative in Table D-6 below summarizing why they are not feasible, include your technical infeasibility criteria in Appendix 5, and proceed to Section F below to document Alternative Compliance measures for those DMAs. Recall that each proposed DMA must pass through the LID BMP hierarchy before alternative compliance measures may be considered.

This is based on the clarification letter titled “San Diego Water Board’s Expectations of Documentation to Support a Determination of Priority Development Project Infiltration Infeasibility” (April 28, 2017, Via email from San Diego Regional Water Quality Control Board to San Diego County Municipal Storm Water Copermittees⁵).

Table D-6 Summary of Infeasibility Documentation

Question	Narrative Summary (include reference to applicable appendix/attachment/report, as applicable)
a) When in the entitlement process did a geotechnical engineer analyze the site for infiltration feasibility?	N/A
b) When in the entitlement process were other investigations conducted (e.g., groundwater	N/A

⁵ <http://www.projectcleanwater.org/download/pdp-infiltration-infeasibility/>

<p>quality, water rights) to evaluate infiltration feasibility?</p>	
<p>c) What was the scope and results of testing, if conducted, or rationale for why testing was not needed to reach findings?</p>	N/A
<p>d) What public health and safety requirements affected infiltration locations?</p>	N/A
<p>e) What were the conclusions and recommendations of the geotechnical engineer and/or other professional responsible for other investigations?</p>	N/A
<p>f) What was the history of design discussions between the permittee and applicant for the proposed project, resulting in the final design determination related locations feasible for infiltration?</p>	N/A
<p>g) What site design alternatives were considered to achieve infiltration or partial infiltration on site?</p>	N/A
<p>h) What physical impairments (i.e., fire road egress, public safety considerations, utilities) and public safety concerns influenced site layout and infiltration feasibility?</p>	N/A
<p>i) What LID Principles (site design BMPs) were included in the project site design?</p>	N/A

D.4 LID BMP Sizing

Each LID BMP must be designed to ensure that the DCV will be captured by the selected BMPs with no discharge to the storm drain or surface waters during the DCV size storm. Infiltration BMPs must at minimum be sized to capture the DCV to achieve pollutant control requirements.

Biofiltration BMPs must at a minimum be sized to:

- Treat 1.5 times the DCV not reliably retained on site using a volume-base or flow-based sizing method, or
- Include static storage volume, including pore spaces and pre-filter detention volume, at least 0.75 times the portion of the DCV not reliably retained on site.

First, calculate the DCV for each LID BMP using the V_{BMP} worksheet in Appendix F of the LID BMP Design Handbook. Second, design the LID BMP to meet the required V_{BMP} using the methods included in Section 3 of the LID BMP Design Handbook. Utilize the worksheets found in the LID BMP Design Handbook or consult with the Copermittee to assist you in correctly sizing your LID BMPs. Use Table D-7 below to document the DCV each LID BMP. Provide the completed design procedure sheets for each LID BMP in Appendix 6. You may add additional rows to the table below as needed.

Table D-7 DCV Calculations for LID BMPs

DMA Type/ID	DMA (square feet)	Post-Project Surface Type	Effective Impervious Fraction, I_f	DMA Runoff Factor	DMA Areas x Runoff Factor	Enter BMP Name / Identifier Here		
						Biofiltration Basin or Vegetated Swale		
	[A]		[B]	[C]	[A] x [C]			
Basin A North	105,963	Mixed	0.87	0.69	73,114	Design Storm Depth (in)	DCV, V_{BMP} (cubic feet)	Proposed Volume on Plans (cubic feet)
Basin A South	280,169	Mixed	0.87	0.69	193,317			
Basin B	203,387	Mixed	0.87	0.69	140,337			
Basin E	21,156	Imper	1.00	0.69	14,598			
Basin F	16,064	Imper	1.00	0.69	11,084			
	$A_T = \Sigma[A]$				$\Sigma = [D] = 432,450$	[E] = 0.6	$[F] = \frac{[D] \times [E]}{12} = 21,623$	[G] = 31,394

[B], [C] is obtained as described in Section 2.6.1.b of the SMR WQMP

[E] is obtained from Exhibit A in the SMR WQMP

[G] is obtained from a design procedure sheet, such as in LID BMP Design Handbook and placed in Appendix 6.

Complete Table D-8 below to document the Design Capture Volume and the Proposed Volume for each LID BMP. You can add rows to the table as needed. Alternatively, the Santa Margarita Hydrology Model (SMRHM) can be used to size LID BMPs to address the DCV and, if applicable, to size Hydrologic Control BMPs to meet the Hydrologic Performance Standard described in the SMR WQMP, as identified in Section E.

Table D-8 LID BMP Sizing

BMP Name / ID	DMA No.	BMP Type / Description	Design Capture Volume (ft ³)	Proposed Volume (ft ³)
Basin A	Basin A (N&S)	Bio Basin (Partial Infil)	13,187	15,386
Basin B	Basin B	Bio Basin (Partial Infil)	6,950	14,100
Vegetated Swale E	Basin E	Bioretention (Partial Infil)	960	1,092
Vegetated Swale F	Basin F	Bioretention (Partial Infil)	725	816

If bioretention will include a capped underdrain, then include sizing calculations demonstrating that the BMP will meet infiltration sizing requirements with the underdrain capped and also meet biofiltration sizing requirements if the underdrain is uncapped.

Section E: Implement Hydrologic Control BMPs and Sediment Supply BMPs

If a completed Table 1.2 demonstrates that the project is exempt from Hydromodification Performance Standards, specify N/A and proceed to Section G.

- N/A Project is Exempt from Hydromodification Performance Standards.

If a PDP is not exempt from hydromodification requirements than the PDP must satisfy the requirements of the performance standards for hydrologic control BMPs and Sediment Supply BMPs. The PDP may choose to satisfy hydrologic control requirements using onsite or offsite BMPs (i.e. Alternative Compliance). Sediment supply requirements cannot be met via alternative compliance. If N/A is not selected above, select one of the two options below and complete the applicable sections.

- Project is Not Hydromodification Exempt and chooses to implement Hydrologic Control and Sediment Supply BMPs Onsite (complete Section E).
- Project is Not Hydromodification Exempt and chooses to implement Hydrologic Control Requirements using Alternative Compliance (complete Section F). Selection of this option must be approved by the Copermittee.

E.1 Hydrologic Control BMP Selection

Capture of the DCV and achievement of the Hydrologic Performance Standard may be met by combined and/or separate structural BMPs. The user should consider the full suite of Hydrologic Control BMPs to manage runoff from the post-development condition and meet the Hydrologic Performance Standard identified in this section.

The Hydrologic Performance Standard consists of matching or reducing the flow duration curve of post-development conditions to that of pre-existing, naturally occurring conditions, for the range of geomorphically significant flows (10% of the 2-year runoff event up to the 10-year runoff event). Select each of the hydrologic control BMP types that are applied to meet the above performance standard on the site.

- LID principles as defined in Section 3.2 of the SMR WQMP.
- Structural LID BMPs that may be modified or enlarged, if necessary, beyond the DCV.
- Structural Hydrologic Control BMPs that are distinct from the LID BMPs above. The LID BMP Design Handbook provides information not only on Hydrologic Control BMP design, but also on BMP design to meet the combined LID requirement and Hydrologic Performance Standard. The Handbook specifies the type of BMPs that can be used to meet the Hydrologic Performance Standard.

E.2 Hydrologic Control BMP Sizing

Hydrologic Control BMPs must be designed to ensure that the flow duration curve of the post-development DMA will not exceed that of the pre-existing, naturally occurring, DMA for the range of geomorphically significant flows. Using SMRHM, (or another acceptable continuous simulation model if approved by the Copermittee) the applicant shall demonstrate that the performance of the Hydrologic Control BMPs complies with the Hydrologic Performance Standard. Complete Table E-1 below and identify, for each DMA, the type of Hydrologic Control BMP, if the SMRHM model confirmed the management (Identified as “passed” in SMRHM), the total volume capacity of the Hydrologic Control BMP, the Hydrologic Control BMP footprint at top floor elevation, and the drawdown time of the Hydrologic Control BMP. SMRHM summary reports should be documented in Appendix 7. Refer to the SMRHM Guidance Document for additional information on SMRHM. You can add rows to the table as needed.

Table E-1 Hydrologic Control BMP Sizing

BMP Name / ID	DMA No.	BMP Type / Description	SMRHM Passed	BMP Volume (cf)	BMP Footprint (sf)	Drawdown time (hr)
Basin A	Basin A	Biofiltration and Detention Basin	<input checked="" type="checkbox"/>	15,386	5,813	60.78
Basin B	Basin B	Biofiltration and Detention Basin	<input checked="" type="checkbox"/>	14,100	5,282	31.31
			<input type="checkbox"/>			
			<input type="checkbox"/>			

If a bioretention BMP with capped underdrain is used and hydromodification requirements apply, then sizing calculations must demonstrate that the BMP meets flow duration control criteria with the underdrain capped and uncapped. Both calculations must be included.

E.3 Implement Sediment Supply BMPs

The sediment supply performance standard applies to PDPs for which hydromodification applied that have the potential to impact Potential Critical Coarse Sediment Yield Areas. Refer to Exhibit G of the WQMP to determine if there are onsite Potential Critical Coarse Sediment Yield Areas or Potential Sediment Source Areas. Select one of the two options below and include the Potential Critical Coarse Sediment Yield Area Exhibit showing your project location in Appendix 7.

- There are no mapped Potential Critical Coarse Sediment Yield Areas or Potential Sediment Source Areas on the site. The Sediment Supply Performance Standard is met with no further action.
- There are mapped Potential Critical Coarse Sediment Yield Areas or Potential Sediment Source Areas on the site, the Sediment Supply Performance Standard will be met through Option 1 or Option 2 below.

The applicant may refer to Section 3.6.4 of the SMR WQMP for a description of the methodology to meet the Sediment Supply Performance Standard. Select the applicable compliance pathway and complete the

appropriate sections to demonstrate compliance with the Sediment Supply Performance Standard if the second box is selected above:

- Avoid impacts related to any PDP activities to Potential Critical Coarse Sediment Yield Areas. Proceed to Section E.3.1.
- Complete a Site-Specific Critical Coarse Sediment Analysis. Proceed to Section E.3.2.

E.3.1 Option 1: Avoid Potential Critical Coarse Sediment Yield Areas and Potential Sediment Source Areas

The simplest approach for complying with the Sediment Supply Performance Standard is to avoid impacts to areas identified as Potential Critical Coarse Sediment Yield Areas or Potential Sediment Supply Areas. If a portion of PDP is identified as a Potential Critical Coarse Sediment Yield Area or a Potential Sediment Source Area, that PDP may still achieve compliance with the Sediment Supply Performance Standards if Potential Critical Coarse Sediment Yield Areas and Potential Sediment Supply Areas are avoided, i.e. areas are not developed and thereby delivery of Critical Coarse Sediment to the receiving waters is not impeded by site developments.

Provide a narrative describing how the PDP has avoided impacts to Potential Critical Coarse Sediment Yield Areas and/or Potential Sediment Source Areas below.

The site does not enter into the creeks jurisdictional limits and will therefore not impact the Potential Critical Coarse Sediment Yield Areas and/or Potential Sediment Source Areas.

If it is not feasible to avoid these areas, proceed to Option 2 to complete a Site-Specific Critical Coarse Sediment Analysis.

E.3.2 Option 2: Site-Specific Critical Coarse Sediment Analysis

Perform a stepwise assessment to ensure the maintenance of the pre-project source(s) of Critical Coarse Sediment (i.e., Bed Sediment Supply):

1. Determine whether the site or a portion of the site is a Significant Source of Bed Sediment Supply to the Receiving Channel (i.e., an actual verified Critical Coarse Sediment Yield Area);
2. Avoid areas identified as actual verified Critical Coarse Sediment Yield Areas in the PDP design and maintain pathways for discharge of Bed Sediment Supply from these areas to receiving waters.

Step 1: Identify if the site is an actual verified Critical Coarse Sediment Yield Area supplying Bed Sediment Supply to the receiving channel

- Step 1.A – Is the Bed Sediment of onsite streams similar to that of receiving streams?

- Rate the similarity:
- High
 - Medium
 - Low

Results from the geotechnical and sieve analysis to be performed both onsite and in the receiving channel should be documented in Appendix 7. Of particular interest, the results of the sieve

analysis, the soil erodibility factor, a description of the topographic relief of the project area, and the lithology of onsite soils should be reported in Appendix 7.

- Step 1.B – Are onsite streams capable of delivering Bed Sediment Supply from the site, if any, to the receiving channel?

Rate the potential: High
 Medium
 Low

Results from the analyses of the sediment delivery potential to the receiving channel should be documented in Appendix 7 and identify, at a minimum, the Sediment Source, the distance to the receiving channel, the onsite channel density, the project watershed area, the slope, length, land use, and rainfall intensity.

- Step 1.C – Will the receiving channel adversely respond to a change in Bed Sediment Load?

Rate the need for bed sediment supply:
 High
 Medium
 Low

Results from the in-stream analysis to be performed both onsite should be documented in Appendix 7. The analysis should, at a minimum, quantify the bank stability and the degree of incision, provide a gradation of the Bed Sediment within the receiving channel, and identify if the channel is sediment supply-limited.

- Step 1.D – Summary of Step 1

Summarize in Table E.3 the findings of Step 1 and associate a score (in parenthesis) to each step. The sum of the three individual scores determines if a stream is a significant contributor to the receiving stream.

- Sum is equal to or greater than eight - Site is a significant source of sediment bed material – all on-site streams must be preserved or by-passed within the site plan. The applicant shall proceed to Step 2 for all onsite streams.
- Sum is greater than five but lower than eight. Site is a source of sediment bed material – some of the on-site streams must be preserved (with identified streams noted). The applicant shall proceed to Step 2 for the identified streams only.
- Sum is equal to or lower than five. Site is not a significant source of sediment bed material. The applicant may advance to Section F.

Table E-2 Triad Assessment Summary

Step	Rating			Total Score
1.A	<input type="checkbox"/> High (3)	<input type="checkbox"/> Medium (2)	<input type="checkbox"/> Low (1)	
1.B	<input type="checkbox"/> High (3)	<input type="checkbox"/> Medium (2)	<input type="checkbox"/> Low (1)	
1.C	<input type="checkbox"/> High (3)	<input type="checkbox"/> Medium (2)	<input type="checkbox"/> Low (1)	
Significant Source Rating of Bed Sediment to the receiving channel(s)				

Step 2: Avoid Development of Critical Coarse Sediment Yield Areas, Potential Sediment Sources Areas, and Preserve Pathways for Transport of Bed Sediment Supply to Receiving Waters

Onsite streams identified as an actual verified Critical Coarse Sediment Yield Areas should be avoided in the site design and transport pathways for Critical Coarse Sediment should be preserved

Check those that apply:

The site design does avoid all onsite channels identified as actual verified Critical Coarse Sediment Yield Areas

AND

The drainage design bypasses flow and sediment from onsite upstream drainages identified as actual verified Critical Coarse Sediment Yield Areas to maintain Critical Coarse Sediment supply to receiving waters

(If both are yes, the applicant may disregard subsequent steps of Section E.3 and directly advance directly to Section G).

- Or -

The site design does NOT avoid all onsite channels identified as actual verified Critical Coarse Sediment Yield Areas

OR

The project impacts transport pathways of Critical Coarse Sediment from onsite upstream drainages.

(If either of these are the case, the applicant may proceed with the subsequent steps of Section E.3).

Provide in Appendix 7 a site map that identifies all onsite channels and highlights those onsite channels that were identified as a Significant Source of Bed Sediment. The site map shall demonstrate, if feasible, that the site design avoids those onsite channels identified as a Significant Source of Bed Sediment. In addition, the applicant shall describe the characteristics of each onsite channel identified as a Significant Source of Bed Sediment. If the design plan cannot avoid the onsite channels, please provide a rationale for each channel individually.

The site map shall demonstrate that the drainage design bypasses those onsite channels that supply Critical Coarse Sediment to the receiving channel(s). In addition, the applicant shall describe the characteristics of each onsite channel identified as an actual verified Critical Coarse Sediment Yield Area.

Identified Channel #1 - Insert narrative description here

Identified Channel #2 - Insert narrative description here

Identified Channel #3 - Insert narrative description here

E.3.3 Sediment Supply BMPs to Result in No Net Impact to Downstream Receiving Waters

If impacts to Critical Coarse Sediment Yield Areas cannot be avoided, sediment supply BMPs must be implemented such there is no net impact to receiving waters. Sediment supply BMPs may consist of approaches that permit flux of bed sediment supply from Critical Coarse Sediment Yield Areas within the project boundary. This approach is subject to acceptance by the [Insert Jurisdiction]. It may require extensive documentation and analysis by qualified professionals to support this demonstration.

Appendix H of the San Diego Model BMP Design Manual provides additional information on site-specific investigation of Critical Coarse Sediment Supply areas.

<http://www.projectcleanwater.org/download/2018-model-bmp-design-manual/>

If applicable, insert narrative description here

Documentation of sediment supply BMPs should be detailed in Appendix 7.

Section F: Alternative Compliance

Alternative Compliance may be used to achieve compliance with pollutant control and/or hydromodification requirements for a given PDP. Alternative Compliance may be used under two scenarios, check the applicable box if the PDP is proposing to use Alternative Compliance to satisfy all or a portion of the Pollutant Control and/or Hydrologic Control requirements (but not sediment supply requirements)

- If it is not feasible to fully implement Infiltration or Biofiltration BMPs at a PDP site, Flow-Through Treatment Control BMPs may be used to treat pollutants contained in the portion of DCV not reliably retained on site and Alternative Compliance measures must also be implemented to mitigate for those pollutants in the DCV that are not retained or removed on site prior to discharging to a receiving water.

- Alternative Compliance is selected to comply with either pollutant control or hydromodification flow control requirements even if complying with these requirements is potentially feasible on-site. If such voluntary Alternative Compliance is implemented, Flow-Through Treatment Control BMPs must still be used to treat those pollutants in the portion of the DCV not reliably retained on site prior to discharging to a receiving water.

Refer to Section 2.7 of the SMR WQMP and consult the Local Jurisdiction for currently available Alternative Compliance pathways. Coordinate with the Copermittee if electing to participate in Alternative Compliance and complete the sections below to document implementation of the Flow-Through BMP component of the program.

F.1 Identify Pollutants of Concern

The purpose of this section is to help you appropriately plan for mitigating your Pollutants of Concern in lieu of implementing LID BMPs and to document compliance and.

Utilize Table A-1 from Section A, which noted your project's Receiving Waters, to identify impairments for Receiving Waters (including downstream receiving waters) by completing Table F-1. Table F-1 includes the watersheds identified as impaired in the Approved 2010 303(d) list; check box corresponding with the PDP's receiving water. The most recent 303(d) lists are available from the State Water Resources Control Board website:

https://www.waterboards.ca.gov/water_issues/programs/tmdl/integrated2010.shtml). https://www.waterboards.ca.gov/water_issues/programs/tmdl/integrated2010.shtml.

Table F-1 Summary of Approved 2010 303(d) listed waterbodies and associated pollutants of concern for the Riverside County SMR Region and downstream waterbodies.

Water Body		Nutrients¹	Metals²	Toxicity	Bacteria and Pathogens	Pesticides and Herbicides	Sulfate	Total Dissolved Solids
<input type="checkbox"/>	De Luz Creek	X	X				X	
<input type="checkbox"/>	Long Canyon Creek		X		X	X		
<input checked="" type="checkbox"/>	Murrieta Creek	X	X	X		X		
<input type="checkbox"/>	Redhawk Channel	X	X		X	X		X
<input type="checkbox"/>	Santa Gertudis Creek	X	X		X	X		
<input checked="" type="checkbox"/>	Santa Margarita Estuary (Lagoon?)	X						
<input checked="" type="checkbox"/>	Santa Margarita River (Lower)	X			X			
<input checked="" type="checkbox"/>	Santa Margarita River (Upper)	X		X				
<input type="checkbox"/>	Temecula Creek	X	X	X		X		X
<input checked="" type="checkbox"/>	Warm Springs Creek	X	X		X	X		

¹ Nutrients include nitrogen, phosphorus and eutrophic conditions caused by excess nutrients.

² Metals includes copper, iron, and manganese.

Use Table F-2 to identify the pollutants identified with the project site. Indicate the applicable PDP Categories and/or Project Features by checking the boxes that apply. If the identified General Pollutant Categories are the same as those listed for your Receiving Waters, then these will be your Pollutants of Concern; check the appropriate box or boxes in the last row.

Table F-2 Potential Pollutants by Land Use Type

Priority Development Project Categories and/or Project Features (check those that apply)		General Pollutant Categories									
		Bacterial Indicators	Metals	Nutrients	Pesticides	Toxic Organic Compounds	Sediments	Trash & Debris	Oil & Grease	Total Dissolved Solids	Sulfate
<input type="checkbox"/>	Detached Residential Development	P	N	P	P	N	P	P	P	N	N
<input checked="" type="checkbox"/>	Attached Residential Development	P	N	P	P	N	P	P	P ⁽²⁾	N	N
<input type="checkbox"/>	Commercial/Industrial Development	P ⁽³⁾	P ⁽⁷⁾	P ⁽¹⁾	P ⁽¹⁾	P	P ⁽¹⁾	P	P	N	N
<input type="checkbox"/>	Automotive Repair Shops	N	P	N	N	P ^(4, 5)	N	P	P	N	N
<input type="checkbox"/>	Restaurants (>5,000 ft ²)	P	N	N	P ⁽¹⁾	N	N	P	P	N	N
<input type="checkbox"/>	Hillside Development (>5,000 ft ²)	P	N	P	P	N	P	P	P	N	N
<input checked="" type="checkbox"/>	Parking Lots (>5,000 ft ²)	P ⁽⁶⁾	P ⁽⁷⁾	P ⁽¹⁾	P ⁽¹⁾	P ⁽⁴⁾	P	P	P	N	N
<input checked="" type="checkbox"/>	Streets, Highways, and Freeways	P ⁽⁶⁾	P ⁽⁷⁾	P ⁽¹⁾	P ⁽¹⁾	P ⁽⁴⁾	P	P	P	N	N
<input type="checkbox"/>	Retail Gasoline Outlets	N	P ⁽⁷⁾	N	N	P ⁽⁴⁾	N	P	P	N	N
Project Priority Pollutant(s) of Concern		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

P = Potential

N = Not Potential

⁽¹⁾ A potential Pollutant if non-native landscaping exists or is proposed onsite; otherwise not expected

⁽²⁾ A potential Pollutant if the project includes uncovered parking areas; otherwise not expected

⁽³⁾ A potential Pollutant is land use involving animal waste products; otherwise not expected

⁽⁴⁾ Including petroleum hydrocarbons

⁽⁵⁾ Including solvents

⁽⁶⁾ Bacterial indicators are routinely detected in pavement runoff

⁽⁷⁾ A potential source of metals, primarily copper and zinc. Iron, magnesium, and aluminum are commonly found in the environment and are commonly associated with soils, but are not primarily of anthropogenic stormwater origin in the municipal environment.

F.2 Treatment Control BMP Selection

Treatment Control BMPs typically provide proprietary treatment mechanisms to treat potential Pollutants in runoff, but do not sustain significant biological processes. Treatment Control BMPs must be selected to address the Project Priority Pollutants of Concern (identified above) and meet the acceptance criteria described in Section 2.3.7 of the SMR WQMP. Documentation of acceptance criteria must be included in Appendix 6. In addition, ensure that proposed Treatment Control BMPs are properly identified on the WQMP Site Plan in Appendix 1.

Table F-3 Treatment Control BMP Selection

Selected Treatment Control BMP Name or ID ¹	Priority Pollutant(s) of Concern to Mitigate ²	Removal Efficiency Percentage ³
Basin A	Bacterial indicators, metals, nutrients, pesticides, toxic organic compounds, sediments, trash & debris, oil & grease.	Medium to high efficiency for all pollutants per Appendix D of the Riverside County Santa Margarita River Watershed Region Design Handbook for Low Impact Development Best Management Practices (Revised June 2018)
Basin B	Same as above	Same as above
Vegetated Swale E	Same as above	Same as above
Vegetated Swale F	Same as above	Same as above

¹ Treatment Control BMPs must not be constructed within Receiving Waters. In addition, a proposed Treatment Control BMP may be listed more than once if they possess more than one qualifying pollutant removal efficiency.

² Cross Reference Table E.1 above to populate this column.

³ As documented in a Copermittee Approved Study and provided in Appendix 6.

F.3 Sizing Criteria

Utilize Table F-4 below to appropriately size flow-through BMPs to the DCV, or Design Flow Rate, as applicable. Please reference Chapter 3.5.1 of the SMR WQMP for further information.

Table F-4 Treatment Control BMP Sizing

DMA Type/ID	DMA Area (square feet)	Post-Project Surface Type	Effective Impervious Fraction, I_f	DMA Runoff Factor	DMA Areas x Runoff Factor	Enter BMP Name / Identifier Here	
	[A]		[B]	[C]	[A] x [C]		
						Design Storm (in)	Design Flow Rate (cfs)

	$A_T = \Sigma[A]$			$\Sigma = [D]$	[E]	$[F] = \frac{[D] \times [E]}{[G]}$	

[B], [C] is obtained as described in Section 2.6.1.b from the SMR WQMP
 [E] either 0.2 inches or 2 times the 85th percentile hourly rainfall intensity
 [G] = 43,560,.

F.4 Hydrologic Performance Standard – Alternative Compliance Approach

Alternative compliance options are only available if the governing Copermittee has acknowledged the infeasibility of onsite Hydrologic Control BMPs and approved an alternative compliance approach. See Section 3.5 and 3.6 of the SMR WQMP.

Select the pursued alternative and describe the specifics of the alternative:

- Offsite Hydrologic Control Management within the same channel system

Insert narrative description here

- In-Stream Restoration Project

Insert narrative description here

For Offsite Hydrologic Control BMP Option

Each Hydrologic Control BMP must be designed to ensure that the flow duration curve of the post-development DMA will not exceed that of the pre-existing, naturally occurring, DMA by more than ten percent over a one-year period. Using SMRHM, the applicant shall demonstrate that the performance of each designed Hydrologic Control BMP is equivalent with the Hydrologic Performance Standard for onsite conditions. Complete Table F-5 below and identify, for each Hydrologic Control BMP, the equivalent DMA the Hydrologic Control BMP mitigates, that the SMRHM model passed, the total volume capacity of the BMP, the BMP footprint at top floor elevation, and the drawdown time of the BMP. SMRHM summary reports for the alternative approach should be documented in Appendix 7. Refer to the SMRHM Guidance Document for additional information on SMRHM. You can add rows to the table as needed.

Table F-5 Offsite Hydrologic Control BMP Sizing

BMP Name / Type	Equivalent DMA (ac)	SMRHM Passed	BMP Volume (ac-ft)	BMP Footprint (ac)	Drawdown time (hr)
N/A		<input type="checkbox"/>			
		<input type="checkbox"/>			
		<input type="checkbox"/>			
		<input type="checkbox"/>			

For Instream Restoration Option

Attach to Appendix 7 the technical report detailing the condition of the receiving channel subject to the proposed hydrologic and sediment regimes. Provide the full design plans for the in-stream restoration project that have been approved by the Copermittee. Utilize the San Diego Regional Water Quality Equivalency Guidance Document.

Section G: Implement Trash Capture BMPs

The Local Jurisdiction may require full trash capture BMPs to be installed as part of the project. Consult with the Local Jurisdiction to determine applicability.

Trash Capture BMPs may be applicable to Type 'D' DMAs, as defined in Section 2.3.4 of the SMR WQMP. Trash Capture BMPs are designed to treat Q_{TRASH} , the runoff flow rate generated during the 1-year 1-hour precipitation depth. Utilize Table G-1 to size Trash Capture BMP. Refer to Table G-2 to determine the Trash Capture Design Storm Intensity (E).

Table G-1 Sizing Trash Capture BMPs

DMA Type/ID	DMA Area (square feet)	Post-Project Surface Type	Effective Impervious Fraction, I_f	DMA Runoff Factor	DMA Areas x Runoff Factor	Enter BMP Name / Identifier Here	
	[A]		[B]	[C]	[A] x [C]		
N/A						Trash Capture Design Storm Intensity (in)	Trash Capture Design Flow Rate (cubic feet or cfs)
	$A_T = \Sigma[A]$				$\Sigma = [D]$	[E] = .47	$[F] = \frac{[D] \times [E]}{[G]} =$

[B], [C] is obtained as described in Section 2.6.1.b from the SMR WQMP
[G] = 43,560

Table G-2 Approximate precipitation depth/intensity values for calculation of the Trash Capture Design Storm

City	1-year 1-hour Precipitation Depth/Intensity (inches/hr)
Murrieta	0.47
Temecula	0.50
Wildomar	0.37

Use Table G-3 to summarize and document the selection and sizing of Trash Capture BMPs.

Table G-3 Trash Capture BMPs

BMP Name / ID	DMA No(s)	BMP Type / Description	Required Trash Capture Flowrate (cfs)	Provided Trash Capture Flowrate (cfs)

Section H: Source Control BMPs

Source Control BMPs include permanent, structural features that may be required in your Project plans, such as roofs over and berms around trash and recycling areas, and Operational BMPs, such as regular sweeping and “housekeeping,” that must be implemented by the site’s occupant or user. The Maximum Extent Practicable (MEP) standard typically requires both types of BMPs. In general, Operational Source Control BMPs cannot be substituted for a feasible and effective Structural Source Control BMP. Complete checklist below to determine applicable Source Control BMPs for your site.

Project-Specific WQMP Source Control BMP Checklist		
<p>All development projects must implement Source Control BMPs. Source Control BMPs are used to minimize pollutants that may discharge to the MS4. Refer to Chapter 3 (Section 3.8) of the SMR WQMP for additional information. Complete Steps 1 and 2 below to identify Source Control BMPs for the project site.</p>		
STEP 1: IDENTIFY POLLUTANT SOURCES		
<p>Review project site plans and identify the applicable pollutant sources. “Yes” indicates that the pollutant source is applicable to project site. “No” indicates that the pollutant source is not applicable to project site.</p>		
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Storm Drain Inlets	<input type="checkbox"/> Yes <input type="checkbox"/> No Outdoor storage areas	
<input type="checkbox"/> Yes <input type="checkbox"/> No Floor Drains	<input type="checkbox"/> Yes <input type="checkbox"/> No Material storage areas	
<input type="checkbox"/> Yes <input type="checkbox"/> No Sump Pumps	<input type="checkbox"/> Yes <input type="checkbox"/> No Fueling areas	
<input type="checkbox"/> Yes <input type="checkbox"/> No Pets Control/Herbicide Application	<input type="checkbox"/> Yes <input type="checkbox"/> No Loading Docks	
<input type="checkbox"/> Yes <input type="checkbox"/> No Food Service Areas	<input type="checkbox"/> Yes <input type="checkbox"/> No Fire Sprinkler Test/Maintenance water	
<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Trash Storage Areas	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Plazas, Sidewalks and Parking Lots	
<input type="checkbox"/> Yes <input type="checkbox"/> No Industrial Processes	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Pools, Spas, Fountains and other water features	
<input type="checkbox"/> Yes <input type="checkbox"/> No Vehicle and Equipment Cleaning and Maintenance/Repair Areas		
STEP 2: REQUIRED SOURCE CONTROL BMPs		
<p>List each Pollutant source identified above in column 1 and fill in the corresponding Structural Source Control BMPs and Operational Control BMPs by referring to the Stormwater Pollutant Sources/Source Control Checklist included in Appendix 8. The resulting list of structural and operational source control BMPs must be implemented as long as the associated sources are present on the project site. Add additional rows as needed.</p>		
Pollutant Source	Structural Source Control BMP	Operational Source Control BMP
Storm Drain Inlets	No Dumping Drains to River signage required (see City of Murrieta Requirements)	inspect signage once per year. Repair or replace if unreadable.
Trash Storage Areas	Insert text here	Insert text here
Plazas, Sidewalks and Parking Lots	Insert text here	Insert text here
Pool	Insert text here	Insert text here
Insert text here	Insert text here	Insert text here
Insert text here	Insert text here	Insert text here
Insert text here	Insert text here	Insert text here

Section I: Coordinate Submittal with Other Site Plans

Populate Table I-1 below to assist the plan checker in an expeditious review of your project. During construction and at completion, [Insert Jurisdiction] inspectors will verify the installation of BMPs against the approved plans. The first two columns will contain information that was prepared in previous steps, while the last column will be populated with the corresponding plan sheets. This table is to be completed with the submittal of your final Project-Specific WQMP.

Table I-1 Construction Plan Cross-reference

BMP No. or ID	BMP Identifier and Description	Corresponding Plan Sheet(s)
Basin A	Biofiltration Basin	Insert text here
Basin B	Biofiltration Basin	Insert text here
Vegetated Swale E	Bioretention Vegetated Swale	Insert text here
Vegetated Swale F	Bioretention Vegetated Swale	Insert text here
Insert text here	Insert text here	Insert text here

Note that the updated table — or Construction Plan WQMP Checklist — is only a reference tool to facilitate an easy comparison of the construction plans to your Project-Specific WQMP. The Copermitttee with jurisdiction over the Project site can advise you regarding the process required to propose changes to the approved Project-Specific WQMP.

Use Table I-2 to identify other applicable permits that may impact design of the site. If yes is answered to any of the items below, the Copermitttee may require proof of approval/coverage from those agencies as applicable including documentation of any associated requirements that may affect this Project-Specific WQMP.

Table I-2 Other Applicable Permits

Agency	Permit Required	
State Department of Fish and Game, 1602 Streambed Alteration Agreement	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N
State Water Resources Control Board, Clean Water Act Section 401 Water Quality Certification	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N
US Army Corps of Engineers, Clean Water Act Section 404 Permit	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N
US Fish and Wildlife, Endangered Species Act Section 7 Biological Opinion	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N
Statewide Construction General Permit Coverage	<input checked="" type="checkbox"/> Y	<input type="checkbox"/> N
Statewide Industrial General Permit Coverage	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N
Western Riverside MSHCP Consistency Approval (e.g., JPR, DBESP)	<input type="checkbox"/> Y	<input checked="" type="checkbox"/> N
Other (please list in the space below as required) TBD	<input checked="" type="checkbox"/> Y	<input type="checkbox"/> N

Section J: Operation, Maintenance and Funding

The Copermittee with jurisdiction over the Project site will periodically verify that BMPs on your Project are maintained and continue to operate as designed. To make this possible, the Copermittee will require that you include in Appendix 9 of this Project-Specific WQMP:

1. A means to finance and implement maintenance of BMPs in perpetuity, including replacement cost.
2. Acceptance of responsibility for maintenance from the time the BMPs are constructed until responsibility for operation and maintenance is legally transferred. A warranty covering a period following construction may also be required.
3. An outline of general maintenance requirements for the Stormwater BMPs you have selected.
4. Figures delineating and designating pervious and impervious areas, location, and type of Stormwater BMP, and tables of pervious and impervious areas served by each facility. Geo-locating the BMPs using a coordinate system of latitude and longitude is recommended to help facilitate a future statewide database system.
5. A separate list and location of self-retaining areas or areas addressed by LID Principles that do not require specialized Operations and Maintenance or inspections but will require typical landscape maintenance as noted in Chapter 5, in the SMR WQMP. Include a brief description of typical landscape maintenance for these areas.

The Copermittee with jurisdiction over the Project site will also require that you prepare and submit a detailed BMP Operation and Maintenance Plan that sets forth a maintenance schedule for each of the BMPs built on your site. An agreement assigning responsibility for maintenance and providing for inspections and certification may also be required.

Details of these requirements and instructions for preparing a BMP Operation and Maintenance Plan are in Chapter 5 of the SMR WQMP.

Maintenance Mechanism: Insert text here.

Will the proposed BMPs be maintained by a Homeowners' Association (HOA) or Property Owners Association (POA)?

Y N

Include your Operation and Maintenance Plan and Maintenance Mechanism in Appendix 9. Additionally, include all pertinent forms of educational materials for those personnel that will be maintaining the proposed BMPs within this Project-Specific WQMP in Appendix 10.

Section K: Acronyms, Abbreviations and Definitions

Regional MS4 Permit	Order No. R9-2013-0001 as amended by Order No. R9-2015-0001 and Order No. R9-2015-0100 an NPDES Permit issued by the San Diego Regional Water Quality Control Board.
Applicant	Public or private entity seeking the discretionary approval of new or replaced improvements from the Copermittee with jurisdiction over the project site. The Applicant has overall responsibility for the implementation and the approval of a Priority Development Project. The WQMP uses consistently the term “user” to refer to the applicant such as developer or project proponent. The WQMP employs also the designation “user” to identify the Registered Professional Civil Engineer responsible for submitting the Project-Specific WQMP, and designing the required BMPs.
Best Management Practice (BMP)	Defined in 40 CFR 122.2 as schedules of activities, prohibitions of practices, maintenance procedures, and other management practices to prevent or reduce the pollution of waters of the United States. BMPs also include treatment requirements, operating procedures and practices to control plant site runoff, spillage or leaks, sludge or waste disposal, or drainage from raw material storage. In the case of municipal storm water permits, BMPs are typically used in place of numeric effluent limits.
BMP Fact Sheets	BMP Fact Sheets are available in the LID BMP Design Handbook. Individual BMP Fact Sheets include siting considerations, and design and sizing guidelines for seven types of structural BMPs (infiltration basin, infiltration trench, permeable pavement, harvest-and-use, bioretention, extended detention basin, and sand filter).
California Stormwater Quality Association (CASQA)	Publisher of the California Stormwater Best Management Practices Handbooks, available at www.cabmphandbooks.com .
Conventional Treatment Control BMP	A type of BMP that provides treatment of stormwater runoff. Conventional treatment control BMPs, while designed to treat particular Pollutants, typically do not provide the same level of volume reduction as LID BMPs, and commonly require more specialized maintenance than LID BMPs. As such, the Regional MS4 Permit and this WQMP require the use of LID BMPs wherever feasible, before Conventional Treatment BMPs can be considered or implemented.
Copermittees	The Regional MS4 Permit identifies the Cities of Murrieta, Temecula, and Wildomar, the County, and the District, as Copermittees for the SMR.

County	The abbreviation refers to the County of Riverside in this document.
CEQA	California Environmental Quality Act - a statute that requires state and local agencies to identify the significant environmental impacts of their actions and to avoid or mitigate those impacts, if feasible.
CIMIS	California Irrigation Management Information System - an integrated network of 118 automated active weather stations all over California managed by the California Department of Water Resources.
CWA	Clean Water Act - is the primary federal law governing water pollution. Passed in 1972, the CWA established the goals of eliminating releases of high amounts of toxic substances into water, eliminating additional water pollution by 1985, and ensuring that surface waters would meet standards necessary for human sports and recreation by 1983. CWA Section 402(p) is the federal statute requiring NPDES permits for discharges from MS4s.
CWA Section 303(d) Waterbody	Impaired water in which water quality does not meet applicable water quality standards and/or is not expected to meet water quality standards, even after the application of technology based pollution controls required by the CWA. The discharge of urban runoff to these water bodies by the Copermittees is significant because these discharges can cause or contribute to violations of applicable water quality standards.
Design Storm	The Regional MS4 Permit has established the 85th percentile, 24-hour storm event as the "Design Storm". The applicant may refer to Exhibit A to identify the applicable Design Storm Depth (D85) to the project.
DCV	Design Capture Volume (DCV) is the volume of runoff produced from the Design Storm to be mitigated through LID Retention BMPs, Other LID BMPs and Volume Based Conventional Treatment BMPs, as appropriate.
Design Flow Rate	The design flow rate represents the minimum flow rate capacity that flow-based conventional treatment control BMPs should treat to the MEP, when considered.
DCIA	Directly Connected Impervious Areas - those impervious areas that are hydraulically connected to the MS4 (i.e. street curbs, catch basins, storm drains, etc.) and thence to the structural BMP without flowing over pervious areas.
Discretionary Approval	A decision in which a Copermittee uses its judgment in deciding whether and how to carry out or approve a project.
District	Riverside County Flood Control and Water Conservation District.

DMA	A Drainage Management Area - a delineated portion of a project site that is hydraulically connected to a common structural BMP or conveyance point. The Applicant may refer to Section 3.3 for further guidelines on how to delineate DMAs.
Drawdown Time	Refers to the amount of time the design volume takes to pass through the BMP. The specified or incorporated drawdown times are to ensure that adequate contact or detention time has occurred for treatment, while not creating vector or other nuisance issues. It is important to abide by the drawdown time requirements stated in the fact sheet for each specific BMP.
Effective Area	Area which 1) is suitable for a BMP (for example, if infiltration is potentially feasible for the site based on infeasibility criteria, infiltration must be allowed over this area) and 2) receives runoff from impervious areas.
ESA	An Environmental Sensitive Area (ESA) designates an area "in which plants or animals life or their habitats are either rare or especially valuable because of their special nature or role in an ecosystem and which would be easily disturbed or degraded by human activities and developments". (Reference: California Public Resources Code § 30107.5).
ET	Evapotranspiration (ET) is the loss of water to the atmosphere by the combined processes of evaporation (from soil and plant surfaces) and transpiration (from plant tissues). It is also an indicator of how much water crops, lawn, garden, and trees need for healthy growth and productivity
FAR	The Floor Area Ratio (FAR) is the total square feet of a building divided by the total square feet of the lot the building is located on.
Flow-Based BMP	Flow-based BMPs are conventional treatment control BMPs that are sized to treat the design flow rate.
FPPP	Facility Pollution Prevention Plan
HCOC	Hydrologic Condition of Concern - Exists when the alteration of a site's hydrologic regime caused by development would cause significant impacts on downstream channels and aquatic habitats, alone or in conjunction with impacts of other projects.
HMP	Hydromodification Management Plan – Plan defining Performance Standards for PDPs to manage increases in runoff discharge rates and durations.
Hydrologic Control BMP	BMP to mitigate the increases in runoff discharge rates and durations and meet the Performance Standards set forth in the HMP.
HSG	Hydrologic Soil Groups – soil classification to indicate the minimum rate of infiltration obtained for bare soil after prolonged wetting. The HSGs are A (very low runoff potential/high infiltration rate), B, C, and D (high runoff potential/very low infiltration rate)

Hydromodification	The Regional MS4 Permit identifies that increased volume, velocity, frequency and discharge duration of storm water runoff from developed areas has the potential to greatly accelerate downstream erosion, impair stream habitat in natural drainages, and negatively impact beneficial uses.
JRMP	A separate Jurisdictional Runoff Management Plan (JRMP) has been developed by each Copermittee and identifies the local programs and activities that the Copermittee is implementing to meet the Regional MS4 Permit requirements.
LID	Low Impact Development (LID) is a site design strategy with a goal of maintaining or replicating the pre-development hydrologic regime through the use of design techniques. LID site design BMPs help preserve and restore the natural hydrologic cycle of the site, allowing for filtration and infiltration which can greatly reduce the volume, peak flow rate, velocity, and pollutant loads of storm water runoff.
LID BMP	A type of stormwater BMP that is based upon Low Impact Development concepts. LID BMPs not only provide highly effective treatment of stormwater runoff, but also yield potentially significant reductions in runoff volume – helping to mimic the pre-project hydrologic regime, and also require less ongoing maintenance than Treatment Control BMPs. The applicant may refer to Chapter 2.
LID BMP Design Handbook	The LID BMP Design Handbook was developed by the Copermittees to provide guidance for the planning, design and maintenance of LID BMPs which may be used to mitigate the water quality impacts of PDPs within the County.
LID Bioretention BMP	LID Bioretention BMPs are bioretention areas are vegetated (i.e., landscaped) shallow depressions that provide storage, infiltration, and evapotranspiration, and provide for pollutant removal (e.g., filtration, adsorption, nutrient uptake) by filtering stormwater through the vegetation and soils. In bioretention areas, pore spaces and organic material in the soils help to retain water in the form of soil moisture and to promote the adsorption of pollutants (e.g., dissolved metals and petroleum hydrocarbons) into the soil matrix. Plants use soil moisture and promote the drying of the soil through transpiration. The Regional MS4 Permit defines “retain” as to keep or hold in a particular place, condition, or position without discharge to surface waters.
LID Biofiltration BMP	BMPs that reduce stormwater pollutant discharges by intercepting rainfall on vegetative canopy, and through incidental infiltration and/or evapotranspiration, and filtration, and other biological and chemical processes. As stormwater passes down through the planting soil, pollutants are filtered, adsorbed, biodegraded, and sequestered by the soil and plants, and collected through an underdrain.

LID Harvest and Reuse BMP	BMPs used to facilitate capturing Stormwater Runoff for later use without negatively impacting downstream water rights or other Beneficial Uses.
LID Infiltration BMP	BMPs to reduce stormwater runoff by capturing and infiltrating the runoff into in-situ soils or amended onsite soils. Typical LID Infiltration BMPs include infiltration basins, infiltration trenches and pervious pavements.
LID Retention BMP	BMPs to ensure full onsite retention without runoff of the DCV such as infiltration basins, bioretention, chambers, trenches, permeable pavement and pavers, harvest and reuse.
LID Principles	Site design concepts that prevent or minimize the causes (or drivers) of post-construction impacts, and help mimic the pre-development hydrologic regime.
MEP	Maximum Extent Practicable - standard established by the 1987 amendments to the CWA for the reduction of Pollutant discharges from MS4s. Refer to Attachment C of the Regional MS4 Permit for a complete definition of MEP.
MF	Multi-family – zoning classification for parcels having 2 or more living residential units.
MS4	Municipal Separate Storm Sewer System (MS4) is a conveyance or system of conveyances (including roads with drainage systems, municipal streets, catch basins, curbs, gutters, ditches, man-made channels, or storm drains): (i) Owned or operated by a State, city, town, borough, county, parish, district, association, or other public body (created by or pursuant to State law) having jurisdiction over disposal of sewage, industrial wastes, storm water, or other wastes, including special districts under State law such as a sewer district, flood control district or drainage district, or similar entity, or an Indian tribe or an authorized Indian tribal organization, or designated and approved management agency under section 208 of the CWA that discharges to waters of the United States; (ii) Designated or used for collecting or conveying storm water; (iii) Which is not a combined sewer; (iv) Which is not part of the Publicly Owned Treatment Works (POTW) as defined at 40 CFR 122.26.
New Development Project	Defined by the Regional MS4 Permit as 'Priority Development Projects' if the project, or a component of the project meets the categories and thresholds described in Section 1.1.1.
NPDES	National Pollution Discharge Elimination System - Federal program for issuing, modifying, revoking and reissuing, terminating, monitoring and enforcing permits, and imposing and enforcing pretreatment requirements, under Sections 307, 318, 402, and 405 of the CWA.
NRCS	Natural Resources Conservation Service

PDP	Priority Development Project - Includes New Development and Redevelopment project categories listed in Provision E.3.b of the Regional MS4 Permit.
Priority Pollutants of Concern	Pollutants expected to be present on the project site and for which a downstream water body is also listed as Impaired under the CWA Section 303(d) list or by a TMDL.
Project-Specific WQMP	A plan specifying and documenting permanent LID Principles and Stormwater BMPs to control post-construction Pollutants and stormwater runoff for the life of the PDP, and the plans for operation and maintenance of those BMPs for the life of the project.
Receiving Waters	Waters of the United States.
Redevelopment Project	The creation, addition, and or replacement of impervious surface on an already developed site. Examples include the expansion of a building footprint, road widening, the addition to or replacement of a structure, and creation or addition of impervious surfaces. Replacement of impervious surfaces includes any activity that is not part of a routine maintenance activity where impervious material(s) are removed, exposing underlying soil during construction. Redevelopment does not include trenching and resurfacing associated with utility work; resurfacing existing roadways; new sidewalk construction, pedestrian ramps, or bike lane on existing roads; and routine replacement of damaged pavement, such as pothole repair. Project that meets the criteria described in Section 1.
Runoff Fund	Runoff Funds have not been established by the Copermittees and are not available to the Applicant. If established, a Runoff Fund will develop regional mitigation projects where PDPs will be able to buy mitigation credits if it is determined that implementing onsite controls is infeasible.
San Diego Regional Board	San Diego Regional Water Quality Control Board - The term "Regional Board", as defined in Water Code section 13050(b), is intended to refer to the California Regional Water Quality Control Board for the San Diego Region as specified in Water Code Section 13200. State agency responsible for managing and regulating water quality in the SMR.
SCCWRP	Southern California Coastal Water Research Project
Site Design BMP	Site design BMPs prevent or minimize the causes (or drivers) of post-construction impacts, and help mimic the pre-development hydrologic regime.
SF	Parcels with a zoning classification for a single residential unit.
SMC	Southern California Stormwater Monitoring Coalition
SMR	The Santa Margarita Region (SMR) represents the portion of the Santa Margarita Watershed that is included within the County of Riverside.

Source Control BMP	Source Control BMPs land use or site planning practices, or structural or nonstructural measures that aim to prevent runoff pollution by reducing the potential for contamination at the source of pollution. Source control BMPs minimize the contact between Pollutants and runoff.
Structural BMP	Structures designed to remove pollutants from stormwater runoff and mitigate hydromodification impacts.
SWPPP	Storm Water Pollution Prevention Plan
Tentative Tract Map	Tentative Tract Maps are required for all subdivision creating five (5) or more parcels, five (5) or more condominiums as defined in Section 783 of the California Civil Code, a community apartment project containing five (5) or more parcels, or for the conversion of a dwelling to a stock cooperative containing five (5) or more dwelling units.
TMDL	Total Maximum Daily Load - the maximum amount of a Pollutant that can be discharged into a waterbody from all sources (point and non-point) and still maintain Water Quality Standards. Under CWA Section 303(d), TMDLs must be developed for all waterbodies that do not meet Water Quality Standards after application of technology-based controls.
USEPA	United States Environmental Protection Agency
Volume-Based BMP	Volume-Based BMPs applies to BMPs where the primary mode of pollutant removal depends upon the volumetric capacity such as detention, retention, and infiltration systems.
WQMP	Water Quality Management Plan
Wet Season	The Regional MS4 Permit defines the wet season from October 1 through April 30.

Appendix 1: Maps and Site Plans


Location Map, WQMP Site Plan and Receiving Waters Map

Complete the checklist below to verify all exhibits and components are included in the Project-Specific WQMP. Refer Section 4 of the SMR WQMP and Section D of this Template.

Map and Site Plan Checklist	
Indicate all Maps and Site Plans are included in your Project-Specific WQMP by checking the boxes below.	
<input checked="" type="checkbox"/>	Vicinity and Location Map
<input type="checkbox"/>	Existing Site Map (unless exiting conditions are included in WQMP Site Plan)
<input checked="" type="checkbox"/>	WQMP Site Plan
<input checked="" type="checkbox"/>	Parcel Boundary and Project Footprint
<input checked="" type="checkbox"/>	Existing and Proposed Topography
<input checked="" type="checkbox"/>	Drainage Management Areas (DMAs)
<input checked="" type="checkbox"/>	Proposed Structural Best Management Practices (BMPs)
<input checked="" type="checkbox"/>	Drainage Paths
<input checked="" type="checkbox"/>	Drainage infrastructure, inlets, overflows
<input type="checkbox"/>	Source Control BMPs
<input type="checkbox"/>	Site Design BMPs
<input type="checkbox"/>	Buildings, Roof Lines, Downspouts
<input checked="" type="checkbox"/>	Impervious Surfaces
<input type="checkbox"/>	Pervious Surfaces (i.e. Landscaping)
<input checked="" type="checkbox"/>	Standard Labeling


MURRIETA WHITEWOOD
DEVELOPED CONDITION WQMP EXHIBIT

11/8/21




*BASIN 1: X=2.5', BASIN 2 X=1.5'

**GRAVEL AND UNDERDRAINS TO EXTEND TO THE MID-PONDING DEPTH PER THE RIVERSIDE COUNTY SANTA MARGARITA WATERSHED REGION DESIGN HANDBOOK FOR L.I.D. B.M.P.s (BMP CALC. WORKSHEET 3.5 BIOFIL. WITH PARTIAL INFIL.)



EARTHEN BIOFILTRATION AND DETENTION BASIN



- LEGEND:**
- PROPERTY LINE
 - - - SUBAREA
 - - - FLOWPATH
 - PROPOSED STORM DRAIN
 - PROPOSED LOWFLOW DRAIN
 - EXISTING HIGH FLOW CATCH BASIN
 - PROPOSED LOW FLOW (WOT) CATCH BASIN
 - BIOFILTRATION & DETENTION BASIN
 - BIORETENTION VEGETATED SWALE (FT WIDE MIN)
 - RIPRAP PAD (5' X 10' MIN)

Facility	Volume Required cf	Volume Provided cf
Above Ground BASIN A	13,187	15,386
Above Ground BASIN B	6,950	14,100
Bioretention Vegetated Swale E	960	1092
Bioretention Vegetated Swale F	725	816

Appendix 2: Construction Plans

The latest set of Grading, Drainage and Street Improvement Plans shall be included.

For Bioretention and Biofiltration facilities, the following construction notes shall be shown on the Grading and/or Drainage plans.

- 1) BSM and Aggregates should not be delivered or placed in frozen, wet or muddy conditions. The Contractor should protect materials from absorbing excess water and from erosion at all times. The Contractor shall not store materials unprotected during large rainfall events (>.25 inches). If water is introduced into material while it is stockpiled, the Contractor shall allow the material to drain to an acceptable level before it is placed.
- 2) The Engineer shall furnish to the City a copy of the source testing and a signed certification that the fully blended Bioretention/Biofiltration Soil Media (BSM) material meets all of the WQMP requirements before the material is imported or if the material is mixed onsite prior to installation. Onsite mixing may only occur if sand or topsoil components are sourced from the Project site. Onsite mixing may be conducted by using loaders.
- 3) BSM shall be lightly compacted and placed in loose lifts of 12 inches thick. Compaction should not exceed 75% standard procter. Machinery should not be used in the BSM area to place BSM. As BSM material is being installed, Quality Assurance (QA) tests shall be conducted or for every 1,200 tons or 800 cubic yards mixed on-site from a completely mixed stockpile or windrow, with a minimum of three tests. For imported material from a supplier with a quality control program the QA tests shall be conducted 2,400 tons or 1,600 cubic yards from the supplier.
- 4) The Engineer conducting the Quality Control testing shall furnish to the City a copy of the QA testing and a certification that the BSM for the project meets all of the following requirements.
 - a. BSM shall consist of 60-80% clean sand, up to 20% clean topsoil, and 20% of a nutrient-stabilized organic amendment. The initial infiltration rate shall be greater than 8 inches per hour per laboratory test.
 - b. pH: 6.0 – 8.5; Salinity: 0.5 to 3.0 mmho/cm as electrical conductivity; sodium absorption ratio: < 6.0; Chloride: <800 ppm in saturated extract; Cation Exchange Capacity (CEC): > 10 meq/100 g; Organic Matter: 2 to 5 percent on a dry weight basis; Carbon: Nitrogen ratio: 12 to 40, preferably 15 to 40; Gravel larger than 2mm: 0 to 25-percent of the total sample; Clay smaller than 0.005 mm: 0 to 5 percent of the non-gravel fraction.
 - c. BSM shall be tested to limit the leaching of potential inherent pollutants. BSM used in Biofiltration BMPs shall conform to the following limits for pollutant concentrations in saturated extract: Phosphorous: < 1 mg/L; Nitrate < 3 mg/L, Copper <0.025 mg/L. These pollutant limits are for the amount that is leached from the sample, not from the soil sample itself. Testing may be performed after laboratory rinsing of media with up to 15 pore volumes of water. Equivalent test results will be accepted if certified by a laboratory or appropriate testing facility.

- d. Low nutrient compost used in BSM shall be sourced from a facility permitted through CalRecycle, preferably through USCC STA program. Compost shall conform to the following requirements: Physical contaminants <1% by dry weight; Carbon:Nitrogen ratio: 12:1 to 40:1, Maturity/Stability shall conform to either: Solvita Maturity Index: \geq 5.5, CO₂ Evolution: < 2.5 mg CO₂-C per g compost organic matter per day, or < 5 mg CO₂ – shall be more than 6 months old and representative of current stockpiles.
- e. Coconut coir pith used in BSM shall be thoroughly rinsed with freshwater and screened to remove coarse fibers as part of production and aged > 6 months. Peat used in BSM shall be sphagnum peat.

Potential BSM sources may include (not part of construction note): Gail Materials (Temescal Valley), Agriservice (Oceanside), Greatsoils (Escondido), and Earthworks (Riverside).

Potential Laboratories may include (not part of construction note): Fruit Growers Laboratory, Inc. (Santa Paula, <http://www.fglinc.com/>), Wallace Laboratories (El Segundo, <http://us.wlabs.com/>), Control Labs (Watsonville, <http://controllabs.com>) and A&L Western Laboratories (Modesto, <http://www.al-labs-west.com/>)

Appendix 3: Soils Information

Geotechnical Study, Other Infiltration Testing Data, and/or Other Documentation

Appendix 4: Historical Site Conditions

Phase I Environmental Site Assessment or Other Information on Past Site Use

Appendix 5: LID Feasibility Supplemental Information

Information that supports or supplements the determination of LID technical feasibility documented in Section D

Appendix 6: LID BMP Design Details

BMP Sizing, Design Details and other Supporting Documentation to supplement Section D

Santa Margarita Watershed

BMP Design Volume, V_{BMP} (Rev. 03-2012)

Legend:

Required Entries

Calculated Cells

(Note this worksheet shall **only** be used in conjunction with BMP designs from the **LID BMP Design Handbook**)

Company Name	Alliance Land Planning and Engineering	Date	8/10/2021
Designed by	SRL	County/City Case No	
Company Project Number/Name			
Drainage Area Number/Name	BASIN A NORTH		

Enter the Area Tributary to this Feature $A_T = 2.43$ acres

85th Percentile, 24-hour Rainfall Depth, from the Isohyetal Map in Handbook Appendix E

Site Location	Township	Murrieta
	Range	
	Section	
Enter the 85 th Percentile, 24-hour Rainfall Depth	$D_{85} =$	0.60

Determine the Effective Impervious Fraction

Type of post-development surface cover (use pull down menu)	Mixed Surface Types
Effective Impervious Fraction	$I_f = 0.87$

Calculate the composite Runoff Coefficient, C for the BMP Tributary Area

Use the following equation based on the WEF/ASCE Method

$$C = 0.858I_f^3 - 0.78I_f^2 + 0.774I_f + 0.04$$

$C = 0.69$

Determine Design Storage Volume, V_{BMP}

Calculate V_U , the 85% Unit Storage Volume $V_U = D_{85} \times C$	$V_u = 0.41$ (in*ac)/ac
Calculate the design storage volume of the BMP, V_{BMP} .	
$V_{BMP} (ft^3) = \frac{V_U (in\text{-}ac/ac) \times A_T (ac) \times 43,560 (ft^2/ac)}{12 (in/ft)}$	$V_{BMP} = 3,617 ft^3$

Notes:

Santa Margarita Watershed

BMP Design Volume, V_{BMP} (Rev. 03-2012)

Legend:

Required Entries

Calculated Cells

(Note this worksheet shall **only** be used in conjunction with BMP designs from the **LID BMP Design Handbook**)

Company Name	Alliance Land Planning and Engineeri	Date	8/10/2021
Designed by	SRL	County/City Case No	
Company Project Number/Name			
Drainage Area Number/Name	BASIN A SOUTH		

Enter the Area Tributary to this Feature $A_T = 6.43$ acres

85th Percentile, 24-hour Rainfall Depth, from the Isohyetal Map in Handbook Appendix E

Site Location	Township	Murrieta
	Range	
	Section	
Enter the 85 th Percentile, 24-hour Rainfall Depth	$D_{85} =$	0.60

Determine the Effective Impervious Fraction

Type of post-development surface cover (use pull down menu)	Mixed Surface Types
Effective Impervious Fraction	$I_f = 0.87$

Calculate the composite Runoff Coefficient, C for the BMP Tributary Area

Use the following equation based on the WEF/ASCE Method

$$C = 0.858I_f^3 - 0.78I_f^2 + 0.774I_f + 0.04$$

$C = 0.69$

Determine Design Storage Volume, V_{BMP}

Calculate V_U , the 85% Unit Storage Volume $V_U = D_{85} \times C$	$V_u = 0.41$ (in*ac)/ac
Calculate the design storage volume of the BMP, V_{BMP} .	
$V_{BMP} (ft^3) = \frac{V_U (in\text{-}ac/ac) \times A_T (ac) \times 43,560 (ft^2/ac)}{12 (in/ft)}$	$V_{BMP} = 9,570 ft^3$

Notes:

Santa Margarita Watershed

BMP Design Volume, V_{BMP} (Rev. 03-2012)

Legend:

Required Entries

Calculated Cells

(Note this worksheet shall **only** be used in conjunction with BMP designs from the **LID BMP Design Handbook**)

Company Name	Alliance Land Planning and Engineeri	Date	8/10/2021
Designed by	SRL	County/City Case No	
Company Project Number/Name			
Drainage Area Number/Name	BASIN B		

Enter the Area Tributary to this Feature $A_T = 4.67$ acres

85th Percentile, 24-hour Rainfall Depth, from the Isohyetal Map in Handbook Appendix E

Site Location	Township	Murrieta
	Range	
	Section	
Enter the 85 th Percentile, 24-hour Rainfall Depth	$D_{85} =$	0.60

Determine the Effective Impervious Fraction

Type of post-development surface cover (use pull down menu)	Mixed Surface Types
Effective Impervious Fraction	$I_f = 0.87$

Calculate the composite Runoff Coefficient, C for the BMP Tributary Area

Use the following equation based on the WEF/ASCE Method

$$C = 0.858I_f^3 - 0.78I_f^2 + 0.774I_f + 0.04$$

$C = 0.69$

Determine Design Storage Volume, V_{BMP}

Calculate V_U , the 85% Unit Storage Volume $V_U = D_{85} \times C$	$V_u = 0.41$ (in*ac)/ac
Calculate the design storage volume of the BMP, V_{BMP} .	
$V_{BMP} (ft^3) = \frac{V_U (in\text{-}ac/ac) \times A_T (ac) \times 43,560 (ft^2/ac)}{12 (in/ft)}$	$V_{BMP} = 6,950 ft^3$

Notes:

Santa Margarita Watershed

BMP Design Flow Rate, Q_{BMP} (Rev. 03-2012)

Legend:

Required Entries

Calculated Cells

Company Name Alliance Land Planning and Date _____

Designed by SRL County/City Case No _____

Company Project Number/Name WHITEWOOD APARTMENTS

Drainage Area Number/Name BASIN E

Enter the Area Tributary to this Feature $A_T =$ 0.49 acres

Determine the Effective Impervious Fraction

Type of post-development surface cover
(use pull down menu)

Concrete or Asphalt

Effective Impervious Fraction

$I_f =$ 1.00

Calculate the composite Runoff Coefficient, C for the BMP Tributary Area

Use the following equation based on the WEF/ASCE Method

$$C = 0.858I_f^3 - 0.78I_f^2 + 0.774I_f + 0.04$$

$C =$ 0.89

BMP Design Flow Rate

$$Q_{BMP} = C \times I \times A_T$$

$Q_{BMP} =$ 0.1 ft^3/s

Notes:

Santa Margarita Watershed

BMP Design Flow Rate, Q_{BMP} (Rev. 03-2012)

Legend:

Required Entries

Calculated Cells

Company Name Alliance Land Planning and Date

Designed by SRL County/City Case No

Company Project Number/Name WHITEWOOD APARTMENTS

Drainage Area Number/Name BASIN F

Enter the Area Tributary to this Feature $A_T =$ 0.37 acres

Determine the Effective Impervious Fraction

Type of post-development surface cover
(use pull down menu)

Concrete or Asphalt

Effective Impervious Fraction

$I_f =$ 1.00

Calculate the composite Runoff Coefficient, C for the BMP Tributary Area

Use the following equation based on the WEF/ASCE Method

$$C = 0.858I_f^3 - 0.78I_f^2 + 0.774I_f + 0.04$$

$C =$ 0.89

BMP Design Flow Rate

$$Q_{BMP} = C \times I \times A_T$$

$Q_{BMP} =$ 0.1 ft³/s

Notes:

Biofiltration with Partial Infiltration Facility - Design Procedure	BMP ID BASIN A	Legend:	Required Entries
			Calculated Cells

Company Name:	Alliance Land Planning and Engineering, Inc.	Date:	#####
Designed by:		County/City Case No.:	

Design Volume

Enter the area tributary to this feature $A_T =$ 8.86 acres

Enter V_{BMP} determined from Section 2.1 of this Handbook $V_{BMP} =$ 13,187 ft³

Enter initial estimate of footprint of BMP, $Area_{BMP}$ (Guidance: A reasonable starting point is 3% of the tributary impervious area) $Area_{BMP} =$ 6,383 ft²

Note: This area shall be measured at the mid-ponding depth of the BMP. For systems with side-slopes, this should be the contour that is midway between the floor of the basin and the maximum water quality ponding elevation of the basin. The underlying gravel layer (infiltration storage layer) should extend to this contour. For systems with vertical walls, the effective area is the full footprint.

Portion of DCV Reliably Retained

Depth of Gravel Infiltration Storage Layer (18" minimum; 30" maximum) $d_g =$ 18.0 inches

Portion of V_{BMP} Reliably Retained via Infiltration Storage in Gravel Layer
 $V_{retained} = d_g \text{ (in)} \times 0.4 \times Area_{BMP} \text{ (ft}^2\text{)} \times 1/12$ $V_{Retained} =$ 3829.8 ft³

Portion of V_{BMP} not Reliably Retained
 $V_{Not\ Reliably\ Retained} = V_{BMP} - V_{Retained}$ $V_{Not\ Reliably\ Retained} =$ 9357.2 ft³

Biofiltration with Partial Retention Facility Surface Area

Depth of Surface Ponding Layer (6" minimum, 12" maximum) $d_p =$ 18.0 inches

Depth of Engineered Soil Media (24" to 36"; 18" if vertically constrained) $d_s =$ 24.0 inches

Design Media Filtration Rate (2.5 in/hr) $I_{design} =$ 2.5 in/hr

Allowable Routing Period, $T_{routing}$ (5 hrs) $T_{routing} =$ 5.0 hr

Effective Biofiltration Depth, d_{E_bio}
 $d_{E_bio} \text{ (ft)} = (d_p + (0.3 \times d_s) + (I_{design} \times T_{routing})) \text{ (ft)}$ $d_{E_bio} =$ 3.1 ft

Effective Static Depth, $d_{E_bio_static}$
 $d_{E_bio_static} = (d_p + (0.3 \times d_s)) \text{ (ft)}$ $d_{E_bio_static} =$ 2.1 ft

$V_{biofiltered} = d_{E_bio} \times Area_{BMP}$ $V_{biofiltered} =$ 20053.3 ft³

$V_{biofiltered_static} = d_{E_bio_static} \times Area_{BMP}$ $V_{biofiltered_static} =$ 13404.3 ft³

Sizing Option 1 Result

Criteria 1: $V_{\text{biofiltered (with routing)}} > 150\%$ of $V_{\text{not reliably retained}}$

Results: **PASS**

Sizing Option 2 Result

Criteria 2: $V_{\text{biofiltered_static}} > 0.75 \times V_{\text{Not Reliably Retained}}$

Results: **PASS**

Note

If neither of these criteria are met, then increase retention depth, increase footprint, or both, and rerun calculations. This calculation is inherently iterative.

Biofiltration with Partial Retention Facility Properties

Side Slopes in Partial Retention with Biofiltration Facility $z =$:1

Message: ERROR, side slopes too steep for Facility design

Diameter of Underdrain inches

Longitudinal Slope of Site (3% maximum) %

Check Dam Spacing feet

Describe Vegetation:

Notes:

Biofiltration with Partial Infiltration Facility - Design Procedure	BMP ID BASIN B	Legend:	Required Entries
			Calculated Cells

Company Name:	Alliance Land Planning and Engineering, Inc.	Date:	
Designed by:	SRL	County/City Case No.:	

Design Volume

Enter the area tributary to this feature $A_T =$ 4.67 acres

Enter V_{BMP} determined from Section 2.1 of this Handbook $V_{BMP} =$ 6,950 ft³

Enter initial estimate of footprint of BMP, $Area_{BMP}$ (Guidance: A reasonable starting point is 3% of the tributary impervious area) $Area_{BMP} =$ 5,879 ft²

Note: This area shall be measured at the mid-ponding depth of the BMP. For systems with side-slopes, this should be the contour that is midway between the floor of the basin and the maximum water quality ponding elevation of the basin. The underlying gravel layer (infiltration storage layer) should extend to this contour. For systems with vertical walls, the effective area is the full footprint.

Portion of DCV Reliably Retained

Depth of Gravel Infiltration Storage Layer (18" minimum; 30" maximum) $d_g =$ 18.0 inches

Portion of V_{BMP} Reliably Retained via Infiltration Storage in Gravel Layer
 $V_{retained} = d_g \text{ (in)} \times 0.4 \times Area_{BMP} \text{ (ft}^2\text{)} \times 1/12$ $V_{Retained} =$ 3527.4 ft³

Portion of V_{BMP} not Reliably Retained
 $V_{Not\ Reliably\ Retained} = V_{BMP} - V_{Retained}$ $V_{Not\ Reliably\ Retained} =$ 3422.6 ft³

Biofiltration with Partial Retention Facility Surface Area

Depth of Surface Ponding Layer (6" minimum, 12" maximum) $d_p =$ 18.0 inches

Depth of Engineered Soil Media (24" to 36"; 18" if vertically constrained) $d_s =$ 24.0 inches

Design Media Filtration Rate (2.5 in/hr) $I_{design} =$ 2.5 in/hr

Allowable Routing Period, $T_{routing}$ (5 hrs) $T_{routing} =$ 5.0 hr

Effective Biofiltration Depth, d_{E_bio}
 $d_{E_bio} \text{ (ft)} = (d_p + (0.3 \times d_s) + (I_{design} \times T_{routing})) \text{ (ft)}$ $d_{E_bio} =$ 3.1 ft

Effective Static Depth, $d_{E_bio_static}$
 $d_{E_bio_static} = (d_p + (0.3 \times d_s)) \text{ (ft)}$ $d_{E_bio_static} =$ 2.1 ft

$V_{biofiltered} = d_{E_bio} \times Area_{BMP}$ $V_{biofiltered} =$ 18469.9 ft³

$V_{biofiltered_static} = d_{E_bio_static} \times Area_{BMP}$ $V_{biofiltered_static} =$ 12345.9 ft³

Sizing Option 1 Result

Criteria 1: $V_{\text{biofiltered (with routing)}} > 150\% \text{ of } V_{\text{not reliably retained}}$

Results: **PASS**

Sizing Option 2 Result

Criteria 2: $V_{\text{biofiltered_static}} > 0.75 \times V_{\text{Not Reliably Retained}}$

Results: **PASS**

Note

If neither of these criteria are met, then increase retention depth, increase footprint, or both, and rerun calculations. This calculation is inherently iterative.

Biofiltration with Partial Retention Facility Properties

Side Slopes in Partial Retention with Biofiltration Facility

$z =$ $:1$

Message: ERROR, side slopes too steep for Facility design

Diameter of Underdrain

inches

Longitudinal Slope of Site (3% maximum)

%

Check Dam Spacing

feet

Describe Vegetation:

Notes:

Bioretention Facility - Design Procedure		BMP ID SWALE E	Legend:	Required Entries
				Calculated Cells
Company Name:	ALLIANCE		Date:	
Designed by:	SRL		County/City Case No.:	
Design Volume				
Enter the area tributary to this feature			$A_T =$	0.49 acres
Enter V_{BMP} determined from Section 2.1 of this Handbook			$V_{BMP} =$	960 ft ³
Type of Bioretention Facility Design				
<input checked="" type="radio"/> Side slopes required (parallel to parking spaces or adjacent to walkways) <input type="radio"/> No side slopes required (perpendicular to parking space or Planter Boxes)				
Bioretention Facility Surface Area				
Depth of Soil Filter Media Layer			$d_S =$	1.5 ft
Top Width of Bioretention Facility, excluding curb			$w_T =$	6.0 ft
Total Effective Depth, d_E $d_E = (0.3) \times d_S + (0.4) \times 1 - (0.7/w_T) + 0.5$			$d_E =$	1.23 ft
Minimum Surface Area, A_m $A_M (ft^2) = \frac{V_{BMP} (ft^3)}{d_E (ft)}$			$A_M =$	779 ft ²
Proposed Surface Area			$A =$	888 ft ²
Bioretention Facility Properties				
Side Slopes in Bioretention Facility			$z =$	4 :1
Diameter of Underdrain				6 inches
Longitudinal Slope of Site (3% maximum)				1 %
6" Check Dam Spacing				25 feet
Describe Vegetation:				
Notes:				

Bioretention Facility - Design Procedure		BMP ID SWALE F	Legend:	Required Entries
				Calculated Cells
Company Name:	ALLIANCE		Date:	
Designed by:	SRL		County/City Case No.:	
Design Volume				
Enter the area tributary to this feature			$A_T =$	0.37 acres
Enter V_{BMP} determined from Section 2.1 of this Handbook			$V_{BMP} =$	725 ft ³
Type of Bioretention Facility Design				
<input checked="" type="radio"/> Side slopes required (parallel to parking spaces or adjacent to walkways) <input type="radio"/> No side slopes required (perpendicular to parking space or Planter Boxes)				
Bioretention Facility Surface Area				
Depth of Soil Filter Media Layer			$d_s =$	3.0 ft
Top Width of Bioretention Facility, excluding curb			$w_T =$	6.0 ft
Total Effective Depth, d_E $d_E = (0.3) \times d_s + (0.4) \times 1 - (0.7/w_T) + 0.5$			$d_r =$	1.68 ft
Minimum Surface Area, A_m $A_M (ft^2) = \frac{V_{BMP} (ft^3)}{d_E (ft)}$			$A_M =$	431 ft ²
Proposed Surface Area			$A =$	486 ft ²
Bioretention Facility Properties				
Side Slopes in Bioretention Facility			$z =$	4 :1
Diameter of Underdrain				6 inches
Longitudinal Slope of Site (3% maximum)				1 %
6" Check Dam Spacing				25 feet
Describe Vegetation:				
Notes:				

Appendix 7: Hydromodification

Supporting Detail Relating to compliance with the Hydromodification Performance Standards

Santa Margarita Region - County HydroMod Iterative Spreadsheet Model

Only for use the unincorporated portions of Riverside County, unless otherwise approved by the Co-Permittee

Development Project Number(s):		Rain Gauge	Temecula Valley
Latitude (decimal format):	33.6033	BMP Type (per WQMP):	Biofiltration
Longitude (decimal format):	-117.1566	BMP Number (Sequential):	Basin A1 & A2

Pre-Development - Hydrology Information

Pre-Development	DRAINAGE AREA (ACRES) - 10 acre max ¹	8.86	2-YEAR, 1-HOUR INTENSITY (IN/HR) - Plate D-4.3	0.53
	LONGEST WATERCOURSE (FT) - 1,000' max ¹	585	10-YEAR, 1-HOUR INTENSITY (IN/HR) - Plate D-4.1	1.66
	UPSTREAM ELEVATION OF WATERCOURSE (FT)	1504	SLOPE OF THE INTENSITY DURATION - Plate D-4.6	0.56
	DOWNSTREAM ELEV. OF WATERCOURSE (FT)	1477	CLOSEST IMPERVIOUS PERCENTAGE (%)	0% Undeveloped - Poor Cover
	EXISTING IMPERVIOUS PERCENTAGE (%)	0		
	Use 10% of Q2 to avoid Field Screening requirements	Yes		

Pre-Development - Soils Information

Cover Type #	Subarea Acreage	Cover Type	Vegetative Cover	Soil A %	Soil B %	Soil C %	Soil D %	RI Index AMC I	RI Index AMC II	RI Index AMC III
1	8.86 Ac.	Barren	- Cover		50	50		76	89	96
								0	0	0
								0	0	0
	8.86 Ac.							Weighted Average RI Numbers = 76.0 89.0 96.0		

Per Dr. Luis Parra, the AMC condition is based on the rainfall record. Applying NEH-4 (1964) for the non-freezing conditions in Riverside County the AMC conditions are: AMC-I for less than 0.5" of rain the previous 5 days; AMC-II for between 0.5" to 1.1" of rain the previous 5 days; or AMC-III for more than 1.1" for the previous 5 days.

Pre-Development - Calculated Range of Flow Rates analyzed for Hydromod (Suceptible Range of Flows)

Pre-Development	Calculated Upper Flow-rate limit	Calculated Lower Flow-rate limit
	Ex. 10-year Flowrate ¹ = 12.712 cfs	Ex. 10% of the 2-year Flowrate ¹ = 0.899 cfs
	(Co-Permittee Approval is required) User-Defined Discharge Values with accompanying Hydrology Study¹	
	Ex. 10-year Flowrate (Attach Study) = <input type="text"/> cfs	Ex. 2-year Flowrate (Attach Study) = <input type="text"/> cfs

¹The equations used to determine the 10-year and 10% of the 2-yr are limited to 10-acres and 1,000'. Flowrates from a separate study can be used to over-ride the calculated values so that larger areas (up to 20 acres) and longer watercourse lengths can be used. All values still need to be filled out, even when there is a user-defined discharge value entered.

Post-Project - Hydrograph Information

Post-Project	DRAINAGE AREA (ACRES)	8.86	Go to "BMP Design" tab to design your BMP, then check results below. Print both this "HydroMod" Sheet and the "BMP Design" sheet for your submittal.
	LONGEST WATERCOURSE (FT)	920	
	DIFFERENCE IN ELEV (FT) - along watercourse	14	
	PROPOSED IMPERVIOUS PERCENTAGE (%)	82	

Post-Project - Soils Information

Cover Type #	Subarea Acreage	Cover Type	Vegetative Cover	Soil A %	Soil B %	Soil C %	Soil D %	RI Index AMC I	RI Index AMC II	RI Index AMC III
22	8.86 Ac.	Urban Landscaping	Good Cover		50	50		43	63	80
								0	0	0
								0	0	0
	8.86 Ac.							Weighted Average RI Numbers = 43.0 63.0 80.0		

Per Dr. Luis Parra, the AMC condition is based on the rainfall record. Applying NEH-4 (1964) for the non-freezing conditions in Riverside County the AMC conditions are: AMC-I for less than 0.5" of rain the previous 5 days; AMC-II for between 0.5" to 1.1" of rain the previous 5 days; or AMC-III for more than 1.1" for the previous 5 days.

Results	Hydromod Poneded depth	2.00 feet	First result out of compliance in the rainfall record			See below for the Height in the Basin (Stage) that is causing a non-compliant result
	Hydromod Drain Time (unlogged)	60.78 hours	Requirement	Proposed		
	Is the HydroMod BMP properly sized?	Yes, this is acceptable	---	---	---	
	Mitigated Q < 110% of Pre-Dev. Q?	Yes, this is acceptable	---	---	---	Issue @ Stage -
	Mitigated Duration < 110% of Pre-Dev.?	Yes, this is acceptable	---	---	---	Issue @ Stage -

Responsible-in-charge:

Date:


Signature:

Spreadsheet Developed by: Benjie Cho, P.E.

PROPOSED BMP DIMENSIONS

STEP1: Size the BMP, so that the Total Volume > Max HydroMod Vol. (Deeper is ok, it will be refined in the Design Geometry)



Is the BMP a Tank shape? 1 for yes; 2 for no.



Basin Shaped BMP (Bottom Stage 1st)

Bottom Stage	H=	2.0'	SS=	2	:	1
Top Area		Bottom Area				
Width	98	Width	90	FT		
Length	73	Length	65	FT		
area =	7154	area =	5850			

Top Stage H= 0.0'



Prop. Top Stg. Vol. =	-	FT3
Prop Bottom Stg Vol =	12,982	FT3
Total Prop. Volume ¹ =	12,982	FT3
Max HydroMod Volume =	12,951	FT3
Total Acreage ² =	5,100	FT2
BMP % of Site =	1.32%	
Max HydroMod Depth ³ =	2.00	FT

¹Does not include forebay, or low flow trench

²Does not account for freeboard or access roads

³Does not consider Increased Runoff

Stage (FT)	Storage (AC-FT)	Storage (FT3)	Q (CFS)
0	0	0	0
0.10	0.014	588	0.02
0.20	0.027	1182	0.07
0.30	0.041	1783	0.14
0.40	0.055	2390	0.21
0.50	0.069	3003	0.25
0.60	0.083	3623	0.29
0.70	0.098	4249	0.32
0.80	0.112	4881	0.35
0.90	0.127	5520	0.37
1.00	0.142	6165	0.40
1.10	0.157	6817	0.42
1.20	0.172	7476	0.44
1.30	0.187	8141	0.46
1.40	0.202	8812	0.48
1.50	0.218	9490	0.50
1.60	0.234	10175	0.52
1.70	0.249	10867	0.54
1.80	0.266	11566	0.55
1.90	0.282	12271	0.57
2.00	0.298	12983	0.59

MINIMUM DESIGN GEOMETRY

STEP3: Delete outlets, then propose the largest lowest orifice that does not, exceed the ex. Q or Duration. If the Q is acceptable, but the duration is exceeded, try decreasing orifice, then adding a weir slightly below the stage that has an issue.

OUTLETS (for Stage-Discharge)

Orifice Outlets			Weir Outlets		
Invert Height (ft)	Diameter (Inches)	No. of Orifices	Crest Height (ft)	Crest Width (ft)	No. of Weirs
0	4.00	1			

HydroMod Depth = 2.00 FT
+ 1' Freeboard = 3.00 FT

Top Surface Area

Based on HydroMod Depth +1' of Freeboard

Bottom Stage	
Width	98 FT
Length	73 FT

0.298 12,983

STEP4: Complete an increased runoff analysis, if the project can impact downstream properties. Incorporate these designs into the WQMP site plan.

Add emergency overflow weir, for flows that exceed the HydroMod volumes, sized to the 100-year peak flow rate. Add access roads (< 10% longitudinal slope) with enough width & turn around access for equipment that would be needed to scarify the bottom or remove Bioretention soil media.

Add Infiltration

Enter information from actual infiltration tests

Yes	Consider Infiltration (Yes or No)?	
5	Infiltration rate (in/hr) ³	0.6771 ft3/sec, Infiltration (over entire bottom)
4	Factor of Safety (3 or greater) ³	0.1693 ft3/sec, Infiltration / Factor of Safety
120	mins, Max. Time represented by tests	

³Per the RC LID Manual, Appendix A.

Only if allowed by the Co-Permittee, these infiltration inputs can be used to simulate Bioretention/Biofiltration rates with Backup Calcs and Data.

FYI, the spreadsheet does not count the duration under the susceptible flowrate. So there are circumstances where as the outlet sizes increases the duration increases as well. That is because some of the flow duration that wasn't counted because it was too low, is now counted, or the compliance check is jumping to the next out of compliance record with different duration exceedance values.

Results	HydroMod Ponded depth		First result out of compliance in the record		See below for the Height in the Basin (Stage) that is causing a non-compliant result
	Requirement	Proposed	Requirement	Proposed	
	HydroMod Drain Time (unclogged)	60.78 hours	---	---	
	HydroMod BMP properly sized?	Yes, this is acceptable	---	---	
	Mit. Q < 110% of Pre-Dev. Q?	Yes, this is acceptable	---	---	Issue @ Stage = ---
	Mit. Duration < 110% of Pre-Dev?*	Yes, this is acceptable	---	---	Issue @ Stage = ---

Santa Margarita Region - County HydroMod Iterative Spreadsheet Model

Only for use the unincorporated portions of Riverside County, unless otherwise approved by the Co-Permittee

Development Project Number(s):		Rain Gauge	Temecula Valley
Latitude (decimal format):	33.6033	BMP Type (per WQMP):	Biofiltration
Longitude (decimal format):	-117.1666	BMP Number (Sequential):	Basin B

Pre-Development - Hydrology Information

DRAINAGE AREA (ACRES) - 10 acre max ¹	4.81	2-YEAR, 1-HOUR INTENSITY (IN/HR) - Plate D-4.3	0.53
LONGEST WATERCOURSE (FT) - 1,000' max ¹	435	10-YEAR, 1-HOUR INTENSITY (IN/HR) - Plate D-4.1	2.13
UPSTREAM ELEVATION OF WATERCOURSE (FT)	1505	SLOPE OF THE INTENSITY DURATION - Plate D-4.6	0.56
DOWNSTREAM ELEV. OF WATERCOURSE (FT)	1475	CLOSEST IMPERVIOUS PERCENTAGE (%)	0% Undeveloped - Poor Cover
EXISTING IMPERVIOUS PERCENTAGE (%)	0		
Use 10% of Q2 to avoid Field Screening requirements	Yes		

Pre-Development - Soils Information

Cover Type #	Subarea Acreage	Cover Type	Vegetative Cover	Soil A %	Soil B %	Soil C %	Soil D %	RI Index AMC I	RI Index AMC II	RI Index AMC III
1	4.81 Ac.	Barren	- Cover		50	50		76	89	96
								0	0	0
								0	0	0
	4.81 Ac.							Weighted Average RI Numbers = 76.0 89.0 96.0		

Per Dr. Luis Parra, the AMC condition is based on the rainfall record. Applying NEH-4 (1964) for the non-freezing conditions in Riverside County the AMC conditions are: AMC-I for less than 0.5" of rain the previous 5 days; AMC-II for between 0.5" to 1.1" of rain the previous 5 days; or AMC-III for more than 1.1" for the previous 5 days.

Pre-Development - Calculated Range of Flow Rates analyzed for Hydromod (Suceptible Range of Flows)

Calculated Upper Flow-rate limit				Calculated Lower Flow-rate limit			
Ex. 10-year Flowrate ¹ =	8.963	cfs		Ex. 10% of the 2-year Flowrate ¹ =	0.552	cfs	
(Co-Permittee Approval is required) User-Defined Discharge Values with accompanying Hydrology Study¹							
Ex. 10-year Flowrate (Attach Study) =		cfs		Ex. 2-year Flowrate (Attach Study) =		cfs	

¹The equations used to determine the 10-year and 10% of the 2-yr are limited to 10-acres and 1,000'. Flowrates from a separate study can be used to over-ride the calculated values so that larger areas (up to 20 acres) and longer watercourse lengths can be used. All values still need to be filled out, even when there is a user-defined discharge value entered.

Post-Project - Hydrograph Information

DRAINAGE AREA (ACRES)	4.81	Go to "BMP Design" tab to design your BMP, then check results below. Print both this "HydroMod" Sheet and the "BMP Design" sheet for your submittal.
LONGEST WATERCOURSE (FT)	756	
DIFFERENCE IN ELEV (FT) - along watercourse	24	
PROPOSED IMPERVIOUS PERCENTAGE (%)	83	

Post-Project - Soils Information

Cover Type #	Subarea Acreage	Cover Type	Vegetative Cover	Soil A %	Soil B %	Soil C %	Soil D %	RI Index AMC I	RI Index AMC II	RI Index AMC III
22	8.86 Ac.	Urban Landscaping	Good Cover		50	50		43	63	80
								0	0	0
								0	0	0
	8.86 Ac.							Weighted Average RI Numbers = 43.0 63.0 80.0		

Per Dr. Luis Parra, the AMC condition is based on the rainfall record. Applying NEH-4 (1964) for the non-freezing conditions in Riverside County the AMC conditions are: AMC-I for less than 0.5" of rain the previous 5 days; AMC-II for between 0.5" to 1.1" of rain the previous 5 days; or AMC-III for more than 1.1" for the previous 5 days.

Results	Hydromod Ponded depth	1.40 feet	First result out of compliance in the rainfall record				See below for the Height in the Basin (Stage) that is causing a non-compliant result	
	Hydromod Drain Time (unclogged)	31.31 hours	Requirement		Proposed			
	Is the HydroMod BMP properly sized?	Yes, this is acceptable	---	---	---	---	---	---
	Mitigated Q < 110% of Pre-Dev. Q?	Yes, this is acceptable	---	---	---	---	---	---
	Mitigated Duration < 110% of Pre-Dev.?	Yes, this is acceptable	---	---	---	---	---	---

Responsible-in-charge:

Date: _____

Signature: _____

0.1 feet, Stage Intervals


Larger intervals may incr. the Q at the bottom stg.

Stage-Storage-Discharge*

PROPOSED BMP DIMENSIONS

STEP1: Size the BMP, so that the Total Volume > Max HydroMod Vol. (Deeper is ok, it will be refined in the Design Geometry)



Is the BMP a Tank shape? 2 1 for yes; 2 for no.



Basin Shaped BMP (Bottom Stage 1st)

Bottom Stage	H=	1.5'	SS=	2	:	1
Top Area		Bottom Area				
Width	51	Width	45	FT		
Length	116	Length	110	FT		
area =	5916	area =	4950			

Top Stage H= 0.0'



Stage (FT)	Storage (AC-FT)	Storage (FT3)	Q (CFS)
0	0	0	0
0.10	0.011	498	0.02
0.20	0.023	1002	0.07
0.30	0.035	1513	0.14
0.40	0.047	2030	0.21
0.50	0.059	2553	0.25
0.60	0.071	3083	0.29
0.70	0.083	3619	0.32
0.80	0.096	4161	0.35
0.90	0.108	4710	0.37
1.00	0.121	5265	0.40
1.10	0.134	5827	0.42
1.20	0.147	6396	0.44
1.30	0.160	6971	0.46
1.40	0.173	7552	0.48
1.50	0.187	8140	0.50

Prop. Top Stg. Vol. =	-	FT3
Prop Bottom Stg Vol =	8,139	FT3
Total Prop. Volume ¹ =	8,139	FT3
Max HydroMod Volume =	7,051	FT3
Total Acreage ² =	5,100	FT2
BMP % of Site =	2.43%	
Max HydroMod Depth ³ =	1.40	FT

¹Does not include forebay, or low flow trench
²Does not account for freeboard or access roads
³Does not consider Increased Runoff

MINIMUM DESIGN GEOMETRY

STEP3: Delete outlets, then propose the largest lowest orifice that does not, exceed the ex. Q or Duration. If the Q is acceptable, but the duration is exceeded, try decreasing orifice, then adding a weir slightly below the stage that has an issue.

OUTLETS (for Stage-Discharge)

Orifice Outlets			Weir Outlets		
Invert Height (ft)	Diameter (inches)	No. of Orifices	Crest Height (ft)	Crest Width (ft)	No. of Weirs
0	4.00	1			

HydroMod Depth = 1.40 FT
 + 1' Freeboard = 2.40 FT

Top Surface Area
 Based on HydroMod Depth + 1' of Freeboard

Bottom Stage	
Width	51 FT
Length	116 FT

STEP4: Complete an increased runoff analysis, if the project can impact downstream properties. Incorporate these designs into the WQMP site plan. Add emergency overflow weir, for flows that exceed the HydroMod volumes, sized to the 100-year peak flow rate. Add access roads (< 10% longitudinal slope) with enough width & turn around access for equipment that would be needed to scarify the bottom or remove Bioretention soil media.

Add Infiltration

Enter information from actual infiltration tests

Yes	Consider Infiltration (Yes or No)?		
5	Infiltration rate (in/hr) ³	0.5729	ft3/sec, Infiltration (over entire bottom)
4	Factor of Safety (3 or greater) ³	0.1432	ft3/sec, Infiltration / Factor of Safety
120	mins, Max. Time represented by tests		

Only if allowed by the Co-Permittee, these infiltration inputs can be used to simulate Bioretention/Biofiltration rates with Backup Calcs and Data.

³Per the RC LID Manual, Appendix A.

FYI, the spreadsheet does not count the duration under the susceptible flowrate. So there are circumstances where as the outlet sizes increases the duration increases as well. That is because some of the flow duration that wasn't counted because it was too low, is now counted, or the compliance check is jumping to the next out of compliance record with different duration exceedance values.

Results

HydroMod Ponded depth	1.40 feet	First result out of compliance in the record		See below for the Height in the Basin (Stage) that is causing a non-compliant result	
HydroMod Drain Time (unclogged)	31.31 hours	Requirement	Proposed		
HydroMod BMP properly sized?	Yes, this is acceptable	---	---	---	---
Mit. Q < 110% of Pre-Dev. Q?	Yes, this is acceptable	---	---	---	Issue @ Stage = ---
Mit. Duration < 110% of Pre-Dev.?	Yes, this is acceptable	---	---	---	Issue @ Stage = ---

Appendix 8: Source Control

Pollutant Sources/Source Control Checklist

Appendix 9: O&M

Operation and Maintenance Plan and Documentation of Finance, Maintenance and Recording Mechanisms

Appendix 10: Educational Materials

BMP Fact Sheets, Maintenance Guidelines and Other End-User BMP Information