



**Drainage Study for
3100 52nd Avenue – Parking Lot
Expansion**

Level 3 Analysis

Design Review No. DRCP2022-00053

Vertical Datum: NAVD88

July 6, 2022

Prepared for:

*LBA Realty
3347 Michelson Drive, Suite 200
Irvine, CA 92612*

Prepared by:

*Stantec Consulting Services Inc.
38 Technology Drive, Suite 200
Irvine, CA 92618*



Table of Contents

1.0	INTRODUCTION	1
1.1	EXISTING SITE DESCRIPTION.....	1
1.2	PROPOSED SITE DESCRIPTION.....	1
2.0	PROPOSED SITE IMPROVEMENTS	5
3.0	METHODOLOGY	5
3.1	HYDROLOGY.....	5
3.1.1	Existing Condition Hydrology.....	5
3.1.2	Proposed Condition Hydrology.....	5
3.2	HYDRAULICS.....	5
4.0	DRAINAGE SHEDS – EXISTING CONDITION	6
4.1	NOLTE METHOD DESIGN RUNOFF.....	6
5.0	DRAINAGE SHEDS – PROPOSED CONDITION	6
5.1	NOLTE METHOD DESIGN RUNOFF.....	6
6.0	DRAINAGE SHEDS - LOW IMPACT DEVELOPMENT (LID)	7
7.0	HYDROMODIFICATION	7
8.0	STORMWATER QUALITY	8
9.0	TRASH CAPTURE	8
10.0	CONCLUSION	8
11.0	APPENDIX A – EXISTING CONDITION NOLTE METHOD DESIGN RUNOFF	10
12.0	APPENDIX B – PROPOSED CONDITION NOLTE METHOD DESIGN RUNOFF	11
13.0	APPENDIX C – LID/SWQ/TRASH CAPTURE EXHIBIT & LID CREDIT CALCULATION WORKSHEET	12
14.0	APPENDIX D – PRELIMINARY GRADING PLAN & OVERLAND RELEASE PATH	13

LIST OF FIGURES

Figure 1-1: Vicinity Map.....	2
Figure 1-2: Location Map.....	3
Figure 1-3: Site Plan.....	4



1.0 INTRODUCTION


1.1 EXISTING SITE DESCRIPTION

The 3100 52nd Avenue project is located south of Sacramento within unincorporated area of Sacramento County. The project is bounded by an industrial building to the north, railroad tracks to the west, residential mobile home park to the south, and industrial development to the east. The project site is approximately 1.80 acres, see Figures 1-1 and 1-2. Currently, 52nd Avenue is flanked with industrial developments. For purposes of this drainage study, the existing condition development will be considered an industrial land use, and as such, the existing storm drain system was designed for this purpose. The site is relatively flat with a grade change of roughly 3 feet. The project site is predominantly composed of clay and is assigned to hydrologic soil group D, according to the Web Soil Survey provided by the Natural Resources Conservation Service.

1.2 PROPOSED SITE DESCRIPTION

The proposed project will consist of a parking lot for tractor trailers. Pedestrian and vehicular access to the project site will be from 52nd Avenue, see Figure 1-3. The existing striping will be removed on the existing offsite asphalt pavement at the northerly boundary of the project. The existing private 12" storm drain onsite will remain in place and continue to convey stormwater runoff from the existing building roof drain to the north. Proposed onsite storm drain infrastructure will connect to the existing 12" storm drain. The proposed development land use will be industrial. The existing offsite developments to the north and east of the project site have industrial land uses as well.

The purpose of this drainage report is to assess the stormwater impact of the proposed project on the existing storm drain and comply with Sacramento County drainage and stormwater quality criteria.



PROJECT SITE



VICINITY MAP

NOT TO SCALE

FIGURE 1-1

PREPARED BY:



Stantec

38 TECHNOLOGY DRIVE, SUITE 200
IRVINE, CA 92618
949.923.6000 stantec.com


PREPARED FOR:

LBA REALTY

3347 MICHELSON DRIVE, SUITE 200
IRVINE, CA

VICINITY MAP

3100 52ND AVENUE



PREPARED BY:




Stantec
38 TECHNOLOGY DRIVE, SUITE 200
IRVINE, CA 92618
949.923.6000 stantec.com

PREPARED FOR:

LBA REALTY
3347 MICHELSON DRIVE, SUITE 200
IRVINE, CA

LOCATION MAP
3100 52ND AVENUE



PREPARED BY:

Stantec
38 TECHNOLOGY DRIVE, SUITE 200
IRVINE, CA 92618
949.923.6000 stantec.com

PREPARED FOR:

LBA REALTY
3347 MICHELSON DRIVE, SUITE 200
IRVINE, CA

SITE PLAN
3100 52ND AVENUE

2.0 PROPOSED SITE IMPROVEMENTS

The proposed grading for the project site will generally be flat. Approximately two-thirds of the project site will have a parking lot for tractor trailers. The surface gradient for this area will be uniform and slope in one direction.

Stormwater will sheet flow across the parking lot and will be intercepted by curb and gutter. The curb and gutter will convey the stormwater to a bioretention basin. The outlet pipe from the bioretention basin will connect to the existing private 12" storm drain system onsite.

The bioretention basin will treat the required amount of stormwater while allowing higher stormwater flow rates to bypass treatment. The bioretention basin will have a 24" square grated inlet with the inlet grate elevated 12" above the basin bottom. See Appendix C LID & SWQ Treatment exhibit for the grated inlet configuration of the bioretention basin. The inlet will intercept and allow the higher flow rates to bypass treatment. The treated stormwater will be intercepted by perforated pipe within the basin's gravel layer and conveyed to the invert of the grated inlet.

3.0 METHODOLOGY

3.1 HYDROLOGY

3.1.1 Existing Condition Hydrology

The Nolte Method was utilized for the analysis of the existing storm drain system. An industrial land use was designated for the existing condition development. Sacramento County Figure 2-5 was used to determine the Nolte Method design runoff. The project site resides in Zone 2.

3.1.2 Proposed Condition Hydrology

The Nolte Method was utilized for the analysis of the existing and proposed storm drain systems. An industrial land use was designated for the proposed condition development. Sacramento County Figure 2-5 was used to determine the Nolte Method design runoff for the offsite area (value per existing condition hydrology) and the SacCalc program was used for determining the onsite Nolte Method design runoff. The project site resides in Zone 2.

3.2 HYDRAULICS

Hydraulic calculations will be included in the Level 4 drainage study.

4.0 DRAINAGE SHEDS – EXISTING CONDITION

4.1 NOLTE METHOD DESIGN RUNOFF

The project site is one drainage shed, E1, and overland flows to an offsite area between the project's westerly property line and the existing railroad tracks. It is assumed to be tributary to the existing public 60" storm drain system. However, it is unknown where the drainage flow is intercepted by the 60" storm drain, see Appendix A for Nolte Method Runoff Existing Condition exhibit. One offsite drainage shed, O1, is also tributary to the existing 60" storm drain system. This drainage shed represents the roof area of the existing building. The roof area is directly tributary to the existing onsite private 12" storm drain that connects downstream to the existing 60" storm drain system. Drainage shed O1 has an industrial land use designation. Sacramento County Figure 2-5 was used to determine the Nolte Method design runoff for drainage sheds E1 and O1. Table 4-1 below summarizes the runoff for the drainage sheds.

Table 4-1 Drainage Shed Runoff Flow Rates

Drainage Shed	Drainage Shed Area (acres)	Nolte Method Design Runoff, Q_N (cfs)
E1	1.80	0.90
O1	0.20	0.10

5.0 DRAINAGE SHEDS – PROPOSED CONDITION

5.1 NOLTE METHOD DESIGN RUNOFF

The project site is one drainage shed, P1, and will have storm drain to convey the Nolte Method runoff flow rate to the existing private 12" storm drain onsite. See Appendix B for Nolte Method Runoff Proposed Condition exhibit. The offsite drainage shed, O1, will continue to be tributary to the existing onsite 12" storm drain. This drainage shed represents the roof area of the existing building. The SacCalc program was used for determining the onsite Nolte Method design runoff for drainage shed P1. Table 5-1 below summarizes the runoff for the drainage sheds. Table 5-2 summarizes the runoff at the onsite private junction.

Table 5-1 Drainage Shed Runoff Flow Rates

Drainage Shed	Drainage Shed Area (acres)	Nolte Method Design Runoff, Q_N (cfs)
P1	1.80	0.87
O1	0.20	0.10

Table 5-2 Runoff Flow Rate at Onsite Private Junction

Drainage Sheds Tributary to Junction	Total Tributary Area (acres)	Nolte Method Design Runoff, Q_N (cfs)
P1 & O1	2.00	0.97

6.0 DRAINAGE SHEDS - LOW IMPACT DEVELOPMENT (LID)

The project site is one drainage shed for low impact development design purposes. The drainage shed is P1, see Appendix C for Low Impact Development (LID) exhibit. The LID Credit Calculation Worksheet for commercial projects, from the Stormwater Quality Design Manual (SQDM) for the Sacramento Region and as modified by the Department of Water Resources, was utilized to calculate the LID points for the drainage shed. The project site must reach a total of 100 points to satisfy the SQDM requirements for new development. The drainage shed points are weighted against the total project site area. Table 6-1 below summarizes the LID points and the weighted points for the drainage shed.

Table 6-1 Drainage Shed LID Points and Weighted Points

Drainage Shed	Drainage Shed Area (acres)	Percentage (%) of Total Project Site Area	LID Points	Weighted Points
P1	1.80	100%	118	118
TOTALS	1.80	100.00%		118.0

The weighted LID points add up to 118 total points. Therefore, the project site meets the requirements of the SQDM for LID implementation.

7.0 HYDROMODIFICATION

According to the latest Applicability Map from the Sacramento Stormwater Quality Partnership website, the project site resides in an area exempt for hydromodification analysis. Therefore, no hydromodification analysis was performed.

8.0 STORMWATER QUALITY

Source control measures and treatment control measures are required per the SQDM. Both types of measures are to be implemented to prevent pollutants from reaching municipal storm drain systems or local waterways. The LID Credit Calculation Worksheet for commercial projects calculates LID points and required stormwater quality treatment flow rates/volumes for drainage sheds. The LID worksheet will let the user know if stormwater quality treatment has been satisfied or if additional treatment is necessary. Table 8-1 below summarizes the stormwater treatment required for the drainage shed.

Table 8-1 Drainage Shed Stormwater Quality Treatment

Drainage Shed	Treatment Required	Treatment Provided	Treatment Control Measure	Treatment Control Measure Sizing
P1	0.096 ac-ft	0.096 ac-ft	Bioretention basin	2,269 sq-ft (10' x 227') with 12" gravel depth

The drainage shed satisfies the LID worksheet for stormwater quality treatment (see Appendix C). Drainage shed P1 has a bioretention basin for treatment control measures. The drainage shed will have the following source control measures: efficient irrigation and landscaping.

9.0 TRASH CAPTURE

Trash particles that are 5mm or larger in size are required to be captured during a 1-year, 1-hour storm event and not allowed to enter the municipal storm drain systems or local waterways.

Drainage shed P1 has a bioretention basin. The bioretention basin will have a 24" square grated inlet structure fitted with a screening device to provide full trash capture. The screening device will be bolted to the wall of the inlet structure at the opening of the outlet pipe.

10.0 CONCLUSION

The Nolte Method design stormwater runoff rates for the existing and proposed conditions will be nearly identical. However, the proposed condition runoff is anticipated to be slightly less than the existing condition runoff.



For the 100-yr storm event, the existing and proposed conditions have the same overland release discharge point from the project site. The proposed parking lot and existing building finish floor elevation are well above the ponding water surface elevation expected to occur onsite during a 100-yr storm event. Therefore, the maximum flooding depth possible within the parking area is less than 1 foot.

CONCLUSION

The LID credit points calculated for the project site exceed the minimum 100 points. The project site resides in an area exempt for hydromodification analysis. Therefore, no hydromodification analysis was performed. Stormwater quality treatment will be provided by a bioretention basin. A trash capture device will be installed in the outlet structure of the bioretention basin.

11.0 APPENDIX A – EXISTING CONDITION NOLTE METHOD DESIGN RUNOFF

DRAWING: u:\2042633000\drawing\exhibit_files\633000c-ex7004.dwg PLOTTED: 7/6/2022 1:11 PM BY: McLeilan, Mark



PREPARED BY:



Stantec
38 TECHNOLOGY DRIVE, SUITE 200
IRVINE, CA 92618
949.923.6000 stantec.com

PREPARED FOR:

LBA REALTY
3347 MICHELSON DRIVE, SUITE 200
IRVINE, CA

**NOLTE METHOD RUNOFF
EXISTING CONDITION
3100 52ND AVENUE**

DATE: **6/28/2022**


SHEET **1**

OF **1**

JOB NO. **2042 633000**

12.0 APPENDIX B – PROPOSED CONDITION NOLTE METHOD DESIGN RUNOFF

DRAWING: u:\2042633000\drawing\exhibit_files\633000c-ex7005.dwg PLOTTED: 7/6/2022 1:55 PM BY: McLeilan, Mark




O1
0.20 ACRES
INDUSTRIAL
Q_N = 0.10 CFS

P1
1.80 ACRES
INDUSTRIAL
Q_N = 0.87 CFS

EXISTING 10' WIDE
STORM DRAIN EASEMENT
JUNCTION P1 & O1
2.00 ACRES
INDUSTRIAL
Q_N = 0.97 CFS

24" GRATE INLET
12" ABOVE BASIN BOTTOM
19.00 TC
15.50 INV.

(20.7) FG
OVERLAND RELEASE
CONTROL POINT
100-YR STORM EVENT



PREPARED BY:



Stantec
38 TECHNOLOGY DRIVE, SUITE 200
IRVINE, CA 92618
949.923.6000 stantec.com

PREPARED FOR:

LBA REALTY
3347 MICHELSON DRIVE, SUITE 200
IRVINE, CA

**NOLTE METHOD RUNOFF
PROPOSED CONDITION
3100 52ND AVENUE**

DATE:
6/29/2022

SHEET **1**
OF **1**

JOB NO. **2042 633000**

Nolte method results
(Project: 3100 52nd Avenue Nolte Flows - Proposed Condition)
(Hydrologic zone 2)

ID	Drainage area (acres)	Impervious area (%)	Design Q (cfs)
P1	1.80	85.00	0.87

Sacramento Hydrologic Calculator Report

June 29, 2022 14:26

Project Title: 3100 52nd Avenue Nolte Flows - Proposed Condition
 Comments: Nolte Method for proposed condition drainage shed P1
 Prepared by: mbm

Method: Nolte method
 Date: 6/29/2022




Watershed Hydrologic Summary Data

Watershed	Area (acres)	Area Percent											
		Given as	90	85	80	75	70	60	50	40	30	25	20
P1	1.8	fraction		1									

Refer to the Drainage manual for Land Use Impervious Area Percent

13.0 APPENDIX C – LID/SWQ/TRASH CAPTURE EXHIBIT & LID CREDIT CALCULATION WORKSHEET

DRAWING: u:\2042633000\drawing\exhibit_files\633000c-ex7006.dwg PLOTTED: 7/6/2022 2:07 PM BY: McLeilan, Mark



PREPARED BY:

38 TECHNOLOGY DRIVE, SUITE 200
 IRVINE, CA 92618
 949.923.6000 stantec.com

PREPARED FOR:

LBA REALTY
 3347 MICHELSON DRIVE, SUITE 200
 IRVINE, CA

**LID & SWQ TREATMENT
 PROPOSED CONDITION**
 3100 52ND AVENUE

DATE:
6/23/2022

SHEET **1**
 OF **1**

JOB NO. **2042 633000**

This portion is to use a variable depth of gravel below the underdrain

A new worksheet is being done to consider this.

1:1 points for pervious + WQV

RED text is calculated

50% = 100 points
(max 200 points)

$C=0.95$
 $i=0.18 \text{ in/hr}$
 $A= AAT$

Shed	Watershed (AC)	Pervious (AC)	Contributes to runoff		Points for pervious (1:1 ratio)	Depth of gravel below underdrain (in)	Ponding Depth (in)	*Infiltrated (ac) Assumed 0.40 void space	*Treated (ac)	Points for Bioretention Infiltration	TOTAL LID points	% of site	Weighted LID points	AAT	Flow = CiA	Adjusted Area for Flow-Based, Non-LID Treatment	Additional Flow that needs to be treated (cfs)	Additional treatment required?	WQV (ac-ft) Pnot=0.64 in*
			Impervious (AC)	Bioretention Area (sq ft)															
P1	1.80	0.77	0.98	2,269	42.8	12	12	0.391	0.977	75.7	118.5	100%	118.5	-0.337		-0.058	no	0.096	
Sub-total		0.77		1.03															
Totals		1.80										100%	118						


*chart in Appendix E for 12-hr drawdown - assumed 100% impervious since the pervious area is already being credited

14.0 APPENDIX D – PRELIMINARY GRADING PLAN & OVERLAND RELEASE PATH

DRAWING: ut:\2042633000\drawing\exhibit_files\633000c-ex7007.dwg PLOTTED: 7/6/2022 12:43 PM BY: McElion, Mark

EXISTING BUILDING
3100 52ND AVENUE

APN: 041-0092-001




EXIST. 10' WIDE DRAINAGE ESMT.
SACRAMENTO COUNTY

RAILROAD TRACKS

UNDEVELOPED LAND

BRUSH

NANCY LANE



PREPARED BY:



Stantec
38 TECHNOLOGY DRIVE, SUITE 200
IRVINE, CA 92618
949.923.6000 stantec.com

PREPARED FOR:

LBA REALTY
3347 MICHELSON DRIVE, SUITE 200
IRVINE, CA

PRELIMINARY GRADING PLAN
TRAILER PARKING LOT EXPANSION
3100 52ND AVENUE

DATE:	6/24/2022
SHEET	1
OF	1

JOB NO. 2042 633000